



Material Safety Data Sheet

Copyright, 2010, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M™ High Power Brake Cleaner PN 08179

MANUFACTURER: 3M

DIVISION: Automotive Aftermarket

ADDRESS: 3M Center
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 08/05/10

Supersedes Date: 01/18/10

Document Group: 27-8886-7

Product Use:

Intended Use: Automotive

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
ACETONE	67-64-1	60 - 100
XYLENE	1330-20-7	7 - 13
HYDROTREATED LIGHT NAPHTHA (PETROLEUM)	64742-49-0	7 - 13
CARBON DIOXIDE	124-38-9	3 - 7
ETHYLBENZENE	100-41-4	0 - 3
TOLUENE	108-88-3	0 - 0.1
BENZENE	71-43-2	0 - 0.01

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Aerosol

Odor, Color, Grade: Water white liquid acetone odor

General Physical Form: Liquid

Immediate health, physical, and environmental hazards: Flammable liquid and vapor. Flammable liquefied gas. Aerosol container contains flammable gas under pressure. Closed containers exposed to heat from fire may build pressure and explode.

Extremely flammable liquid and vapor. Vapors may travel long distances along the ground or floor to an ignition source and flash back. Aerosol container contains flammable material under pressure. May cause severe eye irritation. May cause target organ effects. Contains a chemical or chemicals which can cause birth defects or other reproductive harm. Contains a chemical or chemicals which can cause cancer.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Inhalation:

Intentional concentration and inhalation may be harmful or fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Prolonged or repeated exposure may cause:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Class Description</u>	<u>Regulation</u>
BENZENE	71-43-2	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
BENZENE	71-43-2	Known human carcinogen	National Toxicology Program Carcinogens
BENZENE	71-43-2	Cancer hazard	OSHA Carcinogens
ETHYLBENZENE	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature	No Data Available
Flash Point	> 0 °F
Flammable Limits - LEL	No Data Available
Flammable Limits - UEL	No Data Available

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Flammable liquid and vapor. Flammable liquefied gas. Closed containers exposed to heat from fire may build pressure and explode. Extremely flammable liquid and vapor. Vapors may travel long distances along the ground

or floor to an ignition source and flash back. Aerosol container contains flammable material under pressure.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available.

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard.

Environmental procedures

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Clean-up methods

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Cover spill area with a fire-extinguishing foam designed for use on solvents, such as alcohols and acetone, that can dissolve in water. An AR - AFFF type foam is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS. Seal the container.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Ground containers securely when transferring contents. Wear low static or properly grounded shoes. Do not pierce or burn container, even after use. No smoking while handling this material. Do not spray near flames or sources of ignition. Avoid breathing of vapors, mists or spray. Aerosol container contains flammable gas under pressure. Avoid static discharge. Avoid eye contact with vapors, mists, or spray. Avoid contact with oxidizing agents.

7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container tightly closed. Do not store containers on their sides. Store away from oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Do not use in a confined area or areas with little or no air movement. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Indirect Vented Goggles

.

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Butyl Rubber

Polyethylene/Ethylene Vinyl Alcohol

.

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges

. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Do not ingest.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
ACETONE	ACGIH	TWA	500 ppm	
ACETONE	ACGIH	STEL	750 ppm	
ACETONE	OSHA	TWA	2400 mg/m3	
BENZENE	ACGIH	TWA	0.5 ppm	Skin Notation*
BENZENE	ACGIH	STEL	2.5 ppm	Skin Notation*
BENZENE	OSHA	TWA	1 ppm	29 CFR 1910.1028
BENZENE	OSHA	STEL	5 ppm	29 CFR 1910.1028
BENZENE	OSHA	TWA	10 ppm	
BENZENE	OSHA	CEIL	25 ppm	
CARBON DIOXIDE	ACGIH	TWA	5000 ppm	
CARBON DIOXIDE	ACGIH	STEL	30000 ppm	
CARBON DIOXIDE	OSHA	TWA	9000 mg/m3	
ETHYLBENZENE	ACGIH	TWA	100 ppm	
ETHYLBENZENE	ACGIH	STEL	125 ppm	
ETHYLBENZENE	CMRG	TWA	25 ppm	
ETHYLBENZENE	CMRG	STEL	75 ppm	
ETHYLBENZENE	OSHA	TWA	435 mg/m3	
HYDROTREATED LIGHT NAPHTHA (PETROLEUM)	CMRG	TWA	50 ppm	
TOLUENE	ACGIH	TWA	20 ppm	
TOLUENE	CMRG	STEL	75 ppm	Skin Notation*
TOLUENE	OSHA	TWA	200 ppm	
TOLUENE	OSHA	CEIL	300 ppm	
XYLENE	ACGIH	TWA	100 ppm	
XYLENE	ACGIH	STEL	150 ppm	

XYLENE	CMRG	TWA	50 ppm
XYLENE	CMRG	STEL	75 ppm
XYLENE	OSHA	TWA	435 mg/m3

* Substance(s) refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Aerosol
Odor, Color, Grade:	Water white liquid acetone odor
General Physical Form:	Liquid
Autoignition temperature	<i>No Data Available</i>
Flash Point	> 0 °F
Flammable Limits - LEL	<i>No Data Available</i>
Flammable Limits - UEL	<i>No Data Available</i>
Boiling point	133 - 290 °F
Density	0.775 g/ml
Vapor Density	>=1 g/cm3 [<i>Ref Std: AIR=1</i>]
Vapor Pressure	<i>No Data Available</i>
Specific Gravity	0.775 g/cm3
pH	<i>No Data Available</i>
Melting point	<i>No Data Available</i>
Solubility In Water	<i>No Data Available</i>
Evaporation rate	<=1 [<i>Ref Std: ETHER=1</i>]
Kow - Oct/Water partition coef	<i>No Data Available</i>
Percent volatile	100 %
Viscosity	<i>No Data Available</i>

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

Heat

Sparks and/or flames

10.2 Materials to avoid

Strong acids

Strong bases

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of waste product in a permitted hazardous waste facility.
Facility must be capable of handling aerosol cans. Dispose of empty product containers in a sanitary landfill.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable), D018 (Benzene)

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

ID Number(s):

60-4550-5116-3, 60-4550-5397-9

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
ETHYLBENZENE	100-41-4	0 - 3
XYLENE	1330-20-7	7 - 13

STATE REGULATIONS

Contact 3M for more information.

CALIFORNIA PROPOSITION 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Classification</u>
BENZENE	71-43-2	*Male reproductive toxin
BENZENE	71-43-2	**Carcinogen
BENZENE	71-43-2	*Developmental Toxin
ETHYLBENZENE	100-41-4	**Carcinogen
TOLUENE	108-88-3	*Female reproductive toxin
TOLUENE	108-88-3	*Developmental Toxin

* WARNING: contains a chemical or chemicals which can cause birth defects or other reproductive harm.

** WARNING: contains a chemical which can cause cancer.

CHEMICAL INVENTORIES

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.
--

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 **Flammability:** 4 **Reactivity:** 0 **Special Hazards:** None
Aerosol Storage Code: 2

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 2 **Flammability:** 4 **Reactivity:** 0 **Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS(r)) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS(r) ratings are to be used with a fully implemented HMIS(r) program. HMIS(r) is a registered mark of the National Paint and Coatings Association (NPCA).

Revision Changes:

Section 8: Eye/face protection information was modified.
Section 8: Skin protection - recommended gloves information was modified.
Section 8: Respiratory protection - recommended respirators information was modified.
Section 14: Transportation legal text was modified.
Section 1: Initial issue message was modified.
Section 14: ID Number(s) Template 1 was modified.
Section 2: Ingredient table was modified.
Section 8: Exposure guidelines ingredient information was modified.
Section 3: Carcinogenicity table was modified.
Section 10: Materials to avoid physical property was modified.
Section 10: Conditions to avoid physical property was modified.
Section 6: Environmental procedures heading was added.
Section 6: Personal precautions heading was added.
Section 6: Clean-up methods heading was added.
Section 6: Release measures heading was deleted.
Section 8: Exposure guidelines legend was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com