

20442, 20444 SPECIAL TEC B FE 5W-30 1L, 5L

Liqui Moly GmbH

Chemwatch Hazard Alert Code: 2

Chemwatch: 39-47202

Issue Date: 05/07/2019

Version No: 3.1.1.1

Print Date: 08/07/2019

Safety Data Sheet according to WHMIS 2015 requirements

S.GHS.CAN.EN

SECTION 1 IDENTIFICATION

Product Identifier

Product name	20442, 20444 SPECIAL TEC B FE 5W-30 1L, 5L
Synonyms	Not Available
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	Use according to manufacturer's directions.
--------------------------	---

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Liqui Moly GmbH
Address	Jerg-Wieland-Strasse 4 Ulm D-89081 Germany
Telephone	+49 731 1420 0
Fax	+49 731 1420 82
Website	http://www.liqui-moly.com/
Email	Not Available

Emergency phone number

Association / Organisation	INFOTRAC
Emergency telephone numbers	+1800 535 5053 (US, Canada & Mexico)
Other emergency telephone numbers	+1 352 323 3500 (International)

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

CANADIAN WHMIS SYMBOLS



Classification	Skin Sensitizer Category 1
----------------	----------------------------

Label elements

Hazard pictogram(s)	
---------------------	--

SIGNAL WORD	WARNING
-------------	----------------

Hazard statement(s)

H317	May cause an allergic skin reaction.
------	--------------------------------------

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P261	Avoid breathing mist/vapours/spray.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s) Response

P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501	Dispose of contents/container in accordance with local regulations.
-------------	---

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**Substances**

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
72623-87-1.	>50	<u>lubricating oils, petroleum C20-50, hydrotreated neutral</u>
64742-54-7.	10-20	<u>paraffinic distillate, heavy, hydrotreated (severe)</u>
Not Available	10-20	<u>mineral oil</u>
68784-31-6	1-5	<u>zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate</u>
722503-69-7	<1	<u>methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium</u>

SECTION 4 FIRST-AID MEASURES**Description of first aid measures**

Eye Contact	<p>If this product comes in contact with eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with water. ▶ If irritation continues, seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	<ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

- ▶ Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing skin disorders may be aggravated by exposure to this product.
- ▶ In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases.
- ▶ High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

NOTE: Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

SECTION 5 FIRE-FIGHTING MEASURES**Extinguishing media**

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Special protective equipment and precautions for fire-fighters

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear full body protective clothing with breathing apparatus.
----------------------	---

	<ul style="list-style-type: none"> ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ Use water delivered as a fine spray to control fire and cool adjacent area.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Combustible. ▶ Slight fire hazard when exposed to heat or flame. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ On combustion, may emit toxic fumes of carbon monoxide (CO). <p>Combustion products include: carbon dioxide (CO₂) phosphorus oxides (PO_x) sulfur oxides (SO_x) other pyrolysis products typical of burning organic material. May emit corrosive fumes.</p> <p>CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.</p>

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<p>Slippery when spilt.</p> <ul style="list-style-type: none"> ▶ Remove all ignition sources. ▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes. ▶ Control personal contact with the substance, by using protective equipment.
Major Spills	<p>Slippery when spilt. Moderate hazard.</p> <ul style="list-style-type: none"> ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> ▶ DO NOT allow clothing wet with material to stay in contact with skin ▶ Electrostatic discharge may be generated during pumping - this may result in fire. ▶ Ensure electrical continuity by bonding and grounding (earthing) all equipment. ▶ Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/sec until fill pipe submerged to twice its diameter, then ≤ 7 m/sec). ▶ Avoid splash filling. ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps.
Other information	<ul style="list-style-type: none"> ▶ Store in original containers. ▶ Keep containers securely sealed. ▶ No smoking, naked lights or ignition sources. ▶ Store in a cool, dry, well-ventilated area.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▶ Metal can or drum ▶ Packaging as recommended by manufacturer. ▶ Check all containers are clearly labelled and free from leaks.
Storage incompatibility	<p>CARE: Water in contact with heated material may cause foaming or a steam explosion with possible severe burns from wide scattering of hot material. Resultant overflow of containers may result in fire.</p> <ul style="list-style-type: none"> ▶ Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	lubricating oils, petroleum C20-50, hydrotreated neutral	Oil mist, mineral	5 mg/m ³	10 mg/m ³	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	lubricating oils, petroleum C20-50, hydrotreated neutral	Oil mist - mineral	5 mg/m ³	10 mg/m ³	Not Available	TLV Basis: lung. As sampled by method that does not collect vapor.


Canada - Alberta Occupational Exposure Limits	lubricating oils, petroleum C20-50, hydrotreated neutral	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	lubricating oils, petroleum C20-50, hydrotreated neutral	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	lubricating oils, petroleum C20-50, hydrotreated neutral	Not Available	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	lubricating oils, petroleum C20-50, hydrotreated neutral	Mineral oil (mist)	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	lubricating oils, petroleum C20-50, hydrotreated neutral	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	lubricating oils, petroleum C20-50, hydrotreated neutral	Oil mist - mineral, severely refined	1 mg/m3	Not Available	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	lubricating oils, petroleum C20-50, hydrotreated neutral	Mineral oil, excluding metal working fluids - Pure, highly and severely refined	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	paraffinic distillate, heavy, hydrotreated (severe)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	paraffinic distillate, heavy, hydrotreated (severe)	Oil mist - mineral	5 mg/m3	10 mg/m3	Not Available	TLV Basis: lung. As sampled by method that does not collect vapor.
Canada - Alberta Occupational Exposure Limits	paraffinic distillate, heavy, hydrotreated (severe)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	paraffinic distillate, heavy, hydrotreated (severe)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	paraffinic distillate, heavy, hydrotreated (severe)	Not Available	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	paraffinic distillate, heavy, hydrotreated (severe)	Mineral oil (mist)	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	paraffinic distillate, heavy, hydrotreated (severe)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	paraffinic distillate, heavy, hydrotreated (severe)	Oil mist - mineral, severely refined	1 mg/m3	Not Available	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	paraffinic distillate, heavy, hydrotreated (severe)	Mineral oil, excluding metal working fluids - Pure, highly and severely refined	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	mineral oil	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	mineral oil	Oil mist - mineral	5 mg/m3	10 mg/m3	Not Available	TLV Basis: lung. As sampled by method that does not collect vapor.
Canada - Alberta Occupational Exposure Limits	mineral oil	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	mineral oil	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	mineral oil	Not Available	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	mineral oil	Mineral oil (mist)	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	mineral oil	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	mineral oil	Oil mist - mineral, severely refined	1 mg/m3	Not Available	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	mineral oil	Mineral oil, excluding metal working fluids - Pure, highly and severely refined	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
20442, 20444 SPECIAL TEC B FE 5W-30 1L, 5L	Not Available	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
lubricating oils, petroleum C20-50, hydrotreated neutral	2,500 mg/m ³	Not Available
paraffinic distillate, heavy, hydrotreated (severe)	2,500 mg/m ³	Not Available
mineral oil	2,500 mg/m ³	Not Available
zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate	Not Available	Not Available
methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium	Not Available	Not Available

Exposure controls

Appropriate engineering controls	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p>
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber <p>NOTE:</p> <ul style="list-style-type: none"> ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care.</p>
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none"> ▶ Overalls. ▶ P.V.C. apron. ▶ Barrier cream.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Brown colour liquid with characteristic odour; not miscible with water.		
Physical state	Liquid	Relative density (Water = 1)	0.86
Odour	Not Available	Partition coefficient n-octanol / water	Not Available

Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	-39	Viscosity (cSt)	63.1 @ 40C. 10.63 @ 100C
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	230	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Inhalation hazard is increased at higher temperatures. Not normally a hazard due to non-volatile nature of product. Inhalation of oil droplets or aerosols may cause discomfort and may produce chemical inflammation of the lungs.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The liquid may be able to be mixed with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives. Open cuts, abraded or irritated skin should not be exposed to this material. The material may accentuate any pre-existing dermatitis condition. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Oil may contact the skin or be inhaled. Extended exposure can lead to eczema, inflammation of hair follicles, pigmentation of the face and warts on the soles of the feet.

20442, 20444 SPECIAL TEC B FE 5W-30 1L, 5L	TOXICITY	IRRITATION
	Not Available	Not Available
lubricating oils, petroleum C20-50, hydrotreated neutral	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
	Inhalation (rat) LC50: >5.3 mg/l4 h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	Oral (rat) LD50: >5000 mg/kg ^[2]	
paraffinic distillate, heavy, hydrotreated (severe)	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
	Inhalation (rat) LC50: >5.3 mg/l4 h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	Oral (rat) LD50: >2000 mg/kg ^[2]	
mineral oil	TOXICITY	IRRITATION
	Not Available	Not Available

zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >5000 mg/kg ^[1] Oral (rat) LD50: 2900 mg/kg ^[1]	Eye: adverse effect observed (irritating) ^[1] Skin: no adverse effect observed (not irritating) ^[1]
methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium	TOXICITY	IRRITATION
	Not Available	Not Available

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

PARAFFINIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE)	The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.
MINERAL OIL	Toxicity and Irritation data for petroleum-based mineral oils are related to chemical components and vary as does the composition and source of the original crude. A small but definite risk of occupational skin cancer occurs in workers exposed to persistent skin contamination by oils over a period of years. This risk has been attributed to the presence of certain polycyclic aromatic hydrocarbons (PAH) (typified by benz[a]pyrene). Petroleum oils which are solvent refined/extracted or severely hydrotreated, contain very low concentrations of both.
ZINC BIS(SEC-BUTYL AND 1,3-DIMETHYLBUTYL) DITHIOPHOSPHATE	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. Dithiophosphate alkyl esters is corrosive and toxic to the tissues on skin or oral exposure depending on its concentration. Symptoms included diarrhoea, skin and gastrointestinal irritation, lethargy, reduced food intake, staining about the nose and eye; occasionally, there was drooping of the eyelid, hair standing up, inco-ordination and salivation. Toxicity is reduced following inhalation (due to vapour pressure and high viscosity). It may produce reproductive, developmental and genetic toxicity on experimental animals, but no substantive data is available to establish effect on humans.
METHYL-C20-26-ALKYLBENZENESULFONIC ACID, BRANCHED, CALCIUM	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. For alkaryl sulfonate petroleum additives: Acute toxicity: Existing data indicates relatively low acute toxicity. Animal testing suggested diarrhea and reduced food intake, which is consistent with the detergents in an oil-based vehicle having an irritating effect on the gastrointestinal tract. Subchronic toxicity: Existing data suggests minimal toxicity after chronic exposure by mouth. Repeated skin contact and inhalation in animals caused injury to the skin and the lungs, respectively. Linear alkyl benzene sulfonates are derived from strong corrosive acids. Animal testing has shown they can cause skin reactions, eye irritation, sluggishness, passage of frequent watery stools, weakness and may lead to death. They may also react with surfaces of the mouth and intestines, depending on the concentration exposed to. There is no evidence of harm to the unborn baby or tendency to cause cancer.
LUBRICATING OILS, PETROLEUM C20-50, HYDROTREATED NEUTRAL & PARAFFINIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE)	The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives; The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since: <ul style="list-style-type: none"> The adverse effects of these materials are associated with undesirable components, and The levels of the undesirable components are inversely related to the degree of processing; Distillate base oils receiving the same degree or extent of processing will have similar toxicities; The potential toxicity of residual base oils is independent of the degree of processing the oil receives. The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing. Unrefined & mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and have shown the highest potential cancer-causing and mutation-causing activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components. For highly and severely refined distillate base oils: In animal studies, the acute, oral, semilethal dose is >5g/kg body weight and the semilethal dose by skin contact is >2g/kg body weight. The semilethal concentration for inhalation is 2.18 to >4 mg/L. The materials have varied from "non-irritating" to "moderately irritating" when tested for skin and eye irritation. Testing for sensitisation has been negative.
ZINC BIS(SEC-BUTYL AND 1,3-DIMETHYLBUTYL) DITHIOPHOSPHATE & METHYL-C20-26-ALKYLBENZENESULFONIC ACID, BRANCHED, CALCIUM	No significant acute toxicological data identified in literature search.

Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✗	Reproductivity	✗
Serious Eye Damage/Irritation	✗	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
✓ – Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

20442, 20444 SPECIAL TEC B FE 5W-30 1L, 5L	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available

	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	lubricating oils, petroleum C20-50, hydrotreated neutral	LC50	96	Fish	>100mg/L
EC50		48	Crustacea	>10-mg/L	2
NOEC		504	Crustacea	>1mg/L	1
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	paraffinic distillate, heavy, hydrotreated (severe)	LC50	96	Fish	>100mg/L
EC50		48	Crustacea	>10-mg/L	2
EC50		96	Algae or other aquatic plants	>1000mg/L	1
NOEC		504	Crustacea	>1mg/L	1
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	mineral oil	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate	LC50	96	Fish	4.4mg/L
EC50		48	Crustacea	75mg/L	2
EC50		72	Algae or other aquatic plants	240mg/L	2
NOEC		504	Crustacea	0.4mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium	Not Available	Not Available	Not Available	Not Available

Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	
	<ul style="list-style-type: none"> ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ It may be necessary to collect all wash water for treatment before disposal. ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▶ Where in doubt contact the responsible authority. ▶ Recycle wherever possible or consult manufacturer for recycling options. ▶ Consult State Land Waste Authority for disposal. ▶ Bury or incinerate residue at an approved site. ▶ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	
	NO

Land transport (TDG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Continued...

Not Applicable

SECTION 15 REGULATORY INFORMATION**Safety, health and environmental regulations / legislation specific for the substance or mixture**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

LUBRICATING OILS, PETROLEUM C20-50, HYDROTREATED NEUTRAL(72623-87-1.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada - Alberta Occupational Exposure Limits	Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits
Canada - British Columbia Occupational Exposure Limits	Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances
Canada - Manitoba Occupational Exposure Limits	Canada Categorization decisions for all DSL substances
Canada - Northwest Territories Occupational Exposure Limits	Canada Domestic Substances List (DSL)
Canada - Nova Scotia Occupational Exposure Limits	IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO
Canada - Prince Edward Island Occupational Exposure Limits	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	International FOSFA List of Banned Immediate Previous Cargoes

PARAFFINIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE)(64742-54-7.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada - Alberta Occupational Exposure Limits	Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits
Canada - British Columbia Occupational Exposure Limits	Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances
Canada - Manitoba Occupational Exposure Limits	Canada Categorization decisions for all DSL substances
Canada - Northwest Territories Occupational Exposure Limits	Canada Domestic Substances List (DSL)
Canada - Nova Scotia Occupational Exposure Limits	IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO
Canada - Prince Edward Island Occupational Exposure Limits	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
Canada - Prince Edward Island Occupational Exposure Limits - Carcinogens	International FOSFA List of Banned Immediate Previous Cargoes
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	

MINERAL OIL(NOT AVAILABLE) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada - Alberta Occupational Exposure Limits	Canada - Quebec Permissible Exposure Values for Airborne Contaminants
Canada - British Columbia Occupational Exposure Limits	Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits
Canada - Manitoba Occupational Exposure Limits	Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances
Canada - Northwest Territories Occupational Exposure Limits	IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO
Canada - Nova Scotia Occupational Exposure Limits	IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards
Canada - Prince Edward Island Occupational Exposure Limits	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
Canada - Prince Edward Island Occupational Exposure Limits - Carcinogens	International FOSFA List of Banned Immediate Previous Cargoes

ZINC BIS(SEC-BUTYL AND 1,3-DIMETHYLBUTYL) DITHIOPHOSPHATE(68784-31-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada Categorization decisions for all DSL substances	International Air Transport Association (IATA) Dangerous Goods Regulations
Canada Domestic Substances List (DSL)	International Maritime Dangerous Goods Requirements (IMDG Code)
Canada Transport Dangerous Goods - Schedule 1	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations
Canada Transport Dangerous Goods - Schedule 3	

METHYL-C20-26-ALKYLBENZENESULFONIC ACID, BRANCHED, CALCIUM(722503-69-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AICS	No (mineral oil)
Canada - DSL	No (methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; mineral oil)
Canada - NDSL	No (paraffinic distillate, heavy, hydrotreated (severe); methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; mineral oil; lubricating oils, petroleum C20-50, hydrotreated neutral; zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate)
China - IECSC	No (methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; mineral oil)
Europe - EINEC / ELINCS / NLP	No (methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; mineral oil)
Japan - ENCS	No (methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; mineral oil; lubricating oils, petroleum C20-50, hydrotreated neutral)
Korea - KECI	No (methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; mineral oil; zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate)
New Zealand - NZIoC	No (methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; mineral oil)
Philippines - PICCS	No (methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; mineral oil)
USA - TSCA	No (methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; mineral oil)
Taiwan - TCSI	No (mineral oil)
Mexico - INSQ	No (methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; mineral oil; lubricating oils, petroleum C20-50, hydrotreated neutral; zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate)
Vietnam - NCI	No (methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; mineral oil; zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate)
Russia - ARIPS	No (paraffinic distillate, heavy, hydrotreated (severe); methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; mineral oil; lubricating oils, petroleum C20-50, hydrotreated neutral; zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate)
Thailand - TECI	No (paraffinic distillate, heavy, hydrotreated (severe); methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; mineral oil; lubricating oils, petroleum C20-50, hydrotreated neutral; zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate)

Continued...

Legend:

Yes = All CAS declared ingredients are on the inventory

No = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	05/07/2019
Initial Date	04/07/2019

SDS Version Summary

Version	Issue Date	Sections Updated
3.1.1.1	05/07/2019	Acute Health (eye), Acute Health (inhaled), Acute Health (skin), Acute Health (swallowed), Advice to Doctor, Chronic Health, Classification, Disposal, Engineering Control, Environmental, Fire Fighter (extinguishing media), Fire Fighter (fire/explosion hazard), Fire Fighter (fire fighting), Fire Fighter (fire incompatibility), First Aid (eye), First Aid (inhaled), First Aid (skin), First Aid (swallowed), Handling Procedure, Ingredients, Instability Condition, Personal Protection (other), Personal Protection (Respirator), Personal Protection (eye), Personal Protection (hands/feet), Spills (major), Spills (minor), Storage (storage incompatibility), Storage (storage requirement), Storage (suitable container), Transport, Name

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average
 PC – STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit,
 IDLH: Immediately Dangerous to Life or Health Concentrations
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.