

## SAFETY DATA SHEET

### Basecoat WB 308NB Orange (Red) Metallic

#### Section 1. Identification

**GHS product identifier** : Basecoat WB 308NB Orange (Red) Metallic  
**Other means of identification** :

**Relevant identified uses of the substance or mixture and uses advised against**  
 : FOR INDUSTRIAL USE ONLY

**Supplier/Manufacturer** : Akzo Nobel Coatings, Inc.  
 1845 Maxwell  
 Troy, MI, 48084  
 USA  
 (800) 618-1010

**Canadian Supplier** : Akzo Nobel Coatings Ltd.  
 110 Woodbine Downs Blvd.  
 Unit #4 Etobicoke, Ontario  
 Canada M9W 5S6  
 +1 (800) 618-1010

**Emergency telephone number** : CHEMTREC +1 (800) 424-9300 (Inside the US)  
 CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls accepted)

**Date of issue / Date of revision** : 23 April 2019  
**Safety Data Sheet Version** : 13.11  
**Date of printing** : 23 April 2019

Akzo Nobel Coatings Inc. encourages and expects you to read and understand this entire MSDS, as there is important information throughout the document. Further, Akzo Nobel Coatings Inc. expects you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

To promote safe handling, each customer or recipient should: 1) Notify its employees, agents, contractors, and others whom it knows or believes will use this material of the information contained in this MSDS and any other information regarding hazards and safety; 2) Furnish this same information to each of its customers for the product; 3) Request its customers to notify their employees, customers, and other users of the product of this information; and 4) Notify its employees, agents, contractors, and others that the precautions identified for this product and any other products with which mixtures may be created are transferable and cumulative to the mixture.

#### Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 3  
 EYE IRRITATION - Category 2A  
 CARCINOGENICITY - Category 1A

#### GHS label elements

## Section 2. Hazards identification

Hazard pictograms :



**Signal word** : Danger

**Hazard statements** : Flammable liquid and vapor.  
Causes serious eye irritation.  
May cause cancer.

### Precautionary statements

**Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Wash hands thoroughly after handling. Ground/bond container and receiving equipment.

**Response** : IF exposed or concerned: Get medical attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

**Storage** : Store locked up. Store in a well-ventilated place. Keep cool.

**Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazards not otherwise classified** : None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

| Ingredient name               | %       | CAS number |
|-------------------------------|---------|------------|
| 2-butoxyethanol               | 40 - 45 | 111-76-2   |
| Aluminium powder (stabilized) | 5 - 10  | 7429-90-5  |
| diron trioxide                | 1 - 5   | 1309-37-1  |
| xylene                        | 1 - 5   | 1330-20-7  |
| 2-dimethylaminoethanol        | 1 - 5   | 108-01-0   |
| ethylbenzene                  | 0 - 1   | 100-41-4   |
| ethanol                       | 0 - 1   | 64-17-5    |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

**Occupational exposure limits, if available, are listed in Section 8.**

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

## Section 4. First aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
halogenated compounds  
metal oxide/oxides

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

## Section 6. Accidental release measures

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name                        | Exposure limits  |
|--|--|
| 2-butoxyethanol                        | <p><b>ACGIH TLV (United States, 3/2015).</b><br/>TWA: 20 ppm 8 hours.</p> <p><b>NIOSH REL (United States, 10/2013).</b><br/><b>Absorbed through skin.</b><br/>TWA: 24 mg/m<sup>3</sup> 10 hours.<br/>TWA: 5 ppm 10 hours.</p> <p><b>OSHA PEL (United States, 2/2013).</b><br/><b>Absorbed through skin.</b><br/>TWA: 240 mg/m<sup>3</sup> 8 hours.<br/>TWA: 50 ppm 8 hours.</p>  |
| Aluminium powder (stabilized)          | <p><b>NIOSH REL (United States, 10/2013).</b><br/>TWA: 5 mg/m<sup>3</sup> 10 hours. Form: Respirable fraction<br/>TWA: 10 mg/m<sup>3</sup> 10 hours. Form: Total</p> <p><b>ACGIH TLV (United States, 3/2015).</b><br/>TWA: 1 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction</p> <p><b>OSHA PEL (United States, 2/2013).</b><br/>TWA: 5 mg/m<sup>3</sup>, (as Al) 8 hours. Form: Respirable fraction<br/>TWA: 15 mg/m<sup>3</sup>, (as Al) 8 hours. Form: Total dust</p> |
| diiron trioxide                        | <p><b>NIOSH REL (United States, 10/2013).</b><br/>TWA: 5 mg/m<sup>3</sup>, (as Fe) 10 hours. Form: Dust and fumes</p> <p><b>ACGIH TLV (United States, 3/2015).</b><br/>TWA: 5 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction</p> <p><b>OSHA PEL (United States, 2/2013).</b><br/>TWA: 10 mg/m<sup>3</sup> 8 hours.</p>  |
| xylene                                 | <p><b>ACGIH TLV (United States, 3/2015).</b><br/>STEL: 651 mg/m<sup>3</sup> 15 minutes.<br/>STEL: 150 ppm 15 minutes.<br/>TWA: 434 mg/m<sup>3</sup> 8 hours.<br/>TWA: 100 ppm 8 hours.</p> <p><b>OSHA PEL (United States, 2/2013).</b><br/>TWA: 435 mg/m<sup>3</sup> 8 hours.<br/>TWA: 100 ppm 8 hours.</p>  |
| 2-dimethylaminoethanol<br>ethylbenzene | <p>None.</p> <p><b>ACGIH TLV (United States, 3/2015).</b><br/>TWA: 20 ppm 8 hours.</p> <p><b>NIOSH REL (United States, 10/2013).</b><br/>STEL: 545 mg/m<sup>3</sup> 15 minutes.<br/>STEL: 125 ppm 15 minutes.<br/>TWA: 435 mg/m<sup>3</sup> 10 hours.<br/>TWA: 100 ppm 10 hours.</p> <p><b>OSHA PEL (United States, 2/2013).</b></p>   |

## Section 8. Exposure controls/personal protection

|         |  |
|---------|--|
| ethanol | <p>TWA: 435 mg/m<sup>3</sup> 8 hours.<br/>TWA: 100 ppm 8 hours.<br/><b>ACGIH TLV (United States, 3/2015).</b><br/>STEL: 1000 ppm 15 minutes.<br/><b>NIOSH REL (United States, 10/2013).</b><br/>TWA: 1900 mg/m<sup>3</sup> 10 hours.<br/>TWA: 1000 ppm 10 hours.<br/><b>OSHA PEL (United States, 2/2013).</b><br/>TWA: 1900 mg/m<sup>3</sup> 8 hours.<br/>TWA: 1000 ppm 8 hours.</p> |
|---------|--|

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## Section 8. Exposure controls/personal protection

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

### Appearance

|   |                       |   |
|---|-----------------------|---|
|   | <b>Physical state</b> | : Liquid.   |
|   | <b>Color</b>          | : Not available.  |
| <b>Odor</b>   |                       | : Not available.  |
| <b>Odor threshold</b>                               |                       | : Not available.  |
| <b>pH</b>   |                       | : Not available.  |
| <b>Melting/freezing point</b>                       |                       | : Not available.  |
| <b>Boiling point</b>                                |                       | : 134°C (273.2°F)   |
| <b>boiling range</b>                                |                       | : Not available.  |
| <b>Flash point</b>                                  |                       | : Closed cup: 49°C (120.2°F)  |
| <b>Evaporation rate</b>                             |                       | : Not available.  |
| <b>Flammability (solid, gas)</b>                    |                       | : Not available.  |
| <b>Upper/lower flammability or explosive limits</b> |                       |   |
|   | <b>Upper:</b>         | : Not determined.   |
|   | <b>Lower:</b>         | : Not determined.   |
| <b>Vapor pressure</b>                               |                       | : Not available.  |
| <b>Vapor density</b>                                |                       | : Not available.  |
| <b>Relative density</b>                             |                       | : 1.064   |
| <b>Density</b>                                      |                       | : 8.88 lbs/gal      1.064 g/cm <sup>3</sup>                         |
| <b>Solubility</b>                                   |                       | : Not available.  |
| <b>Solubility in water</b>                          |                       | : Not available.  |
| <b>Partition coefficient: n-octanol/water</b>       |                       | : Not available.  |
| <b>Auto-ignition temperature</b>                    |                       | : Not available.  |
| <b>Decomposition temperature</b>                    |                       | : Not available.  |
| <b>Viscosity</b>                                    |                       | : Kinematic (room temperature): 20.69 cm <sup>2</sup> /s (2069 cSt) |
| <b>Weight Volatiles</b>                             |                       | : 54.98% (w/w)  |
| <b>Volume Volatiles</b>                             |                       | : 66.49 % (v/v)   |
| <b>Weight Solids</b>                                |                       | : 45.02 % (w/w)   |
| <b>Volume Solids</b>                                |                       | : 33.51 % (v/v)   |
| <b>Regulatory VOC</b>                               |                       | : 4.9 lbs/gal    585 g/l    minus water and exempt solvents         |
| <b>VOC Actual</b>                                   |                       | : 4.9 lbs/gal    585 g/l  |

## Section 10. Stability and reactivity

**Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

**Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

**Incompatible materials** : Reactive or incompatible with the following materials:  
oxidizing materials

**Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name | Result      | Species | Dose        | Exposure |
|-------------------------|-------------|---------|-------------|----------|
| xylene                  | LD50 Oral   | Rat     | 4300 mg/kg  | -        |
| 2-dimethylaminoethanol  | LD50 Oral   | Rat     | 2 g/kg      | -        |
| ethylbenzene            | LD50 Dermal | Rabbit  | >5000 mg/kg | -        |
|                         | LD50 Oral   | Rat     | 3500 mg/kg  | -        |
| ethanol                 | LD50 Oral   | Rat     | 7 g/kg      | -        |

#### Irritation/Corrosion

| Product/ingredient name | Result                   | Species | Score | Exposure                | Observation |
|-------------------------|--------------------------|---------|-------|-------------------------|-------------|
| 2-butoxyethanol         | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 100 milligrams | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 100 milligrams          | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 500 milligrams          | -           |
| xylene                  | Eyes - Mild irritant     | Rabbit  | -     | 87 milligrams           | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 24 hours 5 milligrams   | -           |
|                         | Skin - Mild irritant     | Rat     | -     | 8 hours 60 microliters  | -           |
|                         | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 milligrams | -           |
| 2-dimethylaminoethanol  | Skin - Moderate irritant | Rabbit  | -     | 100 Percent             | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 5 microliters           | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 445 milligrams          | -           |
| ethylbenzene            | Eyes - Severe irritant   | Rabbit  | -     | 500 milligrams          | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 24 hours 15             | -           |

## Section 11. Toxicological information

|         |                          |        |   |   |   |
|---------|--------------------------|--------|---|---|---|
| ethanol | Eyes - Mild irritant     | Rabbit | - | milligrams<br>24 hours 500              | - |
|         | Eyes - Moderate irritant | Rabbit | - | milligrams<br>0.06666667                | - |
|         | Eyes - Moderate irritant | Rabbit | - | minutes 100<br>milligrams<br>100        | - |
|         | Eyes - Severe irritant   | Rabbit | - | microliters<br>500                      | - |
|         | Skin - Mild irritant     | Rabbit | - | milligrams<br>400                       | - |
|         | Skin - Moderate irritant | Rabbit | - | milligrams<br>24 hours 20<br>milligrams | - |

### **Sensitization**

Not available.

### **Mutagenicity**

Not available.

### **Carcinogenicity**

Not available.

### **Classification**

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| 2-butoxyethanol         | -    | 3    | -   |
| diron trioxide          | -    | 3    | -   |
| xylene                  | -    | 3    | -   |
| ethylbenzene            | -    | 2B   | -   |
| ethanol                 | -    | 1    | -   |

### **Reproductive toxicity**

Not available.

### **Teratogenicity**

Not available.

### **Specific target organ toxicity (single exposure)**

Not available.

### **Specific target organ toxicity (repeated exposure)**

Not available.

### **Aspiration hazard**

| Name         | Result                         |
|--------------|--------------------------------|
| ethylbenzene | ASPIRATION HAZARD - Category 1 |

Information on the likely routes of exposure : Not available.

### **Potential acute health effects**

## Section 11. Toxicological information

|                     |   |
|---------------------|---|
| <b>Eye contact</b>  | : Causes serious eye irritation.                    |
| <b>Inhalation</b>   | : No known significant effects or critical hazards. |
| <b>Skin contact</b> | : No known significant effects or critical hazards. |
| <b>Ingestion</b>    | : No known significant effects or critical hazards. |

### **Symptoms related to the physical, chemical and toxicological characteristics**

|                     |  |
|---------------------|--|
| <b>Eye contact</b>  | : Adverse symptoms may include the following:<br>pain or irritation<br>watering<br>redness |
| <b>Inhalation</b>   | : No specific data.  |
| <b>Skin contact</b> | : No specific data.  |
| <b>Ingestion</b>    | : No specific data.  |

### **Delayed and immediate effects and also chronic effects from short and long term exposure**

#### **Short term exposure**

|                                    |                  |
|------------------------------------|------------------|
| <b>Potential immediate effects</b> | : Not available. |
| <b>Potential delayed effects</b>   | : Not available. |

#### **Long term exposure**

|                                    |                  |
|------------------------------------|------------------|
| <b>Potential immediate effects</b> | : Not available. |
| <b>Potential delayed effects</b>   | : Not available. |

#### **Potential chronic health effects**

Not available.

|                              |   |
|------------------------------|---|
| <b>General</b>               | : No known significant effects or critical hazards.                           |
| <b>Carcinogenicity</b>       | : May cause cancer. Risk of cancer depends on duration and level of exposure. |
| <b>Mutagenicity</b>          | : No known significant effects or critical hazards.                           |
| <b>Teratogenicity</b>        | : No known significant effects or critical hazards.                           |
| <b>Developmental effects</b> | : No known significant effects or critical hazards.                           |
| <b>Fertility effects</b>     | : No known significant effects or critical hazards.                           |

### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

| Route | ATE value    |
|-------|--------------|
| Oral  | 8786.2 mg/kg |

## Section 12. Ecological information

### Toxicity

| Product/ingredient name             | Result   | Species                                    | Exposure |
|-------------------------------------|--|--|----------|
| 2-butoxyethanol                     | Acute EC50 >1000 mg/l Fresh water              | Daphnia - Daphnia magna                    | 48 hours |
|                                     | Acute LC50 800000 to 1000000 µg/l Marine water | Crustaceans - Crangon crangon              | 48 hours |
| xylene                              | Acute LC50 1250000 µg/l Marine water           | Fish - Menidia beryllina                   | 96 hours |
|                                     | Acute LC50 8500 µg/l Marine water              | Crustaceans - Palaemonetes pugio           | 48 hours |
| ethylbenzene                        | Acute LC50 13400 µg/l Fresh water              | Fish - Pimephales promelas                 | 96 hours |
|                                     | Acute EC50 4600 µg/l Fresh water               | Algae - Pseudokirchneriella subcapitata    | 72 hours |
|                                     | Acute EC50 3600 µg/l Fresh water               | Algae - Pseudokirchneriella subcapitata    | 96 hours |
|                                     | Acute EC50 2930 to 4400 µg/l Fresh water       | Daphnia - Daphnia magna - Neonate          | 48 hours |
| ethanol                             | Acute LC50 40000 µg/l Marine water             | Crustaceans - Cancer magister - Zoea       | 48 hours |
|                                     | Acute LC50 4200 µg/l Fresh water               | Fish - Oncorhynchus mykiss                 | 96 hours |
|                                     | Acute EC50 17.921 mg/l Marine water            | Algae - Ulva pertusa                       | 96 hours |
|                                     | Acute EC50 2000 µg/l Fresh water               | Daphnia - Daphnia magna                    | 48 hours |
|                                     | Acute LC50 25500 µg/l Marine water             | Crustaceans - Artemia franciscana - Larvae | 48 hours |
|                                     | Acute LC50 42000 µg/l Fresh water              | Fish - Oncorhynchus mykiss                 | 4 days   |
|                                     | Chronic NOEC 4.995 mg/l Marine water           | Algae - Ulva pertusa                       | 96 hours |
|                                     | Chronic NOEC 100 µl/L Fresh water              | Daphnia - Daphnia magna - Neonate          | 21 days  |
| Chronic NOEC 0.375 µl/L Fresh water | Fish - Gambusia holbrooki - Larvae             | 12 weeks                                   |          |

### Persistence and degradability

Not available.

### Bioaccumulative potential

| Product/ingredient name | LogP <sub>ow</sub> | BCF         | Potential |
|-------------------------|--------------------|-------------|-----------|
| 2-butoxyethanol         | 0.81               | -           | low       |
| xylene                  | 3.12               | 8.1 to 25.9 | low       |
| 2-dimethylaminoethanol  | -0.55              | -           | low       |
| ethylbenzene            | 3.6                | -           | low       |
| ethanol                 | -0.35              | -           | low       |

### Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

**Special precautions for user** : Please Note: The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

|                            | DOT<br>Classification  | TDG<br>Classification  | Mexico<br>Classification   | IMDG  | IATA   |
|----------------------------|--|--|--|---|--|
| UN number                  | UN1263   | UN1263   | UN1263   | UN1263  | UN1263   |
| UN proper shipping name    | PAINT  | PAINT  | PAINT  | PAINT   | PAINT  |
| Transport hazard class(es) | 3<br> | 3<br> | 3<br> | 3<br> | 3<br> |
| Packing group              | III  | III  | III  | III   | III  |
| Environmental hazards      | No.  | No.  | No.  | No.   | No.  |

## Section 15. Regulatory information

### U.S. Federal regulations

**United States inventory (TSCA 8b):** All components are listed or exempted.

#### SARA 311/312

**Classification** : Fire hazard  
 Immediate (acute) health hazard  
 Delayed (chronic) health hazard

#### SARA 313

|  | Product name                  | CAS number | %       |
|--|-------------------------------|------------|---------|
| <b>Form R - Reporting requirements</b> | 2-butoxyethanol               | 111-76-2   | 40 - 45 |
|  | Aluminium powder (stabilized) | 7429-90-5  | 5 - 10  |
|  | xylene                        | 1330-20-7  | 1 - 5   |
|  | ethylbenzene                  | 100-41-4   | 0.1 - 1 |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

#### California Prop. 65

**WARNING:** This product contains a chemical known to the State of California to cause cancer.

**WARNING:** This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

| Ingredient name         | Cancer      | Reproductive | No significant risk level | Maximum acceptable dosage level   |
|-------------------------|-------------|--------------|---------------------------|-----------------------------------|
| ethylbenzene<br>toluene | Yes.<br>No. | No.<br>Yes.  | No.<br>No.                | No.<br>7000 µg/day<br>(ingestion) |

### International lists

#### National inventory

**Australia** : All components are listed or exempted.  
**Canada** : All components are listed or exempted.  
**China** : All components are listed or exempted.  
**Europe** : All components are listed or exempted.  
**Japan** : **Japan inventory (ENCS):** At least one component is not listed.  
**Japan inventory (ISHL):** At least one component is not listed.  
**Malaysia** : At least one component is not listed.  
**New Zealand** : All components are listed or exempted.  
**Philippines** : All components are listed or exempted.  
**Republic of Korea** : All components are listed or exempted.  
**Taiwan** : All components are listed or exempted.  
**Turkey** : At least one component is not listed.



## Section 16. Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.