



# LIQUID GOLD GLAZING PUTTY (LGOLD-US)

## Safety Data Sheet LGOLD-US

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/11/2015

Revision date: 06/20/2017

Supersedes: 06/20/2017

Version: 4.1

### DRIVING SURFACE PERFECTION

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product form : Mixture  
Product name : LIQUID GOLD GLAZING PUTTY (LGOLD-US)  
Product group : bodyfiller  
Other means of identification : UP0670

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.3. Details of the supplier of the safety data sheet

###### Supplier

U-POL US Inc  
108 Commerce Way  
Stockertown PA 18083 - USA  
T 1-800-340-7824 - F 1-800-787-5150  
[technical.department@u-pol.com](mailto:technical.department@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

##### 1.4. Emergency telephone number

Emergency number : CHEMTREC - 1-800-424-9300

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### GHS-US classification

Flam. Liq. 3 H226  
Skin Irrit. 2 H315  
Eye Irrit. 2 H319  
Carc. 2 H351  
Repr. 2 H361  
STOT RE 1 H372

##### 2.2. Label elements

###### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS07

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H351 - Suspected of causing cancer  
H361 - Suspected of damaging the unborn child.  
H372 - Causes damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation)

Precautionary statements (GHS-US) :

P202 - Do not handle until all safety precautions have been read and understood.  
P263 - Avoid contact during pregnancy/while nursing.  
P264 - Wash hands thoroughly after handling.  
P280 - Wear eye protection, protective clothing, protective gloves.  
P302+P352 - If on skin: Wash with plenty of soap and water  
P305 - IF IN EYES: Rinse first with plenty of water and if necessary take medical advice  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

# LIQUID GOLD GLAZING PUTTY (LGOLD-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
styrene	(CAS-No.) 100-42-5	23-43	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Repr. 2, H361 STOT RE 1, H372
TITANIUM DIOXIDE	(CAS-No.) 13463-67-7	< 5	Carc. 2, H351
ethylbenzene	(CAS-No.) 100-41-4	< 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapor.
Reactivity	: Flammable liquid and vapor.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment	: Safety glasses. Protective clothing. Gloves.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe vapors, fume. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

# LIQUID GOLD GLAZING PUTTY (LGOLD-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

- For containment : Contain leaking substance. Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, fume. Avoid contact with skin and eyes.  
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.  
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.  
Storage temperature : < 25 °C  
Storage area : Store in a well-ventilated place.  
Special rules on packaging : Keep only in original container.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

LIQUID GOLD GLAZING PUTTY (LGOLD-US)		
ACGIH	Not applicable	
OSHA	Not applicable	
styrene (100-42-5)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	40 ppm
ACGIH	Remark (ACGIH)	CNS impair; URT irr; peripheral
OSHA	Remark (OSHA)	(2) See Table Z-2.
ethylbenzene (100-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	URT irr; kidney dam (nephropathy)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
TITANIUM DIOXIDE (13463-67-7)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
ACGIH	Remark (ACGIH)	LRT irr; A3
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup>

### 8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station.

# LIQUID GOLD GLAZING PUTTY (LGOLD-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment : Gloves. Protective clothing. Safety glasses.



Materials for protective clothing : Impermeable clothing.  
Hand protection : Protective gloves.  
Eye protection : Safety glasses.  
Skin and body protection : Wear suitable protective clothing.  
Respiratory protection : Wear respiratory protection.  
Environmental exposure controls : Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Paste.  
Color : Beige  
Odor : aromatic  
Odor threshold : No data available  
pH : No data available  
Relative evaporation rate (butyl acetate=1) : No data available  
Melting point : Not applicable  
Freezing point : No data available  
Boiling point : No data available  
Flash point : 33 °C  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Flammability (solid, gas) : No data available  
Vapor pressure : No data available  
Relative vapor density at 20 °C : No data available  
Relative density : No data available  
Specific gravity / density : 1.16 - 1.2  
Solubility : insoluble in water. soluble in most organic solvents.  
Log Pow : No data available  
Log Kow : No data available  
Viscosity, kinematic : No data available  
Viscosity, dynamic : 31000 - 41000 cP  
Explosive properties : No data available  
Oxidizing properties : No data available  
Explosion limits : No data available

### 9.2. Other information

VOC content - Regulatory : 214 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapor.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

# LIQUID GOLD GLAZING PUTTY (LGOLD-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>styrene (100-42-5)</b>	
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

<b>ethylbenzene (100-41-4)</b>	
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Suspected of causing cancer.

<b>styrene (100-42-5)</b>	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

<b>ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly carcinogenic to humans

<b>TITANIUM DIOXIDE (13463-67-7)</b>	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Suspected of damaging the unborn child.  
Specific target organ toxicity – single exposure : Not classified  
Specific target organ toxicity – repeated exposure : Causes damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation).  
Aspiration hazard : Not classified  
Symptoms/effects after skin contact : Irritation.  
Symptoms/effects after eye contact : Eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

# LIQUID GOLD GLAZING PUTTY (LGOLD-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.5. Other adverse effects

- Effect on ozone layer : No additional information available
- Effect on the global warming : No known effects from this product.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

- Regional legislation (waste) : Disposal must be done according to official regulations.
- Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Additional information : Flammable vapors may accumulate in the container.

## SECTION 14: Transport information

- In accordance with DOT
- Transport document description : UN1866 Resin solution (flammable), 3, III
- UN-No.(DOT) : UN1866
- Proper Shipping Name (DOT) : Resin solution  
flammable
- Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : III - Minor Danger
- DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.  
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.  
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
- DOT Packaging Bulk (49 CFR 173.xxx) : 242
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L
- DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

### Additional information

- Other information : No supplementary information available.

### ADR

- Transport document description : UN 1866 RESIN SOLUTION, 3, III, (D/E)
- Packing group (ADR) : III
- Class (ADR) : 3 - Flammable liquid
- Hazard identification number (Kemler No.) : 30
- Classification code (ADR) : F1

# LIQUID GOLD GLAZING PUTTY (LGOLD-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (ADR) : 3 - Flammable liquids



Orange plates :

Tunnel restriction code (ADR) : D/E

LQ : 5I

Excepted quantities (ADR) : E1

### Transport by sea

UN-No. (IMDG) : 1866

Proper Shipping Name (IMDG) : RESIN SOLUTION

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : III - substances presenting low danger

### Air transport

UN-No. (IATA) : 1866

Proper Shipping Name (IATA) : Resin solution

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : III - Minor Danger

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

styrene	CAS-No. 100-42-5	23-43%
ethylbenzene	CAS-No. 100-41-4	< 5%
xylene	CAS-No. 1330-20-7	< 5%
phthalic anhydride	CAS-No. 85-44-9	< 5%

#### styrene (100-42-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ : 1000 lb

#### ethylbenzene (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ : 1000 lb

SARA Section 313 - Emission Reporting : 0.1 %

#### TITANIUM DIOXIDE (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. International regulations

#### CANADA

#### styrene (100-42-5)

Listed on the Canadian DSL (Domestic Substances List)

#### ethylbenzene (100-41-4)

Listed on the Canadian DSL (Domestic Substances List)

#### TITANIUM DIOXIDE (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

No additional information available

# LIQUID GOLD GLAZING PUTTY (LGOLD-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 H226  
Skin Irrit. 2 H315  
Eye Irrit. 2 H319  
Repr. 2 H361  
STOT RE 1 H372

Full text of hazard classes and H-statements : see section 16

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

#### 15.2.2. National regulations

<b>styrene (100-42-5)</b>
Listed on IARC (International Agency for Research on Cancer) Listed as carcinogen on NTP (National Toxicology Program) Listed on EPA Hazardous Air Pollutant (HAPS)
<b>ethylbenzene (100-41-4)</b>
Listed on IARC (International Agency for Research on Cancer) Listed on EPA Hazardous Air Pollutant (HAPS)
<b>TITANIUM DIOXIDE (13463-67-7)</b>
Listed on IARC (International Agency for Research on Cancer)

#### 15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

<b>styrene (100-42-5)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	
<b>ethylbenzene (100-41-4)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	54 µg/day

## SECTION 16: Other information

Revision date : 03/10/2017

Full text of H-phrases:

H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity

: 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



# LIQUID GOLD GLAZING PUTTY (LGOLD-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

SDS US UPOL

*For professional use only.*

*The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).*