		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 01/09/2019
		Print Date: 11/24/2020
		SDS Number: R0172415
Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3 ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822386		Version: 2.3

29 CFR 1910.1200 (OSHA HazCom 2012)

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier**

Trade name : Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3  
™ Trademark, Valvoline or its subsidiaries, registered in various countries

<b>Details of the supplier of the safety data sheet</b> Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825)  SDS@valvoline.com	<b>Emergency telephone number</b> 1-800-VALVOLINE (1-800-825-8654)  <b>Regulatory Information Number</b> 1-800-TEAMVAL (1-800-832-6825)  <b>Product Information</b> 1-800-TEAMVAL (1-800-832-6825)
---	---


**SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification**

Flammable liquids : Category 4

Skin irritation : Category 2

**GHS label elements**

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : Combustible liquid.  
Causes skin irritation.

Precautionary Statements : **Prevention:**  
Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
Wash skin thoroughly after handling.  
Wear protective gloves/ eye protection/ face protection.

**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 11/24/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 822386

**Response:**

IF ON SKIN: Wash with plenty of soap and water.  
 If skin irritation occurs: Get medical advice/ attention.  
 Take off contaminated clothing and wash before reuse.  
 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

Store in a well-ventilated place. Keep cool.

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

Static-accumulating flammable liquid.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4	Not a hazardous substance or mixture.	>=30.00 - < 40.00
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	Flam. Liq. 4; H227 Skin Irrit. 2; H315	>=20.00 - < 30.00
RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED	64742-01-4	Not a hazardous substance or mixture.	>=20.00 - < 30.00
Naphtha (petroleum), heavy aromatic	64742-94-5	Asp. Tox. 1; H304	>=1.50 - < 5.00

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
 Show this safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.  
 If unconscious, place in recovery position and seek medical advice.  
 If symptoms persist, call a physician.



**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 11/24/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 822386

- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.  
 If on skin, rinse well with water.  
 Wash contaminated clothing before re-use.  
 If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
 Remove contact lenses.  
 Protect unharmed eye.  
 If eye irritation persists, consult a specialist.
- If swallowed : Do not give milk or alcoholic beverages.  
 Never give anything by mouth to an unconscious person.  
 If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.  
 Causes skin irritation.
- Notes to physician : No hazards which require special first aid measures.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
 Water spray  
 Foam  
 Carbon dioxide (CO2)  
 Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.  
 Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide  
 nitrogen oxides (NOx)  
 Hydrocarbons
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 11/24/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3  
 ™ Trademark, Valvoline or its subsidiaries, registered in various  
 countries  
 822386

- Further information : Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
 Use personal protective equipment.  
 Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
 Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.  
 Suppress (knock down) gases/vapours/mists with a water spray jet.

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : Avoid formation of aerosol.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 Do not breathe vapours/dust.  
 Do not smoke.  
 Container hazardous when empty.  
 Avoid contact with skin and eyes.  
 Smoking, eating and drinking should be prohibited in the application area.  
 For personal protection see section 8.  
 Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
 Observe label precautions.  
 No smoking.

**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 11/24/2020

SDS Number: R0172415

Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 822386

Version: 2.3

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC	64741-88-4	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC	64742-94-5	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed

**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 11/24/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3  
 ™ Trademark, Valvoline or its subsidiaries, registered in various  
 countries  
 822386

into eyes.

- Skin and body protection : Wear as appropriate:  
 Impervious clothing  
 Safety shoes  
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
 Discard gloves that show tears, pinholes, or signs of wear.  
 Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Wash hands before breaks and at the end of workday.  
 When using do not eat or drink.  
 When using do not smoke.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid
- Odour : hydrocarbon-like
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : < -38 °F / < -39 °C
- Boiling point/boiling range : > 356 °F / 180 °C  
 (1013 hPa)
- Flash point : 196 °F / 91 °C
- Evaporation rate : 0.1  
 butyl acetate=1
- Flammability (solid, gas) : No data available
- Flammability (liquids) : Static-accumulating flammable liquid.
- Self-ignition : No data available
- Upper explosion limit / Upper flammability limit : 6.0 %(V)
- Lower explosion limit / Lower flammability limit : 1.0 %(V)
- Vapour pressure : 0.2 mmHg (68 °F / 20 °C)

**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 11/24/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3  
™ Trademark, Valvoline or its subsidiaries, registered in various  
countries  
822386

Relative vapour density : No data available

Relative density : No data available

Density : Average 0.8550 g/cm<sup>3</sup> (68 °F / 20 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 36.8 mm<sup>2</sup>/s (104 °F / 40 °C)

Oxidizing properties : No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.  
None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact

**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 11/24/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3  
™ Trademark, Valvoline or its subsidiaries, registered in various  
countries  
822386

Eye Contact

Ingestion

**Acute toxicity**

Not classified based on available information.

**Components:****Distillates, petroleum, solvent-refined heavy paraffinic:**

Acute oral toxicity : LD50 (Rat): &gt; 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: Not classified as acutely toxic by inhalation  
under GHS.  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Acute oral toxicity : LD50 (Rat): &gt; 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.28 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Assessment: No adverse effect has been observed in acute  
inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: No adverse effect has been observed in acute  
dermal toxicity tests.

**RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Information given is based on data obtained from  
similar substances.

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: Not classified as acutely toxic by inhalation  
under GHS.  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: No adverse effect has been observed in acute  
dermal toxicity tests.

**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 11/24/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3  
 ™ Trademark, Valvoline or its subsidiaries, registered in various  
 countries  
 822386

**Naphtha (petroleum), heavy aromatic:**

Acute oral toxicity : LD50 (Rat): &gt; 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 3,800 mg/m<sup>3</sup>  
 Exposure time: 4 h  
 Test atmosphere: dust/mist  
 Assessment: Not classified as acutely toxic by inhalation  
 under GHS.

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg  
 Assessment: Not classified as acutely toxic by dermal  
 absorption under GHS.

**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Remarks : May cause skin irritation and/or dermatitis.

**Components:****Distillates, petroleum, solvent-refined heavy paraffinic:**

Species : Rabbit  
 Result : No skin irritation

**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Assessment : Irritating to skin.  
 Result : Irritating to skin.

**RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

Species : Rabbit  
 Result : No skin irritation

**Naphtha (petroleum), heavy aromatic:**

Result : Slight, transient irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**Remarks : Vapours may cause irritation to the eyes, respiratory system  
and the skin.**Components:****Distillates, petroleum, solvent-refined heavy paraffinic:**

Species : Rabbit  
 Result : No eye irritation

**RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

Species : Rabbit  
 Result : Slight, transient irritation

**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 11/24/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 822386

**Respiratory or skin sensitisation**

**Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:**

**Distillates, petroleum, solvent-refined heavy paraffinic:**

Test Type : Buehler Test  
 Species : Guinea pig  
 Assessment : Does not cause skin sensitisation.

**RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

Test Type : Buehler Test  
 Species : Guinea pig  
 Assessment : Does not cause skin sensitisation.  
 Method : OECD Test Guideline 406

**Germ cell mutagenicity**

Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Genotoxicity in vitro : Test Type: Ames test  
 Result: negative

**RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

Genotoxicity in vitro : Test Type: Ames test  
 Test system: Salmonella typhimurium  
 Metabolic activation: with and without metabolic activation  
 Result: negative

**Carcinogenicity**

Not classified based on available information.

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 11/24/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 822386

**Components:**

**Distillates, petroleum, solvent-refined heavy paraffinic:**

No aspiration toxicity classification

**RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

No aspiration toxicity classification

**Naphtha (petroleum), heavy aromatic:**

May be fatal if swallowed and enters airways.

**Further information**

**Product:**

Remarks : No data available

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Product:**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

**Components:**

Distillates, petroleum, solvent-refined heavy paraffinic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
 Exposure time: 96 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 203  
 Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
 Exposure time: 48 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
 End point: Growth inhibition  
 Exposure time: 72 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 201

Toxicity to fish (Chronic) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >=

**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 11/24/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3  
 ™ Trademark, Valvoline or its subsidiaries, registered in various  
 countries  
 822386

toxicity) 1,000 mg/l  
 Exposure time: 14 d

Toxicity to daphnia and other : NOEL (Daphnia (water flea)): 10 mg/l  
 aquatic invertebrates Exposure time: 21 d  
 (Chronic toxicity) Test substance: WAF  
 Method: OECD Test Guideline 211

**RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
 Exposure time: 96 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 203

Toxicity to daphnia and other : EL50 (Scud (Gammarus pulex)): > 10,000 mg/l  
 aquatic invertebrates Exposure time: 48 h  
 Test Type: semi-static test  
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
 End point: Growth inhibition  
 Exposure time: 72 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 201

**Persistence and degradability****Components:**

Distillates, petroleum, solvent-refined heavy paraffinic:  
 Biodegradability : Result: Not readily biodegradable.  
 Biodegradation: 2 - 4 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301B

**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Biodegradability : Result: Inherently biodegradable  
 Biodegradation: 58.6 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301F

**RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

Biodegradability : Result: Not readily biodegradable.  
 Biodegradation: 2 - 4 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301B  
 Remarks: Information given is based on data obtained from  
 similar substances.



**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 11/24/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 822386

No data available

**Bioaccumulative potential**

**Components:**

No data available

**Mobility in soil**

**Components:**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : No data available

**Components:**

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Do not dispose of waste into sewer.  
 Do not contaminate ponds, waterways or ditches with chemical or used container.  
 Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
 Dispose of as unused product.  
 Empty containers should be taken to an approved waste handling site for recycling or disposal.  
 Do not re-use empty containers.  
 Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION**

**International transport regulations**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

**U.S. DOT - ROAD**

Not dangerous goods
---------------------

**CFR\_RAIL\_C**

Not dangerous goods
---------------------



**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 11/24/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3  
™ Trademark, Valvoline or its subsidiaries, registered in various countries  
822386

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods

**TDG ROAD\_C**

Not dangerous goods

**TDG RAIL\_C**

Not dangerous goods

**TDG INWT\_C**

Not dangerous goods

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods

**MX\_DG**


Not dangerous goods

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION**

		Page: 15
<b>SAFETY DATA SHEET</b>		Revision Date: 01/09/2019
		Print Date: 11/24/2020
		SDS Number: R0172415
Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3 ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822386		Version: 2.3

**EPCRA - Emergency Planning and Community Right-to-Know Act**

**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Hazard not otherwise classified (physical hazards)  
Skin corrosion or irritation

**California Prop. 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TCSI : Not in compliance with the inventory

**TSCA list**

No substances are subject to TSCA 12(b) export notification requirements.

---

**SECTION 16. OTHER INFORMATION**

**Further information**

Revision Date: 01/09/2019

<b>NFPA:</b>	<b>HMIS III:</b>
--------------	------------------

**SAFETY DATA SHEET**


Revision Date: 01/09/2019

Print Date: 11/24/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 822386



**NFPA Flammable and Combustible Liquids Classification**  
 Combustible Liquid Class IIIA

**Full text of H-Statements**

- H227 Combustible liquid.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.


Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports  
 The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

- ACGIH : American Conference of Industrial Hygienists
- BEI : Biological Exposure Index
- CAS : Chemical Abstracts Service (Division of the American Chemical Society).
- CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
- FG : Food grade
- GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
- H-statement : Hazard Statement
- IATA : International Air Transport Association.

	Page: 17
<b>SAFETY DATA SHEET</b>	Revision Date: 01/09/2019
	Print Date: 11/24/2020
	SDS Number: R0172415
Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3 ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822386	Version: 2.3

IATA-DGR : Dangerous Goods Regulation by the “International Air Transport Association” (IATA).

- ICAO : International Civil Aviation Organization
- ICAO-TI (ICAO) : Technical Instructions by the “International Civil Aviation Organization”
- IMDG : International Maritime Code for Dangerous Goods
- ISO : International Organization for Standardization
- logPow : octanol-water partition coefficient
- LCxx : Lethal Concentration, for xx percent of test population
- LDxx : Lethal Dose, for xx percent of test population.
- ICxx : Inhibitory Concentration for xx of a substance
- Ecxx : Effective Concentration of xx
- N.O.S.: Not Otherwise Specified
- OECD : Organization for Economic Co-operation and Development
- OEL : Occupational Exposure Limit
- P-Statement : Precautionary Statement
- PBT : Persistent , Bioaccumulative and Toxic
- PPE : Personal Protective Equipment
- STEL : Short-term exposure limit
- STOT : Specific Target Organ Toxicity
- TLV : Threshold Limit Value
- TWA : Time-weighted average
- vPvB : Very Persistent and Very Bioaccumulative
- WEL : Workplace Exposure Level

- CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
- DOT : Department of Transportation
- FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
- HMIRC : Hazardous Materials Information Review Commission
- HMIS : Hazardous Materials Identification System
- NFPA : National Fire Protection Association
- NIOSH : National Institute for Occupational Safety and Health
- OSHA : Occupational Safety and Health Administration
- PMRA : Health Canada Pest Management Regulatory Agency
- RTK : Right to Know
- WHMIS : Workplace Hazardous Materials Information System