

SAFETY DATA SHEET

SECTION 1 : IDENTIFICATION

Product identifier used on the label:

Product Name: Seam Sealer (Part 1)
Product Code: 97120A

Other means of identification:

Synonyms: Epoxy Seam Sealer

Recommended use of the chemical and restrictions on use:

Chemical manufacturer address and telephone number:

Manufacturer Name: Saint-Gobain Abrasives, Inc.
Address: 1 New Bond Street
 Worcester, MA 01615
Website: www.Nortonabrasives.com
General Phone Number: 508-795-5000

Emergency phone number:

Emergency Phone Number: 508-795-5000
CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300
Canutec: In Canada, call CANUTEC: (613) 996-6666 (call collect)

SECTION 2 : HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with CFR 1910.1200(d)(f):

GHS Pictograms:



Signal Word: WARNING.

GHS Class: Reproductive toxicity. Category 1B.
 Eye Irritation. Category 2.
 Skin Irritation. Category 2.
 Skin Sensitization. category 1.
 Hazardous to the aquatic environment, short term, acute. category 1.
 Hazardous to the aquatic environment, long-term, chronic. Category 2.

Hazard Statements: H360 - May damage fertility or the unborn child.
 H319 - Causes serious eye irritation.
 H315 - Causes skin irritation.
 H317 - May cause an allergic skin reaction.
 H400 - Very toxic to aquatic life.
 H411 - Toxic to aquatic life with long lasting effects.

Precautionary Statements: P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 - Wash hands thoroughly after handling.
 P272 - Contaminated work clothing should not be allowed out of the workplace.
 P273 - Avoid release to the environment.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 - IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 - IF exposed or concerned: Get medical advice/attention.
 P321 - P332+P313 - If skin irritation occurs: Get medical advice/attention.
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P362+P364 - Take off contaminated clothing and wash it before reuse.
 P391 - Collect spillage.
 P405 - Store locked up.
 P501 - Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.

Hazards not otherwise classified that have been identified during the classification process:

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

Chemical Name	CAS#	Ingredient Percent	EC Num.
---------------	------	--------------------	---------

Bisphenol A Diglycidyl Ether R	25085-99-8	40 - 70 by weight
Butyl Benzyl Phthalate	85-68-7	10 - 30 by weight
Dimethyl Siloxane, Reaction Pr	67762-90-7	3 - 7 by weight
Black Iron Oxide	1317-61-9	0.5 - 1.5 by weight

SECTION 4 : FIRST AID MEASURES

Description of necessary measures:

Eye Contact:	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.
Skin Contact:	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5 : FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:

Suitable Extinguishing Media:	Use carbon dioxide (CO2) or dry chemical when fighting fires involving this material.
Unsuitable extinguishing media:	Water or foam may cause frothing.

Special protective equipment and precautions for fire-fighters:

Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Personal Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.
------------------------------	--

Environmental precautions:

Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
-----------------------------------	---

Methods and materials for containment and cleaning up:

Spill Cleanup Measures:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper personal protective equipment as listed in Section 8.
--------------------------------	---

Reference to other sections:

Other Precautions:	Pump or shovel to storage/salvage vessels.
---------------------------	--

SECTION 7 : HANDLING and STORAGE

Precautions for safe handling:

Handling:	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.
Hygiene Practices:	Wash thoroughly after handling.
Special Handling Procedures:	Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.

Conditions for safe storage, including any incompatibilities:

Storage:	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use.
-----------------	---

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:

Appropriate engineering controls:

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

Individual protection measures:

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.

Skin Protection Description: Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult manufacturer's data for permeability data.

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERTIES:

Physical State: Paste.
Color: black
Odor: Epoxy like odor.
Boiling Point: Not determined.
Melting Point: Not determined.
Specific Gravity: 1.1
Solubility: not soluble in water.
Vapor Density: >1 (air = 1)
Vapor Pressure: Not determined.
Evaporation Rate: <1 (n-Butyl acetate = 1)
Flash Point: >302 °F (>150°C)
Flash Point Method: TCC
Lower Flammable/Explosive Limit: Not determined.
Upper Flammable/Explosive Limit: Not determined.
Auto Ignition Temperature: Not determined.

SECTION 10 : STABILITY and REACTIVITY

Chemical Stability:

Chemical Stability: Stable under normal temperatures and pressures.

Possibility of hazardous reactions:

Hazardous Polymerization: Not reported.

Conditions To Avoid:

Conditions to Avoid: Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions.

Incompatible Materials:

Incompatible Materials: Oxidizers, acids, and chlorinated organic compounds. Reactive metals (e.g. sodium, calcium, zinc). Sodium/calcium hypochlorite. Nitrous acid/ oxide, nitrites. Peroxides. Materials reactive with hydroxyl compounds.

Hazardous Decomposition Products:

Special Decomposition Products: Carbon monoxide, silicone dioxide.

SECTION 11 : TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

SECTION 12 : ECOLOGICAL INFORMATION

SECTION 13 : DISPOSAL CONSIDERATIONS

Description of waste:

SECTION 14 : TRANSPORT INFORMATION

DOT Shipping Name: Non regulated.
DOT UN Number: Non regulated.
IATA Shipping Name: Non regulated.
IATA UN Number: Non regulated.
Canadian Shipping Name: WHMIS Classification: D2B

SECTION 15 : REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:

SECTION 16 : ADDITIONAL INFORMATION

HMIS Ratings:

HMIS Health Hazard: 2*
HMIS Fire Hazard: 1
HMIS Reactivity: 1
HMIS Personal Protection: X

Health Hazard	2*
Fire Hazard	1
Reactivity	1
Personal Protection	X

* Chronic Health Effects

SDS Creation Date: August 09, 2010
SDS Revision Date: December 14, 2015
SDS Revision Notes: GHS Update

Copyright© 1996-2015 Actio Corporation. All Rights Reserved.