



## Material Safety Data Sheet

Copyright, 2014, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**PRODUCT NAME:** 3M™ Impact Resistant Structural Adhesive PNs 07333, 57333  
**MANUFACTURER:** 3M  
**DIVISION:** Automotive Aftermarket  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA  
**Telephone:** 1-888-3M HELPS (1-888-364-3577)

**EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)**

**Issue Date:** 10/13/14  
**Supersedes Date:** 05/19/14  
**Document Group:** 33-5983-3

### ID Number(s):

60-4550-8333-1, 60-4550-8345-5

**This product is a kit or a multipart product which consists of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are:**

33-5988-2, 33-5984-1

### Revision Changes:

Kit: Component document group number(s) information was modified.  
Kit initial issue message information was modified.

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at [www.3M.com](http://www.3M.com)



## Safety Data Sheet

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	33-5984-1	<b>Version Number:</b>	1.03
<b>Issue Date:</b>	12/30/14	<b>Supersedes Date:</b>	10/13/14

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Impact Resistant Structural Adhesive Part A, PNs 07333, 57333

#### Product Identification Numbers

LB-K100-1573-6, LB-K100-1573-7, 41-3588-1330-5

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive, Accelerator for two-part color changing adhesive with optimized shear, peel and impact performance.

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Automotive Aftermarket
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 1.

Skin Corrosion/Irritation: Category 1B.

Skin Sensitizer: Category 1.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Corrosion | Exclamation mark |

##### Pictograms



**Hazard Statements**

Causes severe skin burns and eye damage.  
 May cause an allergic skin reaction.

**Precautionary Statements**

**General:**

Keep out of reach of children.

**Prevention:**

Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wear protective gloves, protective clothing, and eye/face protection.  
 Wash thoroughly after handling.  
 Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Immediately call a POISON CENTER or doctor/physician.  
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF ON SKIN: Wash with plenty of soap and water.  
 Immediately call a POISON CENTER or doctor/physician.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Wash contaminated clothing before reuse.  
 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Hazards not otherwise classified**

May cause chemical gastrointestinal burns. Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

35% of the mixture consists of ingredients of unknown acute oral toxicity.  
 35% of the mixture consists of ingredients of unknown acute dermal toxicity.  
 83% of the mixture consists of ingredients of unknown acute inhalation toxicity.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Epoxy Copolymer (04499600-7155)	Trade Secret*	20 - 40 Trade Secret *
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	10 - 30 Trade Secret *
Acrylic Copolymer	Trade Secret*	0 - 5 Trade Secret *
Aluminum	7429-90-5	5 - 15 Trade Secret *
Methylenedi(Cyclohexylamine)	1761-71-3	1 - 10 Trade Secret *
Synthetic Rubber (04499600-7150)	Trade Secret*	1 - 10 Trade Secret *

Treated Filler (04499600-7152)	Trade Secret*	3 - 7 Trade Secret *
Surface Treated Inorganic Filler (04499600-7151)	Trade Secret*	1 - 5 Trade Secret *
Mineral Filler (04499600-7156)	Trade Secret*	0 - 3 Trade Secret *
Tris(2,4,6-Dimethylaminomonomethyl)phenol	90-72-2	< 5 Trade Secret *
m-Xylene-.alpha.alpha'.Diamine	1477-55-0	0 - 3 Trade Secret *
Polyamide Resin (04499600-7154)	Trade Secret*	< 2 Trade Secret *
Inorganic Filler (04499600-7153)	Trade Secret*	1 - 5 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

#### Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Keep out of reach of children. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
m-Xylene-.alpha.alpha'.Diamine	1477-55-0	ACGIH	CEIL:0.1 mg/m3	Skin Notation
Aluminum	7429-90-5	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
Aluminum	7429-90-5	OSHA	TWA(as Al respirable dust):5 mg/m3;TWA(as Al total dust):15 mg/m3	
Tris(2,4,6-Dimethylaminomonomethyl)phenol	90-72-2	CMRG	TWA:5 ppm	
Inorganic Filler (04499600-7153)	Trade Secret	Manufacturer determined	TWA(as dust):10 mg/m3	
Surface Treated Inorganic Filler (04499600-7151)	Trade Secret	CMRG	CEIL:5 mg/m3	
Surface Treated Inorganic Filler (04499600-7151)	Trade Secret	OSHA	TWA concentration:0.8 mg/m3;TWA:20 millions of particles/cu. ft.	
Treated Filler (04499600-7152)	Trade Secret	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile Rubber

Polyvinyl Alcohol (PVA)

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Boots - Nitrile

Apron – Nitrile

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>General Physical Form:</b>	Liquid
<b>Specific Physical Form:</b>	Paste
<b>Odor, Color, Grade:</b>	Silver Grey Thick Paste (Very Slight Acrylic Smell)
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>No Data Available</i>
<b>Melting point</b>	<i>No Data Available</i>
<b>Boiling Point</b>	<i>No Data Available</i>
<b>Flash Point</b>	219 °F [ <i>Test Method: Closed Cup</i> ]
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Vapor Pressure</b>	5 mmHg

Density	No Data Available
Specific Gravity	1.23 [Ref Std: WATER=1]
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	55,000 - 80,000 centipoise
Hazardous Air Pollutants	0.0003 lb HAPS/lb solids [Test Method: Calculated]
Volatile Organic Compounds	1.8 % weight [Test Method: calculated per CARB title 2]
Volatile Organic Compounds	21 g/l [Test Method: calculated SCAQMD rule 443.1]
Percent volatile	1.8 % weight
VOC Less H2O & Exempt Solvents	21 g/l [Test Method: calculated SCAQMD rule 443.1]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat  
Sparks and/or flames

### 10.5. Incompatible materials

Strong acids  
Strong oxidizing agents

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Aldehydes	Not Specified
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

May be harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

**Skin Contact:**

May be harmful in contact with skin.

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

**Ingestion:**

May be harmful if swallowed.

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

**Carcinogenicity:**

Ingredient	CAS No.	Class Description	Regulation
Inorganic Filler (04499600-7153)	Trade Secret	Anticipated human carcinogen	National Toxicology Program Carcinogens

**Additional Information:**

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Dermal	Rabbit	LD50 2,500 mg/kg
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Ingestion	Rat	LD50 3,160 mg/kg
Aluminum	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum	Ingestion		LD50 estimated to be > 5,000 mg/kg
Aluminum	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > .888 mg/l
Methylenedi(Cyclohexylamine)	Dermal	Rabbit	LD50 2,110 mg/kg
Methylenedi(Cyclohexylamine)	Ingestion	Rat	LD50 625 mg/kg
Synthetic Rubber (04499600-7150)	Dermal	Rabbit	LD50 > 3,000 mg/kg
Synthetic Rubber (04499600-7150)	Ingestion	Rat	LD50 > 15,300 mg/kg
Surface Treated Inorganic Filler (04499600-7151)	Dermal	Rabbit	LD50 > 5,000 mg/kg
Surface Treated Inorganic Filler (04499600-7151)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Surface Treated Inorganic Filler (04499600-7151)	Ingestion	Rat	LD50 > 5,110 mg/kg
Treated Filler (04499600-7152)	Dermal	Rat	LD50 > 2,000 mg/kg
Treated Filler (04499600-7152)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3.0 mg/l
Treated Filler (04499600-7152)	Ingestion	Rat	LD50 6,450 mg/kg
Mineral Filler (04499600-7156)	Dermal		LD50 estimated to be > 5,000 mg/kg
Mineral Filler (04499600-7156)	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Tris(2,4,6-Dimethylaminomonomethyl)phenol	Dermal	Rat	LD50 1,280 mg/kg
Tris(2,4,6-Dimethylaminomonomethyl)phenol	Ingestion	Rat	LD50 1,000 mg/kg
m-Xylene-.alpha.alpha'.Diamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
m-Xylene-.alpha.alpha'.Diamine	Inhalation-Dust/Mist	Rat	LC50 0.8 mg/l

	(4 hours)		
m-Xylene-.alpha.alpha'.Diamine	Ingestion	Rat	LD50 980 mg/kg
Inorganic Filler (04499600-7153)	Dermal		LD50 estimated to be > 5,000 mg/kg
Inorganic Filler (04499600-7153)	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Rabbit	Corrosive
Aluminum	Rabbit	No significant irritation
Surface Treated Inorganic Filler (04499600-7151)	Rabbit	No significant irritation
Treated Filler (04499600-7152)	Rabbit	No significant irritation
Tris(2,4,6-Dimethylaminomonomethyl)phenol	Rabbit	Corrosive
m-Xylene-.alpha.alpha'.Diamine	Rat	Corrosive
Inorganic Filler (04499600-7153)	Professional judgment	No significant irritation

### Serious Eye Damage/Irritation

Name	Species	Value
Bis(3-Aminopropyl) Ether of Diethylene Glycol	similar health hazards	Corrosive
Aluminum	Rabbit	No significant irritation
Surface Treated Inorganic Filler (04499600-7151)	Rabbit	No significant irritation
Treated Filler (04499600-7152)	Rabbit	No significant irritation
Tris(2,4,6-Dimethylaminomonomethyl)phenol	Rabbit	Corrosive
m-Xylene-.alpha.alpha'.Diamine	Rabbit	Corrosive
Inorganic Filler (04499600-7153)	Professional judgment	No significant irritation

### Skin Sensitization

Name	Species	Value
Aluminum	Guinea pig	Not sensitizing
Synthetic Rubber (04499600-7150)	Guinea pig	Some positive data exist, but the data are not sufficient for classification
Surface Treated Inorganic Filler (04499600-7151)	Human and animal	Not sensitizing
Tris(2,4,6-Dimethylaminomonomethyl)phenol	Guinea pig	Some positive data exist, but the data are not sufficient for classification
m-Xylene-.alpha.alpha'.Diamine	Guinea pig	Sensitizing

### Respiratory Sensitization

Name	Species	Value
Aluminum	Human	Some positive data exist, but the data are not sufficient for classification

### Germ Cell Mutagenicity

Name	Route	Value
Aluminum	In Vitro	Not mutagenic
Surface Treated Inorganic Filler (04499600-7151)	In Vitro	Not mutagenic
Mineral Filler (04499600-7156)	In Vitro	Not mutagenic
Tris(2,4,6-Dimethylaminomonomethyl)phenol	In Vitro	Not mutagenic
m-Xylene-.alpha.alpha'.Diamine	In Vitro	Not mutagenic
m-Xylene-.alpha.alpha'.Diamine	In vivo	Not mutagenic

Inorganic Filler (04499600-7153)	In Vitro	Some positive data exist, but the data are not sufficient for classification
----------------------------------	----------	--

**Carcinogenicity**

Name	Route	Species	Value
Surface Treated Inorganic Filler (04499600-7151)	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Inorganic Filler (04499600-7153)	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Surface Treated Inorganic Filler (04499600-7151)	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Surface Treated Inorganic Filler (04499600-7151)	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Surface Treated Inorganic Filler (04499600-7151)	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Treated Filler (04499600-7152)	Ingestion	Not toxic to development	Rat	NOAEL 625 mg/kg/day	prematuring & during gestation
m-Xylene-.alpha.alpha'.Diamine	Ingestion	Not toxic to female reproduction	Rat	NOAEL 450 mg/kg/day	1 generation
m-Xylene-.alpha.alpha'.Diamine	Ingestion	Not toxic to male reproduction	Rat	NOAEL 450 mg/kg	1 generation
m-Xylene-.alpha.alpha'.Diamine	Ingestion	Not toxic to development	Rat	NOAEL 450 mg/kg/day	1 generation

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Treated Filler (04499600-7152)	Inhalation	respiratory system	All data are negative	Rat	NOAEL 0.812 mg/l	90 minutes
Tris(2,4,6-Dimethylaminomonomethyl)phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
m-Xylene-.alpha.alpha'.Diamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Aluminum	Inhalation	nervous system   respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Surface Treated Inorganic Filler (04499600-7151)	Inhalation	respiratory system   silicosis	All data are negative	Human	NOAEL Not available	occupational exposure
Treated Filler (04499600-7152)	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Mineral Filler (04499600-7156)	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Mineral Filler (04499600-7156)	Inhalation	pulmonary fibrosis	All data are negative	Human	NOAEL Not available	

7156)				and animal	available	
Tris(2,4,6-Dimethylaminomonomethyl)phenol	Dermal	skin   liver   nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 125 mg/kg/day	28 days
Tris(2,4,6-Dimethylaminomonomethyl)phenol	Dermal	auditory system   hematopoietic system   eyes	All data are negative	Rat	NOAEL 125 mg/kg/day	28 days
m-Xylene-.alpha.alpha'.Diamine	Ingestion	endocrine system   blood   bone marrow	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 600 mg/kg/day	28 days
Inorganic Filler (04499600-7153)	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL not available	occupational exposure

### Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

## SECTION 12: Ecological information

### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Aluminum	7429-90-5	5 - 15
Aluminum (Aluminum)	7429-90-5	5 - 15

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: Other information

### NFPA Hazard Classification

**Health: 3 Flammability: 1 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	33-5984-1	<b>Version Number:</b>	1.03
<b>Issue Date:</b>	12/30/14	<b>Supersedes Date:</b>	10/13/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**



## Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	33-5988-2	<b>Version Number:</b>	1.04
<b>Issue Date:</b>	01/30/15	<b>Supersedes Date:</b>	10/13/14

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Impact Resistant Structural Adhesive (Part B) PNs 07333, 57333

#### Product Identification Numbers

41-3588-1332-1

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive, Base side of two-part color changing adhesive with optimized shear, peel and impact performance.

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Automotive Aftermarket
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 2.

Carcinogenicity: Category 2.

Germ Cell Mutagenicity: Category 2.

#### 2.2. Label elements

##### Signal word

Warning

##### Symbols

Exclamation mark | Health Hazard |

**Pictograms**



**Hazard Statements**

Causes serious eye irritation.  
 May cause an allergic skin reaction.  
 Suspected of damaging fertility or the unborn child.  
 Suspected of causing cancer.  
 Suspected of causing genetic defects.

**Precautionary Statements**

**General:**

Keep out of reach of children.

**Prevention:**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Avoid breathing dust/fume/gas/mist/vapors/spray.  
 Wear protective gloves and eye/face protection.  
 Wash thoroughly after handling.  
 Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical advice/attention.  
 IF ON SKIN: Wash with plenty of soap and water.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Wash contaminated clothing before reuse.  
 IF exposed or concerned: Get medical advice/attention.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Hazards not otherwise classified**

None.

20% of the mixture consists of ingredients of unknown acute oral toxicity.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	25068-38-6	60 - 100 Trade Secret *
Synthetic Rubber (04499600-7202)	Trade Secret*	1.5 - 20.5 Trade Secret *
Benzoic Acid, C9-C11-Branched Alkyl Esters	131298-44-7	1 - 5 Trade Secret *
1,4-Bis[(2,3-Epoxypropoxy)Methyl]Cyclohexane	14228-73-0	0.1 - 5 Trade Secret *
3-(Trimethoxysilyl)Propyl Glycidyl Ether	2530-83-8	1 - 5 Trade Secret *

Treated Filler (04499600-7203)	Trade Secret*	1 - 5 Trade Secret *
Inorganic Filler (04499600-7205)	Trade Secret*	1 - 5 Trade Secret *
Treated Inorganic Filler (04499600-7204)	Trade Secret*	1 - 5 Trade Secret *
Phenolphthalein	77-09-8	< 1 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid breathing of vapors created during cure cycle. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
3-(Trimethoxysilyl)Propyl Glycidyl Ether	2530-83-8	CMRG	TWA:5 ppm	
Inorganic Filler (04499600-7205)	Trade Secret	CMRG	TWA(as respirable dust):3 mg/m3	
Treated Filler (04499600-7203)	Trade Secret	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Treated Inorganic Filler (04499600-7204)	Trade Secret	CMRG	CEIL:5 mg/m3	
Treated Inorganic Filler (04499600-7204)	Trade Secret	OSHA	TWA concentration:0.8 mg/m3;TWA:20 millions of particles/cu. ft.	
Inorganic Filler (04499600-7205)	Trade Secret	OSHA	TWA concentration:0.8 mg/m3;TWA:20 millions of particles/cu. ft.	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission

control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>General Physical Form:</b>	Liquid
<b>Odor, Color, Grade:</b>	Silver Grey Thick Paste (Very Slight Acrylic Smell)
<b>Boiling Point</b>	35 °C
<b>Flash Point</b>	219 °F
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Vapor Pressure</b>	5 mmHg
<b>Density</b>	1.138 g/ml
<b>Specific Gravity</b>	1.138
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Viscosity</b>	100,000 - 500,000 centipoise
<b>Volatile Organic Compounds</b>	0 % weight
<b>Volatile Organic Compounds</b>	0 g/l
<b>VOC Less H2O &amp; Exempt Solvents</b>	0 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat  
Sparks and/or flames

### 10.5. Incompatible materials

Strong acids  
Strong oxidizing agents

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Aldehydes	Not Specified
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Additional Health Effects:

#### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Phenolphthalein	77-09-8	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Phenolphthalein	77-09-8	Anticipated human carcinogen	National Toxicology Program Carcinogens

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Dermal	Rat	LD50 > 1,600 mg/kg
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Ingestion	Rat	LD50 > 1,000 mg/kg
Treated Filler (04499600-7203)	Dermal	Rat	LD50 > 2,000 mg/kg
Treated Filler (04499600-7203)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3.0 mg/l
Treated Filler (04499600-7203)	Ingestion	Rat	LD50 6,450 mg/kg
Treated Inorganic Filler (04499600-7204)	Dermal	Rabbit	LD50 > 5,000 mg/kg
Treated Inorganic Filler (04499600-7204)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Treated Inorganic Filler (04499600-7204)	Ingestion	Rat	LD50 > 5,110 mg/kg
Benzoic Acid, C9-C11-Branched Alkyl Esters	Dermal	Rabbit	LD50 > 2,000 mg/kg
Benzoic Acid, C9-C11-Branched Alkyl Esters	Inhalation-Dust/Mist (4 hours)	Rat	LC50 2 mg/l
Benzoic Acid, C9-C11-Branched Alkyl Esters	Ingestion	Rat	LD50 > 5,000 mg/kg
Inorganic Filler (04499600-7205)	Dermal	Rabbit	LD50 > 5,000 mg/kg
Inorganic Filler (04499600-7205)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Inorganic Filler (04499600-7205)	Ingestion	Rat	LD50 > 5,110 mg/kg
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Dermal	Rabbit	LD50 4,000 mg/kg
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Ingestion	Rat	LD50 7,010 mg/kg
1,4-Bis[(2,3-Epoxypropoxy)Methyl]Cyclohexane	Dermal	Rabbit	LD50 2,500 mg/kg
1,4-Bis[(2,3-Epoxypropoxy)Methyl]Cyclohexane	Ingestion	Rat	LD50 2,450 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Rabbit	Mild irritant
Treated Filler (04499600-7203)	Rabbit	No significant irritation
Treated Inorganic Filler (04499600-7204)	Rabbit	No significant irritation
Inorganic Filler (04499600-7205)	Rabbit	No significant irritation
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Rabbit	Mild irritant
1,4-Bis[(2,3-Epoxypropoxy)Methyl]Cyclohexane		Mild irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Rabbit	Moderate irritant
Treated Filler (04499600-7203)	Rabbit	No significant irritation
Treated Inorganic Filler (04499600-7204)	Rabbit	No significant irritation

Inorganic Filler (04499600-7205)	Rabbit	No significant irritation
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Rabbit	Corrosive
1,4-Bis[(2,3-Epoxypropoxy)Methyl]Cyclohexane		Mild irritant

### Skin Sensitization

Name	Species	Value
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Human and animal	Sensitizing
Treated Inorganic Filler (04499600-7204)	Human and animal	Not sensitizing
Inorganic Filler (04499600-7205)	Human and animal	Not sensitizing
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Guinea pig	Some positive data exist, but the data are not sufficient for classification
1,4-Bis[(2,3-Epoxypropoxy)Methyl]Cyclohexane	similar compounds	Sensitizing

### Respiratory Sensitization

Name	Species	Value
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Human	Some positive data exist, but the data are not sufficient for classification

### Germ Cell Mutagenicity

Name	Route	Value
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	In vivo	Not mutagenic
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	In Vitro	Some positive data exist, but the data are not sufficient for classification
Treated Inorganic Filler (04499600-7204)	In Vitro	Not mutagenic
Inorganic Filler (04499600-7205)	In Vitro	Not mutagenic
3-(Trimethoxysilyl)Propyl Glycidyl Ether	In vivo	Not mutagenic
3-(Trimethoxysilyl)Propyl Glycidyl Ether	In Vitro	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Treated Inorganic Filler (04499600-7204)	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Inorganic Filler (04499600-7205)	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Dermal	Mouse	Not carcinogenic

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Ingestion	Not toxic to female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Ingestion	Not toxic to male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Dermal	Not toxic to development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Ingestion	Not toxic to development	Rat	NOAEL 750 mg/kg/day	2 generation
Treated Filler (04499600-7203)	Ingestion	Not toxic to development	Rat	NOAEL 625 mg/kg/day	prematuring & during

					gestation
Treated Inorganic Filler (04499600-7204)	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Treated Inorganic Filler (04499600-7204)	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Treated Inorganic Filler (04499600-7204)	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Inorganic Filler (04499600-7205)	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Inorganic Filler (04499600-7205)	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Inorganic Filler (04499600-7205)	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Ingestion	Not toxic to female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Ingestion	Not toxic to male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 3,000 mg/kg/day	during organogenesis

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Treated Filler (04499600-7203)	Inhalation	respiratory system	All data are negative	Rat	NOAEL 0.812 mg/l	90 minutes
1,4-Bis[(2,3-Epoxypropoxy)Methyl]Cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Dermal	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	2 years
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Dermal	nervous system	All data are negative	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	All data are negative	Rat	NOAEL 1,000 mg/kg/day	28 days
Treated Filler (04499600-7203)	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Treated Inorganic Filler (04499600-7204)	Inhalation	respiratory system   silicosis	All data are negative	Human	NOAEL Not available	occupational exposure
Inorganic Filler (04499600-7205)	Inhalation	respiratory system   silicosis	All data are negative	Human	NOAEL Not available	occupational exposure
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Ingestion	heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   nervous system   kidney and/or	All data are negative	Rat	NOAEL 1,000 mg/kg/day	28 days

		bladder   respiratory system				
--	--	------------------------------	--	--	--	--

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information**

**15.1. US Federal Regulations**

Contact 3M for more information.

**311/312 Hazard Categories:**

Fire Hazard - No    Pressure Hazard - No    Reactivity Hazard - No    Immediate Hazard - Yes    Delayed Hazard - Yes

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Phenolphthalein	77-09-8	< 1

**15.2. State Regulations**

Contact 3M for more information.

## California Proposition 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Classification</u>
Phenolphthalein	77-09-8	Carcinogen

WARNING: This product contains a chemical known to the State of California to cause cancer.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

**Health:** 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	33-5988-2	<b>Version Number:</b>	1.04
<b>Issue Date:</b>	01/30/15	<b>Supersedes Date:</b>	10/13/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at [www.3M.com](http://www.3M.com)