		Page: 1
SAFETY DATA SHEET		Revision Date: 11/17/2015
		Print Date: 12/10/2015
		SDS Number: 000000264506
Valvoline™ Heavy Duty BRAKE PARTS CLEANER		Version: 1.0
681046		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ Heavy Duty
BRAKE PARTS CLEANER

Recommended use of the chemical and restrictions on use

<p>Details of the supplier of the safety data sheet Niteo Products, LLC P.O. Box 191629 Dallas TX 75219 United States of America</p>	<p>Emergency telephone number CHEMTREC DIRECT 1-800-424-9300</p> <p>Product Information 1-844-696-4836</p>
---	--

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable aerosols : Category 1

Eye irritation : Category 2A

Specific target organ systemic toxicity - single exposure : Category 1 (Central nervous system, Eyes)

Specific target organ systemic toxicity - single exposure : Category 3 (Central nervous system)


Specific target organ systemic toxicity - repeated exposure : Category 2 (Auditory system)

GHS Label element

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : Extremely flammable aerosol.
Causes serious eye irritation.

		Page: 2
SAFETY DATA SHEET		Revision Date: 11/17/2015
		Print Date: 12/10/2015
		SDS Number: 000000264506
Valvoline™ Heavy Duty BRAKE PARTS CLEANER		Version: 1.0
681046		

May cause drowsiness or dizziness.
 Causes damage to organs (Central nervous system, Eyes).
 May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Precautionary Statements

: Prevention:

Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
 Wash skin thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Wear eye protection/ face protection.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed: Call a POISON CENTER or doctor/ physician. If eye irritation persists: Get medical advice/ attention.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
ACETONE	67-64-1	Flam. Liq. 2; H225 Eye Irrit. 2A; H319 STOT SE 3; H336	86.21

SAFETY DATA SHEET

Revision Date: 11/17/2015

Print Date: 12/10/2015


SDS Number: 000000264506

Valvoline™ Heavy Duty BRAKE PARTS CLEANER

Version: 1.0


681046

CARBON DIOXIDE	124-38-9	Press. Gas Liquefied gas; H280	5.86
XYLENE	1330-20-7	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT SE 3; H335, H336 Asp. Tox. 1; H304	5.12
METHANOL	67-56-1	Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 STOT SE 1; H370	2.79
ETHYL BENZENE	100-41-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT RE 2; H373 Asp. Tox. 1; H304	1.53

		Page: 4
SAFETY DATA SHEET		Revision Date: 11/17/2015
		Print Date: 12/10/2015
		SDS Number: 000000264506
Valvoline™ Heavy Duty BRAKE PARTS CLEANER		Version: 1.0
681046		

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If unconscious place in recovery position and seek medical advice.
Consult a physician after significant exposure.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Obtain medical attention.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion. Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.
This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis.
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
redness of the skin
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)

		Page: 5
SAFETY DATA SHEET		Revision Date: 11/17/2015
		Print Date: 12/10/2015
		SDS Number: 000000264506
Valvoline™ Heavy Duty BRAKE PARTS CLEANER		Version: 1.0
681046		


discomfort in the chest
 effects on memory
 muscle cramps
 pain in the abdomen and lower back
 Blurred vision
 Shortness of breath
 confusion
 irregular heartbeat
 cyanosis (causes blue coloring of the skin and nails from lack of oxygen)
 visual impairment (including blindness)
 Causes serious eye irritation.
 May cause drowsiness or dizziness.
 Causes damage to organs.
 May cause damage to organs through prolonged or repeated exposure.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Alcohol-resistant foam
 Carbon dioxide (CO₂)
 Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
 Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
 Hydrocarbons
 Aldehydes
- Specific extinguishing methods :

 Product is compatible with standard fire-fighting agents.
- Further information : Use a water spray to cool fully closed containers.

		Page: 6
SAFETY DATA SHEET		Revision Date: 11/17/2015
		Print Date: 12/10/2015
		SDS Number: 000000264506
Valvoline™ Heavy Duty BRAKE PARTS CLEANER		Version: 1.0
681046		

Special protective equipment : In the event of fire, wear self-contained breathing apparatus. for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Use personal protective equipment.
Ensure adequate ventilation.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Other information : Comply with all applicable federal, state, and local regulations.
Suppress (knock down) gases/vapours/mists with a water spray jet.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Open drum carefully as content may be under pressure.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Take precautionary measures against static discharges.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
No smoking.

SAFETY DATA SHEET

Revision Date: 11/17/2015

Print Date: 12/10/2015

SDS Number: 000000264506

Valvoline™ Heavy Duty BRAKE PARTS CLEANER

Version: 1.0

681046

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ACETONE	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		REL	250 ppm 590 mg/m ³	NIOSH/GUIDE
		PEL	1,000 ppm 2,400 mg/m ³	OSHA_TRANS
		TWA	250 ppm	ACGIHLIS_P
		STEL	500 ppm	ACGIHLIS_P
		TWA	750 ppm 1,800 mg/m ³	Z1A
		STEL	1,000 ppm 2,400 mg/m ³	Z1A
CARBON DIOXIDE	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		REL	5,000 ppm 9,000 mg/m ³	NIOSH/GUIDE
		STEL	30,000 ppm 54,000 mg/m ³	NIOSH/GUIDE
		PEL	5,000 ppm 9,000 mg/m ³	OSHA_TRANS
XYLENE	1330-20-7	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		PEL	100 ppm 435 mg/m ³	OSHA_TRANS
		REL	100 ppm 435 mg/m ³	NIOSH/GUIDE
		STEL	150 ppm 655 mg/m ³	NIOSH/GUIDE
METHANOL	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		REL	200 ppm 260 mg/m ³	NIOSH/GUIDE
		STEL	250 ppm 325 mg/m ³	NIOSH/GUIDE
		PEL	200 ppm 260 mg/m ³	OSHA_TRANS
		TWA	200 ppm 260 mg/m ³	TN OEL
		STEL	250 ppm 325 mg/m ³	TN OEL
ETHYL BENZENE	100-41-4	TWA	20 ppm	ACGIH
		REL	100 ppm 435 mg/m ³	NIOSH/GUIDE

SAFETY DATA SHEET

Revision Date: 11/17/2015

Print Date: 12/10/2015

SDS Number: 000000264506

Valvoline™ Heavy Duty BRAKE PARTS CLEANER

Version: 1.0

681046

		STEL	125 ppm 545 mg/m ³	NIOSH/GUID E
		PEL	100 ppm 435 mg/m ³	OSHA_TRAN S

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
ACETONE	67-64-1	acetone	Urine	Sampling time: End of shift.	50 mg/l	
Remarks:	Nonspecific					
XYLENE	1330-20-7	Methylhippuric acids	Creatinine in urine	Sampling time: End of shift.	1.5 g/g	
METHANOL	67-56-1	methanol	Urine	Sampling time: End of shift.	15 mg/l	
Remarks:	Background, Nonspecific					
ETHYL BENZENE	100-41-4	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	Sampling time: End of shift.	0.15 g/g	ACGIH BEI
Remarks:	Nonspecific					

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
In the case of dust or aerosol formation use respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

SAFETY DATA SHEET

Revision Date: 11/17/2015

Print Date: 12/10/2015

SDS Number: 000000264506

Valvoline™ Heavy Duty BRAKE PARTS CLEANER

Version: 1.0

681046

- Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.
- Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes
Flame-resistant clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : aerosol
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : -4 °F / -20 °C
Value for Component
- Evaporation rate : No data available
- Flammability (solid, gas) :
No data available
- Flammability (liquids) : Static Accumulating liquid
- Flammability (liquids) :
Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : No data available
- Relative vapour density : No data available
- Relative density : No data available

SAFETY DATA SHEET

Revision Date: 11/17/2015

Print Date: 12/10/2015

SDS Number: 000000264506

Valvoline™ Heavy Duty BRAKE PARTS CLEANER

Version: 1.0

681046

Density : 0.756 g/cm³ (21.1 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Vapours may form explosive mixture with air.


Conditions to avoid : excessive heat

Heat, flames and sparks.

Incompatible materials : Acids
alkalis
aluminum
Amines
Ammonia
halogens
Lead
peroxides
Reducing agents
sodium
strong bases
Strong oxidizing agents
Zinc
Peroxides

Hazardous decomposition products

carbon dioxide and carbon monoxide
formaldehyde-like
Hydrocarbons

		Page: 11
SAFETY DATA SHEET		Revision Date: 11/17/2015
		Print Date: 12/10/2015
		SDS Number: 000000264506
Valvoline™ Heavy Duty BRAKE PARTS CLEANER		Version: 1.0
681046		

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

ACETONE:

Acute oral toxicity : LD 50 (Rat, female): 5,800 mg/kg

Acute inhalation toxicity : LC 50 (Rat, female): 76 mg/l
Exposure time: 4 h

Acute dermal toxicity : LD 50 (Rabbit): > 7,426 mg/kg

XYLENE:

Acute oral toxicity : LD 50 (Rat): 3,523 - 8,600 mg/kg

Acute inhalation toxicity : LC 50 (Rat): 6700 ppm
Exposure time: 4 h
Test atmosphere: vapour

Assessment: The component/mixture is classified as acute inhalation toxicity, category 4.

Acute dermal toxicity : LD 50 (Rabbit): 1,700 mg/kg

METHANOL:

Acute oral toxicity : LD L0 (Human): 300 mg/kg
Assessment: The component/mixture is classified as acute oral toxicity, category 3.

Acute inhalation toxicity : Assessment: The component/mixture is classified as acute inhalation toxicity, category 3.


Acute dermal toxicity : LD 50 (Rabbit): 12,800 mg/kg
Assessment: The component/mixture is classified as acute dermal toxicity, category 3.

ETHYL BENZENE:

Acute oral toxicity : LD 50 (Rat): ca. 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 4000 ppm
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD 50 (Rabbit): 17,800 mg/kg

		Page: 12
SAFETY DATA SHEET		Revision Date: 11/17/2015
		Print Date: 12/10/2015
		SDS Number: 000000264506
Valvoline™ Heavy Duty BRAKE PARTS CLEANER		Version: 1.0
681046		

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation in susceptible persons.

Components:

ACETONE:

Result: Mildly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

CARBON DIOXIDE:

Result: No skin irritation

XYLENE:

Result: Irritating to skin.

METHANOL:

Species: Rabbit

Result: No skin irritation

ETHYL BENZENE:

Result: Irritating to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

ACETONE:

Result: Irritating to eyes.

CARBON DIOXIDE:

Result: No eye irritation

XYLENE:

Result: Irritating to eyes.

METHANOL:


Species: Rabbit

Result: Mildly irritating to eyes

ETHYL BENZENE:

Result: Irritating to eyes.

Remarks: Exposure to a concentration of 5000 ppm causes intolerable irritation of the eyes

		Page: 13
SAFETY DATA SHEET		Revision Date: 11/17/2015
		Print Date: 12/10/2015
		SDS Number: 000000264506
Valvoline™ Heavy Duty BRAKE PARTS CLEANER		Version: 1.0
681046		

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

METHANOL:

Test Type: Maximisation Test (GPMT)

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Causes damage to organs (Central nervous system, Eyes).

Components:

ACETONE:

Exposure routes: Inhalation

Target Organs: Nervous system

Assessment: May cause drowsiness or dizziness.

XYLENE:

Assessment: May cause respiratory irritation., May cause drowsiness or dizziness.

METHANOL:

Target Organs: Central nervous system, Eyes

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.

STOT - repeated exposure

May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Components:

ETHYL BENZENE:

Target Organs: Auditory system

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Components:

ACETONE:

May be harmful if swallowed and enters airways.

XYLENE:

May be fatal if swallowed and enters airways.

ETHYL BENZENE:

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

Revision Date: 11/17/2015

Print Date: 12/10/2015

SDS Number: 000000264506

Valvoline™ Heavy Duty BRAKE PARTS CLEANER

Version: 1.0

681046

Exposure time: 8 d
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 2,112 mg/l
Exposure time: 28 d
Test Type: flow-through test

XYLENE:

Toxicity to fish : LC 50 (Fathead minnow (Pimephales promelas)): 23.53 - 29.97 mg/l
Exposure time: 96 h
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : LC 50 (Water flea (Daphnia magna)): > 100 - < 1,000 mg/l
Exposure time: 24 h
Test Type: static test

METHANOL:

Toxicity to fish : LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss)): 18,000 - 20,000 mg/l
Exposure time: 96 h
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia magna)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test

ETHYL BENZENE:

Toxicity to fish : LC 50 (Fathead minnow (Pimephales promelas)): 9.1 - 15.6 mg/l
Exposure time: 96 h
Test Type: static test

LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss)): 4.2 mg/l
Exposure time: 96 h
Test Type: Renewal

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia magna)): 1.37 - 4.4 mg/l
Exposure time: 48 h
Test Type: static test


Toxicity to algae : (Pseudokirchneriella subcapitata (green algae)): 3.6 mg/l
End point: EC 50
Exposure time: 96 h
Test Type: Growth inhibition

Persistence and degradability

Components:

ACETONE:

Biodegradability : Result: Readily biodegradable

		Page: 16
SAFETY DATA SHEET		Revision Date: 11/17/2015
		Print Date: 12/10/2015
		SDS Number: 000000264506
Valvoline™ Heavy Duty BRAKE PARTS CLEANER		Version: 1.0
681046		

Biodegradation: 90.9 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

XYLENE:

Physico-chemical removability : Remarks: The product evaporates readily.

METHANOL:

Biodegradability : Biodegradation: 99 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301D

ETHYL BENZENE:

Biodegradability : Result: Readily biodegradable
 Biodegradation: 70 - 80 %
 Exposure time: 28 d

Bioaccumulative potential

Components:

ACETONE:
 Partition coefficient: n-octanol/water : log Pow: -0.24

XYLENE:
 Partition coefficient: n-octanol/water : log Pow: 3.16

METHANOL:
 Partition coefficient: n-octanol/water : log Pow: -0.77

ETHYL BENZENE:
 Partition coefficient: n-octanol/water : log Pow: 3.15

Mobility in soil

Components:
 No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

Components:

SAFETY DATA SHEET

Revision Date: 11/17/2015

Print Date: 12/10/2015

SDS Number: 000000264506

Valvoline™ Heavy Duty BRAKE PARTS CLEANER
681046

Version: 1.0

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

UN	1950	Aerosols	2		LIMITED QUANTITY
----	------	----------	---	--	------------------

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN	1950	Aerosols	2.1		LIMITED QUANTITY
----	------	----------	-----	--	------------------

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

UN	1950	Aerosols	2.1		LIMITED QUANTITY
----	------	----------	-----	--	------------------

INTERNATIONAL MARITIME DANGEROUS GOODS

UN	1950	AEROSOLS	2.1		LIMITED QUANTITY
----	------	----------	-----	--	------------------

TRANSPORT CANADA - INLAND WATERWAYS

UN	1950	AEROSOLS	2.1		LIMITED QUANTITY
----	------	----------	-----	--	------------------



SAFETY DATA SHEET

Revision Date: 11/17/2015

Print Date: 12/10/2015

SDS Number: 000000264506

Valvoline™ Heavy Duty BRAKE PARTS CLEANER
681046

Version: 1.0

TRANSPORT CANADA - RAIL

UN	1950	AEROSOLS	2.1	LIMITED QUANTITY
----	------	----------	-----	------------------

TRANSPORT CANADA - ROAD

UN	1950	AEROSOLS	2.1	
----	------	----------	-----	--

U.S. DOT - INLAND WATERWAYS

UN	1950	Aerosols, flammable	2.1	
----	------	---------------------	-----	--

U.S. DOT - RAIL

UN	1950	Aerosols, flammable	2.1	
----	------	---------------------	-----	--

U.S. DOT - ROAD

UN	1950	AEROSOLS	2.1	
----	------	----------	-----	--

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act


CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
XYLENE	1330-20-7	100	1950.610541

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

SARA 313 Component(s)

XYLENE	1330-20-7	5.12 %
METHANOL	67-56-1	2.79 %

		Page: 19
SAFETY DATA SHEET		Revision Date: 11/17/2015
		Print Date: 12/10/2015
		SDS Number: 000000264506
Valvoline™ Heavy Duty BRAKE PARTS CLEANER		Version: 1.0
681046		

ETHYL BENZENE 100-41-4 1.53 %

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

ETHYL BENZENE 100-41-4

BENZENE 71-43-2

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

METHANOL 67-56-1

TOLUENE 108-88-3

BENZENE 71-43-2

The components of this product are reported in the following inventories:

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 11/17/2015

NFPA:	HMIS III:
--------------	------------------

SAFETY DATA SHEET

Revision Date: 11/17/2015

Print Date: 12/10/2015

SDS Number: 000000264506

Valvoline™ Heavy Duty BRAKE PARTS CLEANER

Version: 1.0

681046

<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<table border="1"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">4*</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">4</td> </tr> <tr> <td style="background-color: yellow;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	4*	FLAMMABILITY	4	PHYSICAL HAZARD	0
HEALTH	4*						
FLAMMABILITY	4						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Not applicable

Full text of H-Statements


- H225 Highly flammable liquid and vapor.
- H226 Flammable liquid and vapor.
- H280 Contains gas under pressure; may explode if heated.
- H301 Toxic if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H370 Causes damage to organs.
- H373 May cause damage to organs through prolonged or repeated exposure.

Sources of key data used to compile the Safety Data Sheet

Internal data including own and sponsored test reports
 The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.
 Cefic, the European Chemical Industry Council.
 ESIS European Chemical Substances Information System

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Niteo's Environmental Health and Safety Department (1-844-696-4836).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

		Page: 21
SAFETY DATA SHEET		Revision Date: 11/17/2015
		Print Date: 12/10/2015
		SDS Number: 000000264506
Valvoline™ Heavy Duty BRAKE PARTS CLEANER		Version: 1.0
681046		

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System