		Page: 1
SAFETY DATA SHEET		Revision Date: 05/22/2017
		Print Date: 6/2/2017
		SDS Number: R0296767
Zerex™ G-48 Antifreeze Coolant ™ Trademark, Valvoline or its subsidiaries, registered in various countries ZXG482		Version: 1.3

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Zerex™ G-48
 Antifreeze Coolant
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries

Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL	Emergency telephone number 1-800-VALVOLINE (1-800-825-8654) Regulatory Information Number 1-800-TEAMVAL Product Information 1-800-TEAMVAL
---	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) : Category 4
 Reproductive toxicity : Category 1B
 Specific target organ systemic toxicity - repeated exposure (Oral) : Category 2 (Kidney, Liver)

GHS label elements

Hazard pictograms :  

Signal Word : Danger

Hazard Statements : Harmful if swallowed.
 May damage fertility or the unborn child.
 May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Precautionary Statements : **Prevention:**
 Obtain special instructions before use.

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767

Version: 1.3

Zerex™ G-48 Antifreeze Coolant
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 ZXG482

Do not handle until all safety precautions have been read and understood.
 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
 Wash skin thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
 IF exposed or concerned: Get medical advice/ attention.
Storage:
 Store locked up.
Disposal:
 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
ETHYLENE GLYCOL	107-21-1	Acute Tox. 4; H302 STOT RE 2; H373	93.3307
DIETHYLENE GLYCOL	111-46-6	Acute Tox. 4; H302 STOT RE 2; H373	4.6608
2-ETHYLHEXANOIC ACID, SODIUM SALT	19766-89-3	Repr. 2; H361	3.0072
DISODIUM TETRABORATE ANHYDROUS	1330-43-4	Repr. 1B; H360	0.7658

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.



SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767

Version: 1.3

Zerex™ G-48 Antifreeze Coolant
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 ZXG482

Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

- If inhaled : If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Flush eyes with water as a precaution.
 Remove contact lenses.
 Protect unharmed eye.
 If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
 Rinse mouth with water.
 Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Effects of acute ethylene glycol poisoning appear in three fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration, nausea, vomiting, and in severe cases, coma, convulsions, and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnea, tachycardia, mild hypotension, cyanosis, and in severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement, and congestive failure. The final stage occurs 24-72 post-exposure and is characterized by renal failure, ranging from a mild increase in blood urea nitrogen and creatinine followed by recovery, to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The most significant laboratory finding in ethylene glycol intoxication is severe metabolic acidosis.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
 stomach or intestinal upset (nausea, vomiting, diarrhea)
 irritation (nose, throat, airways)
 Cough
 pain in the abdomen and lower back
 cyanosis (causes blue coloring of the skin and nails from lack of oxygen)
 lung edema (fluid buildup in the lung tissue)



SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767

Version: 1.3

Zerex™ G-48 Antifreeze Coolant
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 ZXG482

acute kidney failure (sudden slowing or stopping of urine production)
 Convulsions
 Harmful if swallowed.
 May damage fertility or the unborn child.

Notes to physician

: This product contains ethylene glycol. Ethanol decreases the metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of severe poisoning since the elimination half-life of ethylene glycol is 3 hours. If medical care will be delayed several hours, give the patient three to four 1-ounce oral "shots" of 86-proof or higher whiskey before or during transport to the hospital. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and as such, may be used as an antidote in the treatment of ethylene glycol poisoning. Hemodialysis effectively removes ethylene glycol and its metabolites from the body.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Carbon dioxide (CO2)
 Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Alcohols
 Aldehydes
 carbon dioxide and carbon monoxide
 ethers
 toxic fumes
 Hydrocarbons
 Sodium oxides

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767

Version: 1.3

Zerex™ G-48 Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various countries
ZXG482

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767

Version: 1.3

Zerex™ G-48 Antifreeze Coolant
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 ZXG482

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ETHYLENE GLYCOL	107-21-1	C	100 mg/m3 Aerosol only	ACGIH
		C	50 ppm 125 mg/m3	OSHA P0
		C	40 ppm 100 mg/m3 Vapour	CAL PEL
DIETHYLENE GLYCOL	111-46-6	TWA	10 mg/m3	US WEEL
DISODIUM TETRABORATE ANHYDROUS	1330-43-4	TWA	1 mg/m3	NIOSH REL
		PEL	5 mg/m3	CAL PEL
		TWA	10 mg/m3	OSHA P0
		TWA	2 mg/m3 Inhalable fraction (Borate)	ACGIH
		STEL	6 mg/m3 Inhalable fraction (Borate)	ACGIH

Hazardous components without workplace control parameters

Components	CAS-No.
2-ETHYLHEXANOIC ACID, SODIUM SALT	19766-89-3
DISODIUM TETRABORATE ANHYDROUS	1330-43-4

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767

Version: 1.3

Zerex™ G-48 Antifreeze Coolant
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 ZXG482

- Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:
 Impervious clothing
 Safety shoes
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.
 Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Wash hands before breaks and at the end of workday.
 When using do not eat or drink.
 When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Colour : blue
- Odour : mild
- Odour Threshold : No data available
- pH : Average 7.2
- Melting point/freezing point : No data available
- Boiling point/boiling range : 387.1 °F / 197.3 °C
 Calculated Phase Transition Liquid/Gas
- Flash point : > 250 °F / > 121 °C
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : 15.3 %(V)
 GLP: Calculated Explosive Limit
- Lower explosion limit : 3.2 %(V)
 GLP: Calculated Explosive Limit

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767

Version: 1.3

Zerex™ G-48 Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various countries
ZXG482

Vapour pressure	: 3 hPa (25 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: No data available
Density	: 1.1213 g/cm ³ (15.6 °C)
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: excessive heat
Incompatible materials	: Acids Aldehydes Alkali metals Alkaline earth metals Bases strong alkalis Strong oxidizing agents Sulphur compounds
Hazardous decomposition	

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767

Version: 1.3

Zerex™ G-48 Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various countries
ZXG482

products

Alcohols
Aldehydes
carbon dioxide and carbon monoxide
ethers
Hydrocarbons
Organic acids
ketones
various hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity

:
Remarks: Ingestion of medications contaminated with diethylene glycol has caused kidney failure and death in humans. Products containing diethylene glycol should be considered toxic by ingestion.

Acute dermal toxicity

: Remarks: Skin absorption of this material (or a component) may be increased through injured skin.

Components:

ETHYLENE GLYCOL:

Acute oral toxicity

: LD0 (Human): Estimated 1.56 g/kg

Assessment: The component/mixture is classified as acute oral toxicity, category 4.

Acute inhalation toxicity

: LC50 (Rat): 10.9 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity

: LD50 (Rabbit): 9,530 mg/kg

DIETHYLENE GLYCOL:

Acute oral toxicity

: LD50 (Human): Expected 1,120 mg/kg
Target Organs: Kidney

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767

Version: 1.3

Zerex™ G-48 Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various countries
ZXG482

Acute inhalation toxicity : LC50 (Rat): > 4.6 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 13,300 mg/kg

2-ETHYLHEXANOIC ACID, SODIUM SALT:

Acute oral toxicity : LD50 (Rat): 2,043 mg/kg
Remarks: Information given is based on data obtained from similar substances.

Acute inhalation toxicity : Assessment: Not classified as acutely toxic by inhalation under GHS.
Remarks: Information given is based on data obtained from similar substances.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.
Remarks: Information given is based on data obtained from similar substances.

DISODIUM TETRABORATE ANHYDROUS:

Acute inhalation toxicity : LC50 (Rat): > 2.03 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Skin corrosion/irritation

Not classified based on available information.

Components:**ETHYLENE GLYCOL:**

Species: Rabbit

Result: No skin irritation

DIETHYLENE GLYCOL:

Species: Human

Result: Slight, transient irritation

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767

Version: 1.3

Zerex™ G-48 Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various countries
ZXG482

2-ETHYLHEXANOIC ACID, SODIUM SALT:

Species: Rabbit

Result: Slight, transient irritation

Remarks: Information given is based on data obtained from similar substances.

DISODIUM TETRABORATE ANHYDROUS:

Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:**ETHYLENE GLYCOL:**

Result: Slight, transient irritation

DIETHYLENE GLYCOL:

Species: Rabbit

Result: Slight, transient irritation

2-ETHYLHEXANOIC ACID, SODIUM SALT:

Species: Rabbit

Result: Slight, transient irritation

Remarks: Information given is based on data obtained from similar substances.

DISODIUM TETRABORATE ANHYDROUS:

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:**ETHYLENE GLYCOL:**

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

DIETHYLENE GLYCOL:

Test Type: Maximisation Test

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Did not cause sensitisation on laboratory animals.

2-ETHYLHEXANOIC ACID, SODIUM SALT:

Test Type: Maximisation Test

Species: Guinea pig

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767

Version: 1.3

Zerex™ G-48 Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various countries
ZXG482

Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.

DISODIUM TETRABORATE ANHYDROUS:
Test Type: Buehler Test
Species: Guinea pig
Assessment: Does not cause skin sensitisation.
Method: OECD Test Guideline 406

Germ cell mutagenicity
Not classified based on available information.

Components:**ETHYLENE GLYCOL:**

Genotoxicity in vitro : Test Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

DIETHYLENE GLYCOL:

Genotoxicity in vitro : Test Type: Ames test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

: Test species: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 479
Result: negative
GLP: yes

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Test species: Mouse
Method: OECD Test Guideline 474
Result: negative
GLP: yes

2-ETHYLHEXANOIC ACID, SODIUM SALT:

Genotoxicity in vitro : Test Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative
Remarks: Information given is based on data obtained from similar substances.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

May damage fertility or the unborn child.

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767

Version: 1.3

Zerex™ G-48 Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various countries
ZXG482

Components:**2-ETHYLHEXANOIC ACID, SODIUM SALT:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

DISODIUM TETRABORATE ANHYDROUS:

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:**ETHYLENE GLYCOL:**

Exposure routes: Ingestion

Target Organs: Kidney, Liver

Assessment: May cause damage to organs through prolonged or repeated exposure.

DIETHYLENE GLYCOL:

Exposure routes: Ingestion

Target Organs: Kidney

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Experience with human exposure**Components:****DIETHYLENE GLYCOL:**

Liver

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:**ETHYLENE GLYCOL:**

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l
Exposure time: 96 h
Test Type: static test

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767

Version: 1.3

Zerex™ G-48 Antifreeze Coolant
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 ZXG482

LC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l
 Exposure time: 48 h
 Test Type: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 - 13,000 mg/l
 End point: Growth inhibition
 Exposure time: 7 Days

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l
 Exposure time: 7 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 24,000 mg/l
 Exposure time: 7 d

DIETHYLENE GLYCOL:

Toxicity to fish : LC50 (Fathead minnow (Pimephales promelas)): 75,210 mg/l
 Exposure time: 96 h
 Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : LC50 (Water flea (Daphnia magna)): > 10,000 mg/l
 Exposure time: 24 h
 Test Type: static test
 Method: DIN 38412

2-ETHYLHEXANOIC ACID, SODIUM SALT:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 100 mg/l
 Exposure time: 96 h
 Test Type: semi-static test
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 910 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 49.3 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Remarks: Information given is based on data obtained from similar substances.

DISODIUM TETRABORATE ANHYDROUS:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 79.7 mg/l
 Exposure time: 96 h
 Remarks: Information refers to the main component.

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767

Version: 1.3

Zerex™ G-48 Antifreeze Coolant
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 ZXG482

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): 17.5 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Method: OECD Test Guideline 201
 Remarks: Information refers to the main component.

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): 5.6 mg/l
 Exposure time: 34 d
 Test Type: semi-static test
 Method: OECD Test Guideline 210
 Remarks: Information refers to the main component.

Persistence and degradability**Components:****ETHYLENE GLYCOL:**

Biodegradability : Result: Readily biodegradable.
 Biodegradation: 90 - 100 %
 Exposure time: 10 d
 Method: OECD Test Guideline 301

DIETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.
 Biodegradation: 70 - 80 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

2-ETHYLHEXANOIC ACID, SODIUM SALT:

Biodegradability : Result: Readily biodegradable.
 Biodegradation: > 70 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301E
 Remarks: Information given is based on data obtained from similar substances.

DISODIUM TETRABORATE ANHYDROUS:

Biodegradability : Result: The methods for determining biodegradability are not applicable to inorganic substances.

No data available

Bioaccumulative potential**Components:****ETHYLENE GLYCOL:**

Bioaccumulation : Species: Crayfish (Procambarus)
 Bioconcentration factor (BCF): 0.27
 Exposure time: 61 d
 Concentration: 1000 mg/l
 Method: Flow through



SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767

Version: 1.3

Zerex™ G-48 Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various countries
ZXG482

Partition coefficient: n-octanol/water : log Pow: -1.36

DIETHYLENE GLYCOL:
Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 100

Partition coefficient: n-octanol/water : log Pow: -1.47

2-ETHYLHEXANOIC ACID, SODIUM SALT:
Partition coefficient: n-octanol/water : log Pow: 1.3

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations



SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767

Version: 1.3

Zerex™ G-48 Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various countries
ZXG482

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID



SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767

Version: 1.3

Zerex™ G-48 Antifreeze Coolant
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 ZXG482

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

**EPCRA - Emergency Planning and Community Right-to-Know Act
 CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ETHYLENE GLYCOL	107-21-1	5000	5357

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard
 Chronic Health Hazard

SARA 313
 ETHYLENE GLYCOL 107-21-1 93.33 %

California Prop 65 : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIOC : Not in compliance with the inventory

TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0296767


Version: 1.3

Zerex™ G-48 Antifreeze Coolant
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 ZXG482

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/22/2017

NFPA:	HMIS III:						
<p style="text-align: center;">Flammability</p>  <p style="text-align: center;">Special hazard.</p>	<table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">1*</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: yellow; color: black;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p style="font-size: small;">0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	1*	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	1*						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						


NFPA Flammable and Combustible Liquids Classification
 Combustible Liquid Class IIIB

Full text of H-Statements

- H302 Harmful if swallowed.
- H360 May damage fertility or the unborn child.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

Sources of key data used to compile the Safety Data Sheet
 Valvoline internal data including own and sponsored test reports
 The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

	Page: 20
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0296767
Zerex™ G-48 Antifreeze Coolant ™ Trademark, Valvoline or its subsidiaries, registered in various countries ZXG482	Version: 1.3

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System