


| | | |
|---|--|---------------------------|
|  | | Page: 1 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 11/3/2016 |
| | | SDS Number: 000000252945 |
| Valvoline™ Full Synthetic with MaxLife™ Technology SAE 0W-20 Motor Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 852400 | | Version: 1.1 |

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ Full Synthetic with MaxLife™ Technology SAE
0W-20 Motor Oil

™ Trademark, Valvoline or its subsidiaries, regisred in various
countries

Recommended use of the chemical and restrictions on use

| | |
|---|--|
| Details of the supplier of the safety data sheet Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509 United States of America SDS@valvoline.com | Emergency telephone number 1-800-VALVOLINE Regulatory Information Number 1-800-TEAMVAL Product Information 1-800-TEAMVAL |
|---|--|

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.


SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components


| Chemical Name | CAS-No. | Classification | Concentration (%) |
|---------------|---------|----------------|-------------------|
|---------------|---------|----------------|-------------------|

| | | |
|---|--|---------------------------|
|  | | Page: 2 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 11/3/2016 |
| | | SDS Number: 000000252945 |
| Valvoline™ Full Synthetic with MaxLife™ Technology SAE 0W-20 Motor Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 852400 | | Version: 1.1 |

| | | | |
|---------------------------------|------------|--|-------|
| HEAVY PARAFFINIC DISTILLATE | 64742-54-7 | Asp. Tox. 1; H304 | 73.98 |
| ZINC DIALKYL DITHIOPHOSPHATE | 68649-42-3 | Skin Irrit. 2; H315 Aquatic Acute 2; H401 Aquatic Chronic 2; H411 | 1.08 |

SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary

| | | |
|---|--|---------------------------|
|  | | Page: 3 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 11/3/2016 |
| | | SDS Number: 000000252945 |
| Valvoline™ Full Synthetic with MaxLife™ Technology SAE 0W-20 Motor Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 852400 | | Version: 1.1 |

abnormalities.
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
acne
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.


SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
- Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
- Methods and materials for : Soak up with inert absorbent material (e.g. sand, silica gel,

| | | |
|--|--|---------------------------|
|  | | Page: 4 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 11/3/2016 |
| | | SDS Number: 000000252945 |
| Valvoline™ Full Synthetic with MaxLife™ Technology SAE 0W-20 Motor Oil ™ Trademark, Valvoline or its subsidiaries, regised in various countries 852400 | | Version: 1.1 |

containment and cleaning up : acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection


Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

: Wear as appropriate:
impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear resistant gloves (consult your safety equipment supplier).

| | | |
|---|--|---------------------------|
|  | | Page: 5 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 11/3/2016 |
| | | SDS Number: 000000252945 |
| Valvoline™ Full Synthetic with MaxLife™ Technology SAE 0W-20 Motor Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 852400 | | Version: 1.1 |

Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 424.99 °F / 218.33 °C
(1,013.333333 hPa)
Calculated Phase Transition Liquid/Gas

Flash point : > 390 °F / > 199 °C
Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 0.00004 hPaCalculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 0.847 g/cm3 (15.6 °C)

Solubility(ies)


Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity

| | | |
|---|--|---------------------------|
|  | | Page: 6 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 11/3/2016 |
| | | SDS Number: 000000252945 |
| Valvoline™ Full Synthetic with MaxLife™ Technology SAE 0W-20 Motor Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 852400 | | Version: 1.1 |

Viscosity, dynamic : No data available

Viscosity, kinematic : 45.2 mm²/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide
Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

HEAVY PARAFFINIC DISTILLATE:

Acute oral toxicity : LD 50 (Rat): > 15 g/kg

Acute dermal toxicity : LD 50 (Rabbit): > 5 g/kg


ZINC DIALKYL DITHIOPHOSPHATE:

Acute oral toxicity : LD 50 (Rat): > 2,000 - 5,000 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Skin corrosion/irritation

Not classified based on available information.

| | |
|--|---------------------------|
|  | Page: 7 |
| SAFETY DATA SHEET | Revision Date: 07/31/2016 |
| | Print Date: 11/3/2016 |
| | SDS Number: 000000252945 |
| Valvoline™ Full Synthetic with MaxLife™ Technology SAE 0W-20 Motor Oil ™ Trademark, Valvoline or its subsidiaries, regised in various countries 852400 | Version: 1.1 |

Product:

Result: Mildly irritating to skin

Remarks: Expected

Result: Repeated exposure may cause skin dryness or cracking.

Components:

HEAVY PARAFFINIC DISTILLATE:

Result: Mildly irritating to skin

ZINC DIALKYL DITHIOPHOSPHATE:

Result: Irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result: Mildly irritating to eyes

Remarks: Expected based on components.

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

HEAVY PARAFFINIC DISTILLATE:

Result: Not irritating to eyes

ZINC DIALKYL DITHIOPHOSPHATE:

Result: Possibly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.


Product:

No aspiration toxicity classification

Components:

HEAVY PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

| | | |
|--|--|---------------------------|
|  | | Page: 8 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 11/3/2016 |
| | | SDS Number: 000000252945 |
| Valvoline™ Full Synthetic with MaxLife™ Technology SAE 0W-20 Motor Oil ™ Trademark, Valvoline or its subsidiaries, regised in various countries 852400 | | Version: 1.1 |

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

HEAVY PARAFFINIC DISTILLATE:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

ZINC DIALKYL DITHIOPHOSPHATE:

Ecotoxicology Assessment


Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

No data available

| | | |
|--|--|---------------------------|
|  | | Page: 9 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 11/3/2016 |
| | | SDS Number: 000000252945 |
| Valvoline™ Full Synthetic with MaxLife™ Technology SAE 0W-20 Motor Oil ™ Trademark, Valvoline or its subsidiaries, regised in various countries 852400 | | Version: 1.1 |

Bioaccumulative potential

Components:

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- General advice : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
- Dispose of in accordance with all applicable local, state and federal regulations.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations


REGULATION

| ID NUMBER | PROPER SHIPPING NAME | *HAZARD CLASS | SUBSIDIARY HAZARDS | PACKING GROUP | MARINE POLLUTANT / LTD. QTY. |
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|
| | | | | | |

U.S. DOT - ROAD

| |
|---------------------|
| Not dangerous goods |
| |

CFR_RAIL_C

| | | |
|---|--|---------------------------|
|  | | Page: 10 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 11/3/2016 |
| | | SDS Number: 000000252945 |
| Valvoline™ Full Synthetic with MaxLife™ Technology SAE 0W-20 Motor Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 852400 | | Version: 1.1 |

| |
|---------------------|
| Not dangerous goods |
|---------------------|

U.S. DOT - INLAND WATERWAYS

| |
|---------------------|
| Not dangerous goods |
|---------------------|

TDG_ROAD_C

| |
|---------------------|
| Not dangerous goods |
|---------------------|

TDG_RAIL_C

| |
|---------------------|
| Not dangerous goods |
|---------------------|

TDG_INWT_C

| |
|---------------------|
| Not dangerous goods |
|---------------------|

INTERNATIONAL MARITIME DANGEROUS GOODS

| |
|---------------------|
| Not dangerous goods |
|---------------------|

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

| |
|---------------------|
| Not dangerous goods |
|---------------------|

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

| |
|---------------------|
| Not dangerous goods |
|---------------------|

MX_DG


| |
|---------------------|
| Not dangerous goods |
|---------------------|

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

| | |
|------------------|----|
| Marine pollutant | no |
|------------------|----|

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

| | | |
|--|--|---------------------------|
|  | | Page: 11 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 11/3/2016 |
| | | SDS Number: 000000252945 |
| Valvoline™ Full Synthetic with MaxLife™ Technology SAE 0W-20 Motor Oil ™ Trademark, Valvoline or its subsidiaries, regised in various countries 852400 | | Version: 1.1 |

SARA 311/312 Hazards : No SARA Hazards

SARA 313 Component(s)

| | | |
|---|------------|--------|
| ZINC DIALKYL DITHIOPHOSPHATE | 68649-42-3 | 1.08 % |
| PHOSPHORODITHIOIC ACID, MIXED O,O- BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS | 84605-29-8 | 0.53 % |

Pennsylvania Right To Know

| | | |
|---|--------------|-----------------|
| HEAVY PARAFFINIC DISTILLATE | 64742-54-7 | 70.00 - 90.00 % |
| HYDROTREATED HEAVY PARAFFINIC BASE OIL | 64742-54-7 | 10.00 - 20.00 % |
| LUBRICANT ADDITIVE | Not Assigned | 5.00 - 10.00 % |
| HEAVY PARAFFINIC DISTILLATE | 64742-54-7 | 1.00 - 5.00 % |

New Jersey Right To Know


| | | |
|---|--------------|-----------------|
| HEAVY PARAFFINIC DISTILLATE | 64742-54-7 | 70.00 - 90.00 % |
| HYDROTREATED HEAVY PARAFFINIC BASE OIL | 64742-54-7 | 10.00 - 20.00 % |
| LUBRICANT ADDITIVE | Not Assigned | 5.00 - 10.00 % |
| HEAVY PARAFFINIC DISTILLATE | 64742-54-7 | 1.00 - 5.00 % |
| ZINC DIALKYL DITHIOPHOSPHATE | 68649-42-3 | 1.00 - 5.00 % |
| DINONYL DIPHENYLAMINE | 36878-20-3 | 1.00 - 5.00 % |

California Prop 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

The components of this product are reported in the following inventories:

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL.
- AUSTR : Not in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECL : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory

| | | |
|--|--|---------------------------|
|  | | Page: 12 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 11/3/2016 |
| | | SDS Number: 000000252945 |
| Valvoline™ Full Synthetic with MaxLife™ Technology SAE 0W-20 Motor Oil ™ Trademark, Valvoline or its subsidiaries, regised in various countries 852400 | | Version: 1.1 |

IECSC : On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/31/2016

| | | | | | | | |
|--|---|---------------|----------|---------------------|----------|------------------------|----------|
| <p>NFPA:</p> <div style="text-align: center;"> <p>Flammability</p>  <p>Health Instability</p> <p>Special hazard.</p> </div> | <p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white; text-align: center;">HEALTH</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: red; color: white; text-align: center;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: yellow; text-align: center;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p> | HEALTH | 1 | FLAMMABILITY | 1 | PHYSICAL HAZARD | 0 |
| HEALTH | 1 | | | | | | |
| FLAMMABILITY | 1 | | | | | | |
| PHYSICAL HAZARD | 0 | | | | | | |


NFPA Flammable and Combustible Liquids Classification
Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.

- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H401 Toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the

| | | |
|---|--|---------------------------|
|  | | Page: 13 |
| SAFETY DATA SHEET | | Revision Date: 07/31/2016 |
| | | Print Date: 11/3/2016 |
| | | SDS Number: 000000252945 |
| Valvoline™ Full Synthetic with MaxLife™ Technology SAE 0W-20 Motor Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 852400 | | Version: 1.1 |

information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System