



**SAFETY DATA SHEET**  
Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

**SECTION 1. IDENTIFICATION**

Product name : Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Product code : 881155

**Manufacturer or supplier's details**

Company name of supplier : Valvoline LLC

Address : 100 Valvoline Way  
Lexington, KY 40509  
United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvoline.com

Emergency telephone number : +1-800-VALVOLINE (+1-800-825-8654)

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Not a hazardous substance or mixture.

**GHS label elements**

Not a hazardous substance or mixture.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY	64742-54-7	>= 15 - < 20



**SAFETY DATA SHEET**  
Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

PARAFFINIC		
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	$\geq 10 - < 15$
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	$\geq 1.5 - < 5$
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1	$\geq 1.5 - < 5$
Distillates (petroleum), solvent- dewaxed heavy paraffinic; Baseoil - unspecified	64742-56-9	$\geq 1 - < 1.5$
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	$\geq 0.5 - < 1$

Actual concentration is withheld as a trade secret

#### SECTION 4. FIRST AID MEASURES

- General advice : Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
- Notes to physician : Treat symptomatically.
- No hazards which require special first aid measures.

#### SECTION 5. FIREFIGHTING MEASURES

- Hazardous combustion products : carbon dioxide and carbon monoxide



**SAFETY DATA SHEET**  
Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

- Further information : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).  
Keep in suitable, closed containers for disposal.

---

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.
- Conditions for safe storage : Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : No materials to be especially mentioned.
- Further information on storage stability : No decomposition if stored and applied as directed.

---

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA	5 mg/m <sup>3</sup>	ACGIH



**SAFETY DATA SHEET**  
 Valvoline™ European Vehicle SAE 0W-40  
 Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

		(Inhalable particulate matter)		
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified	64742-56-9	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH



**SAFETY DATA SHEET**  
Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

---

**Personal protective equipment**

- Respiratory protection : No personal respiratory protective equipment normally required.
- Eye protection : Safety glasses
- Skin and body protection : Protective suit
- Hygiene measures : General industrial hygiene practice.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : 428 °F / 220 °C  
Method: Cleveland open cup
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Self-ignition : No data available
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapour pressure : No data available
- Relative vapour density : No data available
- Relative density : No data available



**SAFETY DATA SHEET**  
Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

---

Density	:	0.843 g/cm <sup>3</sup>
Solubility(ies)	:	
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	77 mm <sup>2</sup> /s (104 °F / 40 °C)
Oxidizing properties	:	No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Stable under recommended storage conditions. No hazards to be specially mentioned.
Conditions to avoid	:	None known.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**

Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**



**SAFETY DATA SHEET**  
Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation

Result : Slight, transient irritation



**SAFETY DATA SHEET**  
Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Species : Rabbit  
Result : No skin irritation

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:**

Species : Rabbit  
Result : Slight, transient irritation

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Result : Slight, transient irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : No eye irritation  
Assessment : No eye irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : No eye irritation  
Assessment : No eye irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : No eye irritation  
Assessment : No eye irritation

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Species : Rabbit  
Result : No eye irritation

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:**

Species : Rabbit  
Result : Slight, transient irritation



**SAFETY DATA SHEET**  
Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Result : Slight, transient irritation  
Assessment : Slight, transient irritation

**Respiratory or skin sensitisation**

**Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Test Type : Buehler Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:**

Test Type : Buehler Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Test Type : Buehler Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)



**SAFETY DATA SHEET**  
Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen., Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

**IARC** Group 1: Carcinogenic to humans  
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC  
64742-65-0  
(Mineral oils, untreated or mildly treated)

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** Known to be human carcinogen  
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC  
64742-65-0  
(Mineral Oils: Untreated and Mildly Treated)

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

May be fatal if swallowed and enters airways.



**SAFETY DATA SHEET**  
Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

No aspiration toxicity classification

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

May be fatal if swallowed and enters airways.

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:**

No aspiration toxicity classification

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

No aspiration toxicity classification

**Further information**

**Product:**

Remarks : No data available

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Product:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
plants Exposure time: 72 h

Toxicity to fish (Chronic : NOEC (Fish): 10 mg/l  
toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l



**SAFETY DATA SHEET**  
Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

aquatic invertebrates  
(Chronic toxicity)

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
plants Exposure time: 72 h

Toxicity to fish (Chronic : NOEC (Fish): 10 mg/l  
toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l  
aquatic invertebrates  
(Chronic toxicity)

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l



**SAFETY DATA SHEET**  
Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

---

aquatic invertebrates		Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	:	NOELR (Oncorhynchus mykiss (rainbow trout)): >= 1,000 mg/l Exposure time: 14 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEL (Daphnia (water flea)): 10 mg/l Exposure time: 21 d Test substance: WAF Method: OECD Test Guideline 211

**Ecotoxicology Assessment**

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:**

Toxicity to fish	:	LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates	:	NOEL (Daphnia magna (Water flea)): 10 mg/l Exposure time: 21 d



**SAFETY DATA SHEET**  
Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

(Chronic toxicity)                      Test Type: semi-static test  
                                                    Test substance: WAF  
                                                    Method: OECD Test Guideline 211

**Ecotoxicology Assessment**

Acute aquatic toxicity                    : Not classified based on available information.

Chronic aquatic toxicity                : Not classified based on available information.

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Toxicity to fish                            : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
                                                    Exposure time: 96 h  
                                                    Test Type: static test  
                                                    Test substance: WAF

Toxicity to daphnia and other        : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
aquatic invertebrates                    Exposure time: 48 h  
                                                    Test Type: static test  
                                                    Test substance: WAF

Toxicity to algae/aquatic               : NOEL (Pseudokirchneriella subcapitata (algae)): >= 100 mg/l  
plants                                            End point: Growth inhibition  
                                                    Exposure time: 72 h  
                                                    Test Type: static test  
                                                    Test substance: WAF

**Ecotoxicology Assessment**

Acute aquatic toxicity                    : Not classified based on available information.

Chronic aquatic toxicity                : Not classified based on available information.

**Persistence and degradability**

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Biodegradability                         : Result: Not readily biodegradable.  
                                                    Biodegradation: 2 - 4 %  
                                                    Exposure time: 28 d  
                                                    Method: OECD Test Guideline 301B

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:**

Biodegradability                         : Result: Inherently biodegradable.  
                                                    Biodegradation: 31 %  
                                                    Exposure time: 28 d  
                                                    Method: OECD Test Guideline 301B



**SAFETY DATA SHEET**  
Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

---

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Biodegradability : Result: Inherently biodegradable.  
Method: OECD Test Guideline 301F

**Bioaccumulative potential**

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Partition coefficient: n- : log Pow: Expected > 7  
octanol/water

**Mobility in soil**

No data available

**Other adverse effects**

**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
Protection of Stratospheric Ozone - CAA Section 602 Class I  
Substances  
Remarks: This product neither contains, nor was  
manufactured with a Class I or Class II ODS as defined by the  
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +  
B).

Additional ecological : No data available  
information

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

Contaminated packaging : Empty containers should be taken to an approved waste  
handling site for recycling or disposal.

---

**SECTION 14. TRANSPORT INFORMATION**

**International Regulations**

**UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good



**SAFETY DATA SHEET**  
Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

---

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations**

**49 CFR**

Not regulated as a dangerous good

**Special precautions for user**

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

---

**SECTION 15. REGULATORY INFORMATION**

**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

**Clean Water Act**

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any priority pollutants related to the U.S. Clean Water Act

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307



**SAFETY DATA SHEET**  
Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

**US State Regulations**

**Massachusetts Right To Know**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified	64742-56-9
CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM)	64742-70-7

**Pennsylvania Right To Know**

DECENE-1 HOMOPOLYMER HYDROGENATED	68037-01-4
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
PROPRIETARY SUBSTANCE OF INFINEUM P6660 US, 0-280491	Not Assigned
PROPRIETARY OF INFINEUM SV203 166 KG	Not Assigned
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified	64742-56-9
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts	113706-15-3
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0

**Maine Chemicals of High Concern**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
--------------------------------------------------------	------------

**Vermont Chemicals of High Concern**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
--------------------------------------------------------	------------

**Washington Chemicals of High Concern**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
--------------------------------------------------------	------------

**California Prop. 65**

WARNING: This product can expose you to chemicals including DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC, DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



**SAFETY DATA SHEET**  
Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

**California List of Hazardous Substances**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7

**California Permissible Exposure Limits for Chemical Contaminants**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1

**The components of this product are reported in the following inventories:**

TCSI	: On the inventory, or in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory
AIIC	: Not in compliance with the inventory
DSL	: On the inventory, or in compliance with the inventory
	ZINC BIS[O-(6-METHYLHEPTYL)]BIS[O-SEC-BUTYL]BIS(DITHIOPHOSPHATE)
ENCS	: Not in compliance with the inventory
ISHL	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: Not in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory
TECI	: Not in compliance with the inventory

**TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

**Inventories**



**SAFETY DATA SHEET**  
 Valvoline™ European Vehicle SAE 0W-40  
 Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022


Print Date:  
02/20/2023

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

**SECTION 16. OTHER INFORMATION**

**Further information**

**NFPA 704:**



**HMIS® IV:**

<b>HEALTH</b>	/	<b>0</b>
<b>FLAMMABILITY</b>		<b>1</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- ACGIH / TWA : 8-hour, time-weighted average
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -



# SAFETY DATA SHEET

Valvoline™ European Vehicle SAE 0W-40  
Synthetic Motor Oil

Version: 1.5

Revision Date: 09/15/2022

Print Date:  
02/20/2023

Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 09/15/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information : 000000273583