



**SAFETY DATA SHEET**  
Valvoline™ EXTENDED PROTECTION FULL  
SYNTHETIC MULTI-VEHICLE AUTOMATIC  
TRANSMISSION FLUID

Version: 1.0

Revision Date: 03/28/2022

Print Date:  
04/07/2023

29 CFR 1910.1200 (OSHA HazCom 2012)

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier**

Trade name : Valvoline™ EXTENDED PROTECTION FULL  
SYNTHETIC MULTI-VEHICLE AUTOMATIC  
TRANSMISSION FLUID

Product code : 899177

<b>Details of the supplier of the safety data sheet</b> Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825)  SDS@valvoline.com	<b>Emergency telephone number</b> 1-800-VALVOLINE (1-800-825-8654)  <b>Regulatory Information Number</b> 1-800-TEAMVAL (1-800-832-6825)  <b>Product Information</b> 1-800-TEAMVAL (1-800-832-6825)
---	---

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification**

Not a hazardous substance or mixture.

**GHS label elements**

Not a hazardous substance or mixture.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	>=80.00 - < 90.00
LUBRICATING OILS, PETROLEUM, C15-30,	72623-86-0	Asp. Tox. 1; H304	>=1.50 - < 5.00



**SAFETY DATA SHEET**  
Valvoline™ EXTENDED PROTECTION FULL  
SYNTHETIC MULTI-VEHICLE AUTOMATIC  
TRANSMISSION FLUID

Version: 1.0

Revision Date: 03/28/2022

Print Date:  
04/07/2023

HYDROTREATED

Actual concentration is withheld as a trade secret

---

#### SECTION 4. FIRST AID MEASURES

- General advice : Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
- Notes to physician : No hazards which require special first aid measures.  
  
Treat symptomatically.

---

#### SECTION 5. FIREFIGHTING MEASURES

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
- Specific extinguishing methods :
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.



# SAFETY DATA SHEET

Valvoline™ EXTENDED PROTECTION FULL SYNTHETIC MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID

Version: 1.0

Revision Date: 03/28/2022

Print Date:  
04/07/2023

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).  
Keep in suitable, closed containers for disposal.

## SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.
- Conditions for safe storage : Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : No materials to be especially mentioned.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable particulate matter	ACGIH
		PEL	5 mg/m3 particulate	CAL PEL

### Personal protective equipment

- Respiratory protection : No personal respiratory protective equipment normally required.
- Eye protection : Safety glasses
- Skin and body protection : Protective suit



**SAFETY DATA SHEET**  
Valvoline™ EXTENDED PROTECTION FULL  
SYNTHETIC MULTI-VEHICLE AUTOMATIC  
TRANSMISSION FLUID

Version: 1.0

Revision Date: 03/28/2022

Print Date:  
04/07/2023

Hygiene measures : General industrial hygiene practice.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 394 - 480 °F / 201 - 249 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.838 g/cm<sup>3</sup>

Solubility(ies)

    Water solubility : No data available

    Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available



**SAFETY DATA SHEET**  
Valvoline™ EXTENDED PROTECTION FULL  
SYNTHETIC MULTI-VEHICLE AUTOMATIC  
TRANSMISSION FLUID

Version: 1.0

Revision Date: 03/28/2022

Print Date:  
04/07/2023

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : No data available

Viscosity, kinematic : 28.26 mm<sup>2</sup>/s (104 °F / 40 °C)

Oxidizing properties : No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : Stable under recommended storage conditions.  
No hazards to be specially mentioned.

Conditions to avoid : None known.  
No data available

Incompatible materials : Strong oxidizing agents  
Not applicable

Hazardous decomposition products : No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**

Not classified based on available information.

**Components:**

**Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

**LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute



**SAFETY DATA SHEET**  
Valvoline™ EXTENDED PROTECTION FULL  
SYNTHETIC MULTI-VEHICLE AUTOMATIC  
TRANSMISSION FLUID

Version: 1.0

Revision Date: 03/28/2022

Print Date:  
04/07/2023

inhalation toxicity  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

**Skin corrosion/irritation**

Not classified based on available information.

**Components:**

**Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

**LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:**

Species : Rabbit  
Result : No skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:**

**Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

Result : No eye irritation  
Assessment : No eye irritation

**LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:**

Species : Rabbit  
Result : No eye irritation

**Respiratory or skin sensitisation**

**Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:**

Test Type : Buehler Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is



**SAFETY DATA SHEET**  
Valvoline™ EXTENDED PROTECTION FULL  
SYNTHETIC MULTI-VEHICLE AUTOMATIC  
TRANSMISSION FLUID

Version: 1.0

Revision Date: 03/28/2022

Print Date:  
04/07/2023

identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Components:**

**Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

May be fatal if swallowed and enters airways.

**LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

May be fatal if swallowed and enters airways.

**Further information**

**Product:**

Remarks : No data available

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Product:**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Acute aquatic toxicity Category 2; Toxic to aquatic life.

Long-term (chronic) aquatic hazard : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

**Components:**

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l  
Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l



**SAFETY DATA SHEET**  
Valvoline™ EXTENDED PROTECTION FULL  
SYNTHETIC MULTI-VEHICLE AUTOMATIC  
TRANSMISSION FLUID

Version: 1.0

Revision Date: 03/28/2022

Print Date:  
04/07/2023

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

**LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:**

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l  
Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l  
Exposure time: 21 d  
Test substance: WAF  
Method: OECD Test Guideline 211

**Persistence and degradability**

**Components:**

**LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B



**SAFETY DATA SHEET**  
Valvoline™ EXTENDED PROTECTION FULL  
SYNTHETIC MULTI-VEHICLE AUTOMATIC  
TRANSMISSION FLUID

Version: 1.0

Revision Date: 03/28/2022

Print Date:  
04/07/2023

No data available

**Bioaccumulative potential**

**Components:**

No data available

**Mobility in soil**

**Components:**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life., Harmful to aquatic life with long lasting effects.

**Components:**

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

General advice

: The product should not be allowed to enter drains, water courses or the soil.

---

**SECTION 14. TRANSPORT INFORMATION**

**International Regulations**

**UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations**

**CFR\_ROAD**

Not regulated as a dangerous good



**SAFETY DATA SHEET**  
Valvoline™ EXTENDED PROTECTION FULL  
SYNTHETIC MULTI-VEHICLE AUTOMATIC  
TRANSMISSION FLUID

Version: 1.0

Revision Date: 03/28/2022

Print Date:  
04/07/2023

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION**

**EPCRA - Emergency Planning and Community Right-to-Know Act**

**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
SULFUR DIOXIDE	7446-09-5	500	

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

**Clean Water Act**

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

**The components of this product are reported in the following inventories:**

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory



**SAFETY DATA SHEET**  
 Valvoline™ EXTENDED PROTECTION FULL  
 SYNTHETIC MULTI-VEHICLE AUTOMATIC  
 TRANSMISSION FLUID

Version: 1.0

Revision Date: 03/28/2022

Print Date:  
04/07/2023

AIIC	:	Not in compliance with the inventory
DSL	:	All components of this product are on the Canadian DSL
ENCS	:	On the inventory, or in compliance with the inventory
ISHL	:	Not in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
NZIoC	:	On the inventory, or in compliance with the inventory
TECI	:	Not in compliance with the inventory

**TSCA list**

No substances are subject to a Significant New Use Rule.  
 No substances are subject to TSCA 12(b) export notification requirements.

**Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

**SECTION 16. OTHER INFORMATION**

**Further information**

Internal information : 000000279439

<p><b>NFPA:</b></p> <p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard</p>	<p><b>HMIS III:</b></p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;"><b>HEALTH</b></td> <td align="center"><b>0/</b></td> </tr> <tr> <td style="background-color: red; color: white;"><b>FLAMMABILITY</b></td> <td align="center"><b>1</b></td> </tr> <tr> <td style="background-color: yellow;"><b>PHYSICAL HAZARD</b></td> <td align="center"><b>0</b></td> </tr> </table> <p>0 = not significant, 1 =Slight,          2 = Moderate, 3 = High          4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>0/</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>0/</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

**NFPA Flammable and Combustible Liquids Classification**





**SAFETY DATA SHEET**  
Valvoline™ EXTENDED PROTECTION FULL  
SYNTHETIC MULTI-VEHICLE AUTOMATIC  
TRANSMISSION FLUID

Version: 1.0

Revision Date: 03/28/2022

Print Date:  
04/07/2023

---

STOT : Specific Target Organ Toxicity  
TLV : Threshold Limit Value  
TWA : Time-weighted average  
vPvB : Very Persistent and Very Bioaccumulative  
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
DOT : Department of Transportation  
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
HMIRC : Hazardous Materials Information Review Commission  
HMIS : Hazardous Materials Identification System  
NFPA : National Fire Protection Association  
NIOSH : National Institute for Occupational Safety and Health  
OSHA : Occupational Safety and Health Administration  
PMRA : Health Canada Pest Management Regulatory Agency  
RTK : Right to Know  
WHMIS : Workplace Hazardous Materials Information System