		Page: 1
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0173308
NAPA® PREMIUM CONVENTIONAL SAE 85W-140 GEAR OIL		Version: 1.2
851642		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : NAPA® PREMIUM CONVENTIONAL SAE 85W-140 GEAR OIL

Recommended use of the chemical and restrictions on use

<p>Details of the supplier of the safety data sheet</p> <p>Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509 United States of America</p> <p>SDS@valvoline.com</p>	<p>Emergency telephone number 1-800-VALVOLINE</p> <p>Regulatory Information Number 1-800-TEAMVAL</p> <p>Product Information 1-800-TEAMVAL</p>
---	--

SECTION 2. HAZARDS IDENTIFICATION


GHS Classification

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Category 1


GHS Label element

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.

Precautionary Statements : **Prevention:**
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling.
Contaminated work clothing must not be allowed out of the

		Page: 2
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0173308
NAPA® PREMIUM CONVENTIONAL SAE 85W-140 GEAR OIL		Version: 1.2
851642		

workplace.

Wear eye protection/ face protection.

Wear protective gloves.

Response:

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation or rash occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention.

Take off contaminated clothing and wash before reuse.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.


SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components


Chemical Name	CAS-No.	Classification	Concentration (%)
RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED	64742-62-7	Not a hazardous substance or mixture.	94.92
MINERAL OIL		Not a hazardous substance or mixture.	1.39
ALKYL PHOSPHATE		Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335	1.02
LONG-CHAIN ALKYL AMINE		Acute Tox. 4; H302 Acute Tox. 2; H330 Acute Tox. 3; H311	0.34

		Page: 3
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0173308
NAPA® PREMIUM CONVENTIONAL SAE 85W-140 GEAR OIL		Version: 1.2
851642		

		Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	
--	--	--	--

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Dizziness
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
- Notes to physician : No hazards which require special first aid measures.

		Page: 4
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0173308
NAPA® PREMIUM CONVENTIONAL SAE 85W-140 GEAR OIL		Version: 1.2
851642		


SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
Oxides of phosphorus
- Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

		Page: 5
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0173308
NAPA® PREMIUM CONVENTIONAL SAE 85W-140 GEAR OIL		Version: 1.2
851642		


SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED	64742-62-7	PEL	500 ppm 2,000 mg/m ³	OSHA_TRANS
		REL	5 mg/m ³ Mist.	NIOSH/GUIDE
		STEL	10 mg/m ³ Mist.	NIOSH/GUIDE
MINERAL OIL		PEL	5 mg/m ³ Mist.	OSHA_TRANS
		REL	5 mg/m ³ Mist.	NIOSH/GUIDE
		STEL	10 mg/m ³ Mist.	NIOSH/GUIDE
		PEL	5 mg/m ³ Mist.	OSHA_TRANS

		Page: 6
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0173308
NAPA® PREMIUM CONVENTIONAL SAE 85W-140 GEAR OIL		Version: 1.2
851642		

		TWA	5 mg/m3 Mist.	TN OEL
		TWA	5 mg/m3 Inhalable fraction.	ACGIH

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection


: Wear as appropriate:
impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures

: Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Colour : amber
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : 600.01 °F / 315.56 °C
(1,013.333333 hPa)
Calculated Phase Transition Liquid/Gas
- Flash point : > 390 °F / > 199 °C
Method: Cleveland open cup

		Page: 7
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0173308
NAPA® PREMIUM CONVENTIONAL SAE 85W-140 GEAR OIL		Version: 1.2
851642		

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : 7 %(V)
Calculated Explosive Limit

Lower explosion limit : 0.9 %(V)
Calculated Explosive Limit

Vapour pressure : 0.1 hPa (20 °C)
Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 0.9040 g/cm³ (15.56 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 394 mm²/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY


Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide

		Page: 8
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0173308
NAPA® PREMIUM CONVENTIONAL SAE 85W-140 GEAR OIL		Version: 1.2
851642		

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation under GHS.
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD 50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

LD 50 (Rabbit): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

LONG-CHAIN ALKYL AMINE:

Acute oral toxicity :
Assessment: The component/mixture is classified as acute oral toxicity, category 4.

Acute inhalation toxicity : Assessment: The component/mixture is classified as acute inhalation toxicity, category 2.

Acute dermal toxicity : Assessment: The component/mixture is classified as acute dermal toxicity, category 3.

Skin corrosion/irritation

Causes skin irritation.

Product:


Remarks: May cause skin irritation and/or dermatitis.

Result: Repeated exposure may cause skin dryness or cracking.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Species: Rabbit

		Page: 9
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0173308
NAPA® PREMIUM CONVENTIONAL SAE 85W-140 GEAR OIL		Version: 1.2
851642		

Result: Not irritating to skin

MINERAL OIL:

Result: Mildly irritating to skin

ALKYL PHOSPHATE:

Result: Corrosive to skin

LONG-CHAIN ALKYL AMINE:

Result: Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Species: Rabbit

Result: Not irritating to eyes

MINERAL OIL:

Result: Mildly irritating to eyes

ALKYL PHOSPHATE:

Result: Corrosive to eyes

LONG-CHAIN ALKYL AMINE:

Result: Corrosive to eyes

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

LONG-CHAIN ALKYL AMINE:

Assessment: May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.


Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:

		Page: 10
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0173308
NAPA® PREMIUM CONVENTIONAL SAE 85W-140 GEAR OIL		Version: 1.2
851642		

ALKYL PHOSPHATE:
Assessment: May cause respiratory irritation.

STOT - repeated exposure
Not classified based on available information.

Aspiration toxicity
Not classified based on available information.

Product:
No aspiration toxicity classification

Components:
RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:
No aspiration toxicity classification

Further information
Product:
Remarks: No data available

Carcinogenicity:
IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.


SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:
RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

		Page: 11
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0173308
NAPA® PREMIUM CONVENTIONAL SAE 85W-140 GEAR OIL		Version: 1.2
851642		

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l
 Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
 Exposure time: 21 d
 Test substance: WAF
 Method: OECD Test Guideline 211

LONG-CHAIN ALKYL AMINE:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 2 - 4 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

Bioaccumulative potential

Components:

No data available

Mobility in soil

Components:

No data available


Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

Components:

		Page: 12
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0173308
NAPA® PREMIUM CONVENTIONAL SAE 85W-140 GEAR OIL		Version: 1.2
851642		

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C


Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

		Page: 13
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0173308
NAPA® PREMIUM CONVENTIONAL SAE 85W-140 GEAR OIL		Version: 1.2
851642		

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Acute Health Hazard


SARA 313 Component(s) : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
SARA 313

Pennsylvania Right To Know

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED	64742-62-7	90.00 - 100.00 %
LUBRICANT ADDITIVE	Not Assigned	5.00 - 10.00 %

New Jersey Right To Know

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED	64742-62-7	90.00 - 100.00 %
LUBRICANT ADDITIVE	Not Assigned	5.00 - 10.00 %
HEAVY PARAFFINIC DISTILLATE	64742-54-7	1.00 - 5.00 %

		Page: 14
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0173308
NAPA® PREMIUM CONVENTIONAL SAE 85W-140 GEAR OIL		Version: 1.2
851642		

MINERAL OIL	Not Assigned	1.00 - 5.00 %
ALKYL PHOSPHATE	Not Assigned	1.00 - 5.00 %
DISTILLATES (PETROLEUM), SOLVENT- DEWAXED HEAVY PARAFFINIC	64742-65-0	0.10 - 1.00 %


California Prop 65 Proposition 65 warnings are not required for this product based on the results of a risk assessment.

The components of this product are reported in the following inventories:

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL.
- AUSTR : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECL : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECL (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

		Page: 15
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0173308
NAPA® PREMIUM CONVENTIONAL SAE 85W-140 GEAR OIL		Version: 1.2
851642		

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/31/2016

<p>NFPA:</p> <div style="text-align: center;"> <p>Flammability</p>  <p>Health Instability</p> <p>Special hazard.</p> </div>	<p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: yellow;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	1	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	1						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification
Combustible Liquid Class IIIB


Full text of H-Statements referred to under sections 2 and 3.

- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H335 May cause respiratory irritation.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

Further information

Sources of key data used to compile the Safety Data Sheet
 Valvoline internal data including own and sponsored test reports
 The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).

		Page: 16
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0173308
NAPA® PREMIUM CONVENTIONAL SAE 85W-140 GEAR OIL		Version: 1.2
851642		

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System