



Revision Number: 004.0

Issue date: 06/07/2019

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE SF 7633 AE known as Non-Chlorinated Parts Cleaner	IDH number:	234935
Product type/use:	Cleaner	Item number:	30545
Restriction of Use:	None identified	Region:	United States
Company address:	Contact information:		
Henkel Corporation	Telephone: +1 (860) 571-5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CONTENTS UNDER PRESSURE.
 EXTREMELY FLAMMABLE AEROSOL.
 MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.
 CAUSES SKIN IRRITATION.
 CAUSES SERIOUS EYE IRRITATION.
 MAY CAUSE DROWSINESS OR DIZZINESS.
 SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.
 MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL	1
SKIN IRRITATION	2
EYE IRRITATION	2A
REPRODUCTIVE TOXICITY	2
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2
ASPIRATION HAZARD	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe mist or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, clothing, eye and face protection.

Response: IF SWALLOWED: Immediately call a physician or poison control center. IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. Do NOT induce vomiting. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Acetone	67-64-1	60 - 80
Propane	74-98-6	10 - 30
n-Heptane	142-82-5	5 - 10
Xylenes	1330-20-7	1 - 5
Ethylbenzene	100-41-4	0.1 - 1
Toluene	108-88-3	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Get medical attention.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Ingestion: Do not induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide. Dry powder.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. If water is used, fog nozzles are preferable.

Unusual fire or explosion hazards: Cool pressurized can containers with jet of water. Containers may explode. Contents under pressure. Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back. Exposure to temperatures above 49°C (120°F) may cause container to burst. Do not puncture or incinerate pressurized containers.

Hazardous combustion products:

Oxides of carbon. Irritating organic vapours.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Do not allow product to enter sewer or waterways.

Clean-up methods:

Spilled liquid is combustible and can be ignited by heat, flames, sparks, or other sources of ignition. Remove all sources of ignition. Ensure adequate ventilation. Keep unnecessary personnel away. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling:

During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not puncture or incinerate pressurized containers. Refer to Section 8.

Storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Acetone	250 ppm TWA 500 ppm STEL	1,000 ppm (2,400 mg/m3) PEL	None	None
Propane	D: Simple asphyxiant, EX: Explosion hazard (Simple asphyxiant.)	1,000 ppm (1,800 mg/m3) PEL	None	None
n-Heptane	400 ppm TWA 500 ppm STEL	500 ppm (2,000 mg/m3) PEL	None	None
Xylenes	100 ppm TWA 150 ppm STEL	100 ppm (435 mg/m3) PEL	None	None
Ethylbenzene	20 ppm TWA	100 ppm (435 mg/m3) PEL	None	None
Toluene	20 ppm TWA	200 ppm TWA 300 ppm Ceiling 500 ppm MAX. CONC 10 minutes	None	None

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Use an organic vapor respirator for concentrations exceeding the Occupational Exposure Limit. Do not inhale vapors and fumes.

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection:

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Aerosol
Color:	Water white, Clear
Odor:	Solvent
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	760 mm hg
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Vapor density:	Not available.
Flash point:	-23 °C (-9.4 °F) ; This product exhibits no flashback when tested for flame extension.
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Not available.
Partition coefficient (n-octanol/water):	Not available.
VOC content:	768.4 g/l
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Irritating and toxic gases or fumes may be released during a fire.
Incompatible materials:	Acids and bases. Oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Do not puncture, incinerate, or expose to temperatures above 48.9 °C (120 °F). Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: May cause central nervous system effects with nausea, dizziness and headache. May cause respiratory tract irritation.

Skin contact: Causes skin irritation. Prolonged or repeated contact with this product may dry and/or defat the skin.

Eye contact: Causes serious eye irritation.

Ingestion: Principal hazard of ingestion is aspiration into the lungs and subsequent pneumonitis. Central nervous system depression, including dizziness, drowsiness, fatigue, nausea, headache, unconsciousness.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Acetone	Oral LD50 (Mouse) = 5.2 g/kg Oral LD50 (Mouse) = 3,000 mg/kg Oral LD50 (Rabbit) = 5,340 mg/kg Oral LD50 (Rat) = 5,800 mg/kg Oral LD50 (Rat) = 9,800 mg/kg Dermal LD50 (Rabbit) = 20,000 mg/kg	Central nervous system, Irritant
Propane	None	Cardiac, Central nervous system, Irritant
n-Heptane	None	Central nervous system, Irritant
Xylenes	Oral LD50 (Rat) = 6,670 mg/kg Oral LD50 (Rat) = 3,523 - 8,600 mg/kg Oral LD50 (Rat) = 4,300 mg/kg Dermal LD50 (Rabbit) = > 43 g/kg	Cardiac, Central nervous system, Irritant, Kidney, Liver
Ethylbenzene	Oral LD50 (Rat) = 5.46 g/kg Oral LD50 (Rat) = 3,500 mg/kg Dermal LD50 (Rabbit) = 17,800 mg/kg	Irritant, Central nervous system
Toluene	Oral LD50 (Rat) = 2.6 g/kg Dermal LD50 (Rabbit) = 12,124 mg/kg	Behavioral, Cardiac, Central nervous system, Developmental, Ear, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Acetone	No	No	No
Propane	No	No	No
n-Heptane	No	No	No
Xylenes	No	No	No
Ethylbenzene	No	Group 2B	No
Toluene	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.
Hazardous waste number: D001: Ignitable.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Aerosols
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None
DOT Hazardous Substance(s): Xylene (mixed), Acetone

International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, flammable
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

Water Transportation (IMO/MDG)

Proper shipping name: AEROSOLS
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire, Pressure
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Xylenes (CAS# 1330-20-7). Ethylbenzene (CAS# 100-41-4).
CERCLA Reportable quantity: Acetone (CAS# 67-64-1) 5,000 lbs. (2,270 kg)
Propane (CAS# 74-98-6) 100 lbs. (45.4 kg)
n-Heptane (CAS# 142-82-5) 100 lbs. (45.4 kg)
Xylenes (CAS# 1330-20-7) 100 lbs. (45.4 kg)
California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2

Prepared by: Product Safety and Regulatory Affairs

Issue date: 06/07/2019

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.