



Revision Number: 004.0

Issue date: 01/03/2018

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE PC 9599 B HARDENER known as Nordbak FastCure Wearing CMPD 6LB PTB	IDH number:	702207
Product type:	Epoxy Hardener	Item number:	96373_2442151
Restriction of Use:	None identified	Region:	United States
Company address:	Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067	Contact information:	Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: COMBUSTIBLE LIQUID.
CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
MAY CAUSE AN ALLERGIC SKIN REACTION.
MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED.
SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	4
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1
REPRODUCTIVE TOXICITY	2

PICTOGRAM(S)



Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection. In case of inadequate ventilation wear respiratory protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Aluminium oxide - non fibrous form	1344-28-1	50 - 60
Silicon carbide	409-21-2	10 - 20
N-Aminoethylpiperazine	140-31-8	5 - 10
4,4'-Isopropylidenediphenol	80-05-7	5 - 10
4-Nonylphenol, branched	84852-15-3	1 - 5
Diethylenetriamine	111-40-0	1 - 5
Triethanolamine	102-71-6	1 - 5
Piperazine	110-85-0	1 - 5
Silicon dioxide	7631-86-9	1 - 5
1,4-Phenylenediamine-terephthaloyl chloride copolymer	26125-61-1	0.1 - 1
Benzyltrimethylamine	103-83-3	0.1 - 1
Quartz (SiO ₂), <1% respirable	14808-60-7	0.1 - 1
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Oxides of carbon, oxides of nitrogen, irritating organic vapors. Ammonia. Phenolics. Nitric acid.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Immediately contact emergency personnel. Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Clean residue with soap and water. Store in a closed container until ready for disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling:	Do not taste or swallow. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation. Refer to Section 8. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Make sure containers are properly grounded before use or transfer of material.
Storage:	Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Store away from heat, sparks, flames, or other sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Aluminium oxide - non fibrous form	1 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 50 MPPCF TWA Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Silicon carbide	3 mg/m3 TWA Respirable fraction. 10 mg/m3 TWA Inhalable fraction. 0.1 FIBERS/CM3 TWA Fiber.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust.	None	None
N-Aminoethylpiperazine	None	None	None	None
4,4'-Isopropylidenediphenol	None	None	None	None
4-Nonylphenol, branched	None	None	None	None
Diethylenetriamine	(SKIN) 1 ppm TWA	None	None	None
Triethanolamine	5 mg/m3 TWA	None	None	None
Piperazine	0.03 ppm TWA (as piperazine) Inhalable fraction and vapor. (Respiratory sensitization) (Dermal sensitization)	None	None	None
Silicon dioxide	6 mg/m3 TWA	20 MPPCF TWA 0.8 mg/m3 TWA	None	3 mg/m3 TWA Respirable fraction.
1,4-Phenylenediamine-terephthaloyl chloride copolymer	None	None	None	None
Benzylidimethylamine	None	None	None	None
Quartz (SiO2), <1% respirable	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust.	None	None
N-(3- (Trimethoxysilyl)propyl)ethylenediamine	None	None	None	None

Engineering controls:	Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s).
Eye/face protection:	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.
Skin protection:	Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Butyl rubber gloves. Nitrile gloves. Viton gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Blue
Odor:	Slight, Ammoniacal
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	Not available.
Boiling point/range:	Not applicable
Melting point/ range:	Not available.
Specific gravity:	2.716
Vapor density:	Not available.
Flash point:	88 °C (190.4 °F) Setaflash Closed Cup
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Slightly soluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	< 1.0 %; < 10 g/l (value for resin and hardener together) (estimated)
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Ammonia. Phenolics. Nitric acid. Irritating organic vapours.
Incompatible materials:	Strong Lewis acids. Strong mineral acids. Strong bases. Strong oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation: May cause allergic respiratory reaction. These symptoms, which can include chest tightness, wheezing, cough, shortness of breath or asthma attack, could be immediate or delayed (up to several hours after exposure).

Skin contact: Corrosive to skin. Causes skin burns. May cause allergic skin reaction.

Eye contact: Causes serious eye damage.

Ingestion: Irritation and corrosive action can occur in the mouth, stomach tissue and digestive tract if swallowed. May cause an aspiration hazard if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Aluminium oxide - non fibrous form	None	Irritant, Nuisance dust, Corrosive
Silicon carbide	None	Nuisance dust
N-Aminoethylpiperazine	None	Irritant, Corrosive, Allergen
4,4'-Isopropylidenediphenol	Oral LD50 (Rat) = 4,100 mg/kg Oral LD50 (Rat) = 3,300 mg/kg Oral LD50 (Mouse) = 5,280 mg/kg Oral LD50 (Mouse) = 2,500 mg/kg Oral LD50 (Mouse) = 4,100 mg/kg	Allergen, Blood, Irritant, Kidney, Reproductive, Spleen
4-Nonylphenol, branched	None	Irritant, Corrosive
Diethylenetriamine	Oral LD50 (Rat) Approximate 1,140 mg/kg Oral LD50 (Rat) = 1,080 mg/kg Oral LD50 (Rat) = 2.33 g/kg	Allergen, Irritant, Eyes
Triethanolamine	Oral LD50 (Rat) = 8.0 g/kg Dermal LD50 (Rabbit) = > 20,000 mg/kg	Irritant, Allergen
Piperazine	Oral LD50 (Rat) = 2,050 mg/kg Oral LD50 (Rat) = 4,900 mg/kg Oral LD50 (Mouse) = 1,900 mg/kg Oral LD50 (Mouse) = 2,730 mg/kg Oral LD50 (Mouse) = 6,200 mg/kg Oral LD50 (Mouse) = 7,000 mg/kg Oral LD50 (Mouse) = 8,500 mg/kg Oral LD50 (Mouse) = 13,200 mg/kg Oral LD50 (Mouse) = 22,350 mg/kg	Allergen, Corrosive, Gastrointestinal, Irritant, Kidney, Liver, Nervous System, Respiratory
Silicon dioxide	Oral LD50 (Rat) = > 22,500 mg/kg Oral LD50 (Mouse) = > 15,000 mg/kg	Nuisance dust
1,4-Phenylenediamine-terephthaloyl chloride copolymer	None	Irritant, Lung
Benzyltrimethylamine	None	Irritant, Corrosive, Allergen, Respiratory
Quartz (SiO ₂), <1% respirable	None	Immune system, Lung, Some evidence of carcinogenicity
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	None	Irritant, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Aluminium oxide - non fibrous form	No	No	No
Silicon carbide	No	Group 2A	No
N-Aminoethylpiperazine	No	No	No
4,4'-Isopropylidenediphenol	No	No	No
4-Nonylphenol, branched	No	No	No
Diethylenetriamine	No	No	No
Triethanolamine	No	No	No
Piperazine	No	No	No
Silicon dioxide	No	No	No
1,4-Phenylenediamine-terephthaloyl chloride copolymer	Reasonably Anticipated to be a Human Carcinogen.	No	No
Benzyltrimethylamine	No	No	No
Quartz (SiO ₂), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Amines, solid, corrosive, n.o.s. (Aminoethylpiperazine, Diethylenetriamine)
Hazard class or division: 8
Identification number: UN 3259
Packing group: III

International Air Transportation (ICAO/IATA)

Proper shipping name: Amines, solid, corrosive, n.o.s. (Aminoethylpiperazine, Diethylenetriamine)
Hazard class or division: 8
Identification number: UN 3259
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (Aminoethylpiperazine, Diethylenetriamine)
Hazard class or division: 8
Identification number: UN 3259
Packing group: III

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: Alkyl phenol (CAS# 84852-15-3).

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). 4,4'-Isopropylidenediphenol (CAS# 80-05-7). 4-Nonylphenol, branched (CAS# 84852-15-3).

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Additional Regulatory Information: This product is controlled for export by the United States Department of Commerce. The Export Classification Control Number (ECCN) is 1C995.a.2.a

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,3

Prepared by: Product Safety and Regulatory Affairs

Issue date: 01/03/2018

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.