



# SAFETY DATA SHEET

## 1. Identification

<b>Product identifier</b>	<b>Chlor-Free® Universal Degreaser - 14 oz</b>
<b>Other means of identification</b>	
<b>Product Code</b>	Item# 1753974
<b>Recommended use</b>	General purpose degreaser
<b>Recommended restrictions</b>	None known.
<b>Manufacturer/Importer/Supplier/Distributor information</b>	
<b>Manufactured or sold by:</b>	
<b>Company name</b>	CRC Industries, Inc.
<b>Address</b>	885 Louis Dr. Warminster, PA 18974 US
<b>Telephone</b>	
<b>General Information</b>	215-674-4300
<b>Technical Assistance</b>	800-521-3168
<b>Customer Service</b>	800-272-4620
<b>24-Hour Emergency (CHEMTREC)</b>	800-424-9300 (US)
<b>Website</b>	crcindustries.com

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable aerosols Gases under pressure	Category 1 Compressed gas
<b>Health hazards</b>	Skin corrosion/irritation Serious eye damage/eye irritation Reproductive toxicity (fertility) Specific target organ toxicity, single exposure Specific target organ toxicity, single exposure	Category 2 Category 2A Category 2 Category 3 respiratory tract irritation Category 3 narcotic effects
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard Hazardous to the aquatic environment, long-term hazard	Category 2 Category 2
<b>OSHA defined hazards</b>	Not classified.	

### Label elements



<b>Signal word</b>	Danger
<b>Hazard statement</b>	Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging fertility.

## Precautionary statement

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist/vapors. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

### Response

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.

### Storage

Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

### Supplemental information

None.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
methyl acetate		79-20-9	45 - 55
acetone		67-64-1	20 - 30
carbon dioxide		124-38-9	5 - 10
octamethylcyclotetrasiloxane		556-67-2	5 - 10
naphtha (petroleum), hydrotreated light		64742-49-0	1 - 10
heptane, branched, cyclic and linear		426260-76-6	1 - 3
n-heptane		142-82-5	1 - 3
isopropyl alcohol		67-63-0	0.1 - 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

### Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

### Ingestion

In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

### Most important symptoms/effects, acute and delayed

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

### General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

---

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Alcohol resistant foam. Carbon dioxide (CO <sub>2</sub> ). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire-fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

---

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

---

## 7. Handling and storage

<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.
<b>Conditions for safe storage, including any incompatibilities</b>	Level 3 Aerosol.  Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm
carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3 5000 ppm
isopropyl alcohol (CAS 67-63-0)	PEL	980 mg/m3 400 ppm
methyl acetate (CAS 79-20-9)	PEL	610 mg/m3 200 ppm
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	PEL	400 mg/m3 100 ppm
n-heptane (CAS 142-82-5)	PEL	2000 mg/m3 500 ppm

#### US. ACGIH Threshold Limit Values

Components	Type	Value
acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
isopropyl alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
methyl acetate (CAS 79-20-9)	STEL	250 ppm
	TWA	200 ppm
n-heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
acetone (CAS 67-64-1)	TWA	590 mg/m3 250 ppm
carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3 30000 ppm
	TWA	9000 mg/m3 5000 ppm
isopropyl alcohol (CAS 67-63-0)	STEL	1225 mg/m3 500 ppm
	TWA	980 mg/m3 400 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
methyl acetate (CAS 79-20-9)	STEL	760 mg/m3
		250 ppm
	TWA	610 mg/m3
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	200 ppm
		400 mg/m3
n-heptane (CAS 142-82-5)		100 ppm
	Ceiling	1800 mg/m3
	TWA	440 ppm
		350 mg/m3
		85 ppm

**US. Workplace Environmental Exposure Level (WEEL) Guides**

Components	Type	Value
octamethylcyclotetrasiloxane (CAS 556-67-2)	TWA	10 ppm

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
isopropyl alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

\* - For sampling details, please see the source document.

**Appropriate engineering controls**

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection****Hand protection**

Wear protective gloves such as: Nitrile. Polyvinyl alcohol (PVA). Viton/butyl.

**Other**

Wear appropriate chemical resistant clothing.

**Respiratory protection**

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance****Physical state**

Liquid.

**Form**

Aerosol.

**Color**

Colorless.

**Odor**

Mild solvent.

**Odor threshold**

Not available.

**pH**

Not available.

<b>Melting point/freezing point</b>	-144.4 °F (-98 °C) estimated
<b>Initial boiling point and boiling range</b>	132.4 °F (55.8 °C) estimated
<b>Flash point</b>	-4.0 °F (-20.0 °C) estimated
<b>Evaporation rate</b>	Fast.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
Explosive limit - lower (%)	0.75 % estimated
Explosive limit - upper (%)	16 % estimated
<b>Vapor pressure</b>	4518.1 hPa estimated
<b>Vapor density</b>	> 2 (air = 1)
<b>Relative density</b>	0.86 estimated
<b>Solubility(ies)</b>	
Solubility (water)	Slightly soluble.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	433 °F (222.8 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Percent volatile</b>	86.3 % estimated

---

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Heat, flames and sparks. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Carbon oxides. Formaldehyde. Hydrocarbon fumes and smoke. Aldehydes.

---

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause drowsiness or dizziness. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Based on available data, the classification criteria are not met.

**Symptoms related to the physical, chemical and toxicological characteristics** May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

### Information on toxicological effects

**Acute toxicity** Not known.

Product	Species	Test Results
Chlor-Free® Universal Degreaser - 14 oz		
<b>Acute</b>		
<b>Oral</b>		
ATEmix		34275 mg/kg bw

**Skin corrosion/irritation** Causes skin irritation.

**Serious eye damage/eye irritation** Causes serious eye irritation.

## Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

### IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

### US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity** Suspected of damaging fertility.

**Specific target organ toxicity - single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.

**Specific target organ toxicity - repeated exposure** Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful.

---

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

**Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

### Bioaccumulative potential

#### Partition coefficient n-octanol / water (log Kow)

acetone	-0.24
isopropyl alcohol	0.05
methyl acetate	0.18
n-heptane	4.66
octamethylcyclotetrasiloxane	5.1

#### Bioconcentration factor (BCF)

naphtha (petroleum), hydrotreated light	10 - 2500
octamethylcyclotetrasiloxane	Result: 12400

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

---

## 13. Disposal considerations

**Disposal instructions** This material and its container must be disposed of as hazardous waste. Full or partially-full aerosol cans can be treated as universal waste. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Empty container can be recycled. Contents under pressure. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

**Hazardous waste code** Possible RCRA waste code includes:  
D001: Waste Flammable material with a flash point <140 F  
F003: Waste Non-halogenated Solvent - Spent Non-halogenated Solvent

However, it is the generator's responsibility to determine the proper classification and disposal method at the time of disposal.

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

## 14. Transport information

### DOT

**UN number** UN1950

**UN proper shipping name** Aerosols, flammable, Limited Quantity

**Transport hazard class(es)**

**Class** 2.1  
**Subsidiary risk** -  
**Label(s)** 2.1

**Packing group** Not assigned.

**Environmental hazards**

**Marine pollutant** No.

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Special provisions** N82

**Packaging exceptions** 306

**Packaging non bulk** 304

**Packaging bulk** None

**IATA**

**UN number** UN1950

**UN proper shipping name** Aerosols, flammable, Limited Quantity

**Transport hazard class(es)**

**Class** 2.1  
**Subsidiary risk** -

**Packing group** Not assigned.

**ERG Code** 10L

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Other information**

**Passenger and cargo aircraft** Allowed with restrictions.

**Cargo aircraft only** Allowed with restrictions.

**IMDG**

**UN number** UN1950

**UN proper shipping name** AEROSOLS, Limited Quantity

**Transport hazard class(es)**

**Class** 2.1  
**Subsidiary risk** -

**Packing group** Not assigned.


**Environmental hazards**

**Marine pollutant** Yes, but exempt from the regulations.


**EmS** F-D, S-U

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**DOT; IMDG**



**IATA**



## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

### CERCLA Hazardous Substance List (40 CFR 302.4)

acetone (CAS 67-64-1)

methyl acetate (CAS 79-20-9)

### CERCLA Hazardous Substances: Reportable quantity

acetone (CAS 67-64-1) 5000 LBS

methyl acetate (CAS 79-20-9) 100 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

### Toxic Substances Control Act (TSCA)

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

octamethylcyclotetrasiloxane (CAS 556-67-2) 1.0 % One-Time Export Notification only.

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act (SDWA)** Contains component(s) regulated under the Safe Drinking Water Act.

#### Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

acetone (CAS 67-64-1) 6532

#### Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

acetone (CAS 67-64-1) 35 %WV

#### DEA Exempt Chemical Mixtures Code Number

acetone (CAS 67-64-1) 6532

#### FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

acetone (CAS 67-64-1) Low priority

isopropyl alcohol (CAS 67-63-0) Low priority

methyl acetate (CAS 79-20-9) Low priority

**Food and Drug Administration (FDA)** Not regulated.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Classified hazard categories** Flammable (gases, aerosols, liquids, or solids)  
Gas under pressure  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)  
Hazard not otherwise classified (HNOC)

#### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312 Hazardous chemical** Yes

**SARA 313 (TRI reporting)**  
Not regulated.

### US state regulations

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

acetone (CAS 67-64-1)

isopropyl alcohol (CAS 67-63-0)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
n-heptane (CAS 142-82-5)  
octamethylcyclotetrasiloxane (CAS 556-67-2)

**US. New Jersey Worker and Community Right-to-Know Act**

acetone (CAS 67-64-1)  
carbon dioxide (CAS 124-38-9)  
isopropyl alcohol (CAS 67-63-0)  
methyl acetate (CAS 79-20-9)  
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
n-heptane (CAS 142-82-5)

**US. Massachusetts RTK - Substance List**

acetone (CAS 67-64-1)  
carbon dioxide (CAS 124-38-9)  
isopropyl alcohol (CAS 67-63-0)  
methyl acetate (CAS 79-20-9)  
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
n-heptane (CAS 142-82-5)

**US. Pennsylvania Worker and Community Right-to-Know Law**

acetone (CAS 67-64-1)  
carbon dioxide (CAS 124-38-9)  
isopropyl alcohol (CAS 67-63-0)  
methyl acetate (CAS 79-20-9)  
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
n-heptane (CAS 142-82-5)

**US. Rhode Island RTK**

acetone (CAS 67-64-1)  
carbon dioxide (CAS 124-38-9)  
isopropyl alcohol (CAS 67-63-0)  
methyl acetate (CAS 79-20-9)  
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
n-heptane (CAS 142-82-5)

**California Proposition 65**



**WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**California Proposition 65 - CRT: Listed date/Carcinogenic substance**

acetaldehyde (CAS 75-07-0)	Listed: April 1, 1988
benzene (CAS 71-43-2)	Listed: February 27, 1987
cumene (CAS 98-82-8)	Listed: April 6, 2010
ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004
lead (CAS 7439-92-1)	Listed: October 1, 1992
naphthalene (CAS 91-20-3)	Listed: April 19, 2002

**California Proposition 65 - CRT: Listed date/Developmental toxin**

benzene (CAS 71-43-2)	Listed: December 26, 1997
lead (CAS 7439-92-1)	Listed: February 27, 1987
methanol (CAS 67-56-1)	Listed: March 16, 2012
toluene (CAS 108-88-3)	Listed: January 1, 1991

**California Proposition 65 - CRT: Listed date/Female reproductive toxin**

lead (CAS 7439-92-1)	Listed: February 27, 1987
----------------------	---------------------------

**California Proposition 65 - CRT: Listed date/Male reproductive toxin**

benzene (CAS 71-43-2)	Listed: December 26, 1997
lead (CAS 7439-92-1)	Listed: February 27, 1987
n-hexane (CAS 110-54-3)	Listed: December 15, 2017

**Volatile organic compounds (VOC) regulations**

**EPA**

**VOC content (40 CFR 51.100(s))** 9.5 %

**Consumer products (40 CFR 59, Subpt. C)** Not regulated

**State**

<b>Consumer products</b>	This product is regulated as a General Purpose Degreaser (aerosol). This product is compliant for use in all 50 states.
<b>VOC content (CA)</b>	9.5 %
<b>VOC content (OTC)</b>	9.5 %

**International Inventories**

<b>Country(s) or region</b>	<b>Inventory name</b>	<b>On inventory (yes/no)*</b>
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

---

**16. Other information, including date of preparation or last revision**


---

<b>Issue date</b>	02-22-2023
<b>Prepared by</b>	Allison Yoon
<b>Version #</b>	01
<b>Further information</b>	CRC # 1753978
<b>Disclaimer</b>	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..