



Valvoline™
Global

SAFETY DATA SHEET
Valvoline™ SYN GARD™ 668 Automatic
Transmission Fluid

Version: 3.1

Revision Date: 09/29/2023

Print Date:
09/19/2024

SECTION 1. IDENTIFICATION

Product name : Valvoline™ SYN GARD™ 668
Automatic Transmission Fluid

Product code : 896085

Manufacturer or supplier's details

Company name of supplier : Valvoline Global Operations

Address : 100 Valvoline Way
Lexington, KY 40509
United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvolineglobal.com

Emergency telephone
number : +1-800-VALVOLINE (+1-800-825-8654)

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H361d Suspected of damaging the unborn child.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read
and understood.
P280 Wear protective gloves/ protective clothing/ eye protection/
face protection.



SAFETY DATA SHEET
Valvoline™ SYN GARD™ 668 Automatic
Transmission Fluid

Version: 3.1

Revision Date: 09/29/2023

Print Date:
09/19/2024

Response:

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Static-accumulating flammable liquid.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|--|------------|-----------------------|
| HYDROTREATED LIGHT PARAFFINIC DISTILLATE | 64742-55-8 | >= 40 - < 50 |
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC | 64742-54-7 | >= 30 - < 40 |
| HYDROTREATED LIGHT PARAFFINIC DISTILLATE | 64742-55-8 | >= 1.5 - < 5 |
| LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED | 72623-87-1 | >= 1.5 - < 5 |
| METHYL-1H-BENZOTRIAZOLE | 29385-43-1 | >= 0.1 - < 0.5 |

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.

If symptoms persist, call a physician.

In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.



SAFETY DATA SHEET
Valvoline™ SYN GARD™ 668 Automatic
Transmission Fluid

Version: 3.1

Revision Date: 09/29/2023

Print Date:
09/19/2024

| | | |
|---|---|---|
| If swallowed | : | Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital. |
| Most important symptoms and effects, both acute and delayed | : | No symptoms known or expected. |
| Notes to physician | : | Treat symptomatically. No hazards which require special first aid measures. |

SECTION 5. FIREFIGHTING MEASURES

| | | |
|---|---|---|
| Unsuitable extinguishing media | : | High volume water jet |
| Specific hazards during firefighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : | No hazardous combustion products are known |
| Further information | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for firefighters | : | Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| | | |
|---|---|---|
| Environmental precautions | : | Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for containment and cleaning up | : | Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. |

SECTION 7. HANDLING AND STORAGE

| | | |
|---|---|--|
| Advice on protection against fire and explosion | : | Normal measures for preventive fire protection. |
| Advice on safe handling | : | Do not breathe vapours/dust. For personal protection see section 8. |



SAFETY DATA SHEET
 Valvoline™ SYN GARD™ 668 Automatic
 Transmission Fluid

Version: 3.1

Revision Date: 09/29/2023

Print Date:
 09/19/2024

Smoking, eating and drinking should be prohibited in the application area.
 Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|--|------------|------------------------------------|--|----------|
| HYDROTREATED LIGHT PARAFFINIC DISTILLATE | 64742-55-8 | TWA (Mist) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Inhalable particulate matter) | 5 mg/m3 | ACGIH |
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC | 64742-54-7 | TWA (Mist) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Inhalable particulate matter) | 5 mg/m3 | ACGIH |
| HYDROTREATED LIGHT PARAFFINIC DISTILLATE | 64742-55-8 | TWA (Mist) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Inhalable particulate matter) | 5 mg/m3 | ACGIH |
| LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED | 72623-87-1 | TWA (Inhalable particulate matter) | 5 mg/m3 | ACGIH |
| | | TWA (Mist) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Mist) | 5 mg/m3 | OSHA P0 |



Valvoline™
Global

SAFETY DATA SHEET
Valvoline™ SYN GARD™ 668 Automatic
Transmission Fluid

Version: 3.1

Revision Date: 09/29/2023

Print Date:
09/19/2024

| | | | | |
|--|--|------------|----------|-----------|
| | | TWA (Mist) | 5 mg/m3 | NIOSH REL |
| | | ST (Mist) | 10 mg/m3 | NIOSH REL |

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 394 - 480 °F / 201 - 249 °C

Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Flammability (liquids) : Static-accumulating flammable liquid.

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available



Valvoline™
Global

SAFETY DATA SHEET
Valvoline™ SYN GARD™ 668 Automatic
Transmission Fluid

Version: 3.1

Revision Date: 09/29/2023

Print Date:
09/19/2024

| | | |
|--|---|--|
| Vapour pressure | : | No data available |
| Relative vapour density | : | No data available |
| Relative density | : | No data available |
| Density | : | 0.851 g/cm ³ |
| Solubility(ies) | | |
| Water solubility | : | No data available |
| Solubility in other solvents | : | No data available |
| Partition coefficient: n-octanol/water | : | No data available |
| Decomposition temperature | : | No data available |
| Viscosity | | |
| Viscosity, dynamic | : | No data available |
| Viscosity, kinematic | : | 34.3 mm ² /s (104 °F / 40 °C) |
| Oxidizing properties | : | No data available |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|------------------------------------|---|---|
| Reactivity | : | No decomposition if stored and applied as directed. |
| Chemical stability | : | No decomposition if stored and applied as directed. |
| Possibility of hazardous reactions | : | No decomposition if stored and applied as directed. |
| Conditions to avoid | : | excessive heat |
| Incompatible materials | : | alkalis Strong acids Strong oxidizing agents |
| Hazardous decomposition products | : | No hazardous decomposition products are known. |

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

| | | |
|-----------------------|---|-------------------------|
| Acute oral toxicity | : | LD50 (Rat): > 15 g/kg |
| Acute dermal toxicity | : | LD50 (Rabbit): > 5 g/kg |



Valvoline™
Global

SAFETY DATA SHEET
Valvoline™ SYN GARD™ 668 Automatic
Transmission Fluid

Version: 3.1

Revision Date: 09/29/2023

Print Date:
09/19/2024

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: No mortality observed at this dose.
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

METHYL-1H-BENZOTRIAZOLE:

- Acute oral toxicity : LD50: > 300 - < 2,000 mg/kg
Assessment: The component/mixture is moderately toxic after single ingestion.

Skin corrosion/irritation

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

- Assessment : Slight, transient irritation
Result : Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

- Assessment : Slight, transient irritation
Result : Slight, transient irritation

- Result : Repeated exposure may cause skin dryness or cracking.

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

- Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

- Result : No eye irritation



Valvoline™
Global

SAFETY DATA SHEET
Valvoline™ SYN GARD™ 668 Automatic
Transmission Fluid

Version: 3.1

Revision Date: 09/29/2023

Print Date:
09/19/2024

Assessment : No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species : Rabbit
Result : No eye irritation

METHYL-1H-BENZOTRIAZOLE:

Result : Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

METHYL-1H-BENZOTRIAZOLE:

Assessment : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation



Valvoline™
Global

SAFETY DATA SHEET
Valvoline™ SYN GARD™ 668 Automatic
Transmission Fluid

Version: 3.1

Revision Date: 09/29/2023

Print Date:
09/19/2024

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

METHYL-1H-BENZOTRIAZOLE:

Reproductive toxicity - : Some evidence of adverse effects on development, based on
Assessment animal experiments.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

No aspiration toxicity classification

Further information

Product:

Remarks : No data available



Valvoline™
Global

SAFETY DATA SHEET
Valvoline™ SYN GARD™ 668 Automatic
Transmission Fluid

Version: 3.1

Revision Date: 09/29/2023

Print Date:
09/19/2024

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test



Valvoline™
Global

SAFETY DATA SHEET
Valvoline™ SYN GARD™ 668 Automatic
Transmission Fluid

Version: 3.1

Revision Date: 09/29/2023

Print Date:
09/19/2024

| | |
|--|--|
| | Test substance: WAF Method: OECD Test Guideline 202 |
| Toxicity to algae/aquatic plants | : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201 |
| Toxicity to fish (Chronic toxicity) | : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l Exposure time: 14 d |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : NOEL (Daphnia (water flea)): 10 mg/l Exposure time: 21 d Test substance: WAF Method: OECD Test Guideline 211 |

Ecotoxicology Assessment

| | |
|--------------------------|--|
| Acute aquatic toxicity | : Not classified based on available information. |
| Chronic aquatic toxicity | : Not classified based on available information. |

METHYL-1H-BENZOTRIAZOLE:

| | |
|---|---|
| Toxicity to fish | : LC50 (Cyprinodon variegatus (sheepshead minnow)): 55 mg/l Exposure time: 96 h Test Type: semi-static test |
| Toxicity to daphnia and other aquatic invertebrates | : EC50 (Daphnia magna (Water flea)): 8.58 mg/l Exposure time: 48 h Test Type: static test Remarks: Information given is based on data on the components and the ecotoxicology of similar products. |
| Toxicity to algae/aquatic plants | : EC50 (Desmodesmus subspicatus (green algae)): 62 mg/l Exposure time: 72 h |

Ecotoxicology Assessment

| | |
|--------------------------|---|
| Acute aquatic toxicity | : Acute aquatic toxicity Category 2; Toxic to aquatic life. |
| Chronic aquatic toxicity | : Toxic to aquatic life with long lasting effects. |

Chronic aquatic toxicity Category 2; Toxic to aquatic life with long lasting effects.



SAFETY DATA SHEET
Valvoline™ SYN GARD™ 668 Automatic
Transmission Fluid

Version: 3.1

Revision Date: 09/29/2023

Print Date:
09/19/2024

Persistence and degradability

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential

Components:

METHYL-1H-BENZOTRIAZOLE:

Partition coefficient: n- : log Pow: 1.71
octanol/water

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I
Substances
Remarks: This product neither contains, nor was
manufactured with a Class I or Class II ODS as defined by the
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +
B).

Additional ecological : An environmental hazard cannot be excluded in the event of
information unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water
courses or the soil.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.



Valvoline™
Global

SAFETY DATA SHEET
Valvoline™ SYN GARD™ 668 Automatic
Transmission Fluid

Version: 3.1

Revision Date: 09/29/2023

Print Date:
09/19/2024

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|---------------|-----------|-----------------------|--------------------------------|
| XYLENE | 1330-20-7 | 100 | 100 (F003) |
| ETHYL BENZENE | 100-41-4 | 100 | 100 (F003) |
| XYLENE | 1330-20-7 | 100 | |

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Hazard not otherwise classified (physical hazards)
Reproductive toxicity

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.



SAFETY DATA SHEET
Valvoline™ SYN GARD™ 668 Automatic
Transmission Fluid

Version: 3.1

Revision Date: 09/29/2023

Print Date:
09/19/2024

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCOMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

| | | |
|---------------|-----------|----------------|
| XYLENE | 1330-20-7 | >= 0 - < 0.1 % |
| ETHYL BENZENE | 100-41-4 | >= 0 - < 0.1 % |

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

| | | |
|---------------|-----------|----------------|
| XYLENE | 1330-20-7 | >= 0 - < 0.1 % |
| ETHYL BENZENE | 100-41-4 | >= 0 - < 0.1 % |

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

| | |
|---|------------|
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC | 64742-54-7 |
|---|------------|

Pennsylvania Right To Know

| | |
|---|------------|
| HYDROTREATED LIGHT PARAFFINIC DISTILLATE | 64742-55-8 |
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC | 64742-54-7 |
| HYDROTREATED LIGHT PARAFFINIC DISTILLATE | 64742-55-8 |
| LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED | 72623-87-1 |

Maine Chemicals of High Concern

| | |
|---------------|----------|
| ETHYL BENZENE | 100-41-4 |
|---------------|----------|

Vermont Chemicals of High Concern

| | |
|---------------|----------|
| ETHYL BENZENE | 100-41-4 |
|---------------|----------|

Washington Chemicals of High Concern

| | |
|---------------|----------|
| ETHYL BENZENE | 100-41-4 |
|---------------|----------|

New York City Hazardous Substances

| | |
|---|------------|
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC | 64742-54-7 |
| DISTILLATES (PETROLEUM), HYDROTREATED LIGHT | 64742-53-6 |



SAFETY DATA SHEET
Valvoline™ SYN GARD™ 668 Automatic
Transmission Fluid

Version: 3.1

Revision Date: 09/29/2023

Print Date:
09/19/2024

| | |
|---------------|-----------|
| NAPHTHENIC | |
| XYLENE | 1330-20-7 |
| ETHYL BENZENE | 100-41-4 |

California List of Hazardous Substances

| | |
|---|------------|
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC | 64742-54-7 |
|---|------------|

California Permissible Exposure Limits for Chemical Contaminants

| | |
|---|------------|
| HYDROTREATED LIGHT PARAFFINIC DISTILLATE | 64742-55-8 |
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC | 64742-54-7 |
| HYDROTREATED LIGHT PARAFFINIC DISTILLATE | 64742-55-8 |
| LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED | 72623-87-1 |

The components of this product are reported in the following inventories:

| | |
|-------|--|
| TCSI | : On the inventory, or in compliance with the inventory |
| TSCA | : All substances listed as active on the TSCA inventory |
| AIIC | : On the inventory, or in compliance with the inventory |
| DSL | : All components of this product are on the Canadian DSL |
| ENCS | : Not in compliance with the inventory |
| KECI | : On the inventory, or in compliance with the inventory |
| PICCS | : On the inventory, or in compliance with the inventory |
| IECSC | : On the inventory, or in compliance with the inventory |
| NZIoC | : Not in compliance with the inventory |

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)



Valvoline™
Global

SAFETY DATA SHEET
Valvoline™ SYN GARD™ 668 Automatic
Transmission Fluid

Version: 3.1


Revision Date: 09/29/2023

Print Date:
09/19/2024

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

| | | |
|------------------------|---|---|
| HEALTH | * | 0 |
| FLAMMABILITY | 1 | |
| PHYSICAL HAZARD | 0 | |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- ACGIH / TWA : 8-hour, time-weighted average
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide;



Valvoline™
Global

SAFETY DATA SHEET
Valvoline™ SYN GARD™ 668 Automatic
Transmission Fluid

Version: 3.1

Revision Date: 09/29/2023

Print Date:
09/19/2024

GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 09/29/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information : 000000278348