

**SAFETY DATA SHEET**

Revision Date: 10/20/2017

Print Date: 11/2/2017

SDS Number: R0170829

PREMIUM CONVENTIONAL SAE 10W-30 Motor Oil

Version: 1.6

797578

29 CFR 1910.1200 (OSHA HazCom 2012)

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION****Product identifier**Trade name : PREMIUM CONVENTIONAL SAE 10W-30  
Motor Oil**Details of the supplier of the safety data sheet**Valvoline LLC  
100 Valvoline Way  
Lexington, KY 40509  
United States of America (USA)  
1-800-TEAMVAL (1-800-8326-825)**Emergency telephone number**

1-800-VALVOLINE (1-800-825-8654)

**Regulatory Information Number**

1-800-TEAMVAL (1-800-8326-825)

**Product Information**

1-800-TEAMVAL (1-800-8326-825)

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

**GHS label elements**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Defatter

**Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	3.36
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	3.226
Lubricating oils (petroleum),	64742-58-1	This material is	1.2513



<b>SAFETY DATA SHEET</b>	Revision Date: 10/20/2017
	Print Date: 11/2/2017
	SDS Number: R0170829
PREMIUM CONVENTIONAL SAE 10W-30 Motor Oil 797578	Version: 1.6

hydrotreated	considered hazardous under the OSHA Hazard Communication Standard criteria, based on hazard(s) not otherwise classified.
--------------	--

**SECTION 4. FIRST AID MEASURES**

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.  
  
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
acne  
stomach or intestinal upset (nausea, vomiting, diarrhea)  
irritation (nose, throat, airways)

**SAFETY DATA SHEET**

Revision Date: 10/20/2017

Print Date: 11/2/2017

SDS Number: R0170829

PREMIUM CONVENTIONAL SAE 10W-30 Motor Oil

Version: 1.6

797578

Notes to physician : No hazards which require special first aid measures.

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO<sub>2</sub>)

Dry chemical

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide  
Hydrocarbons  
nitrogen oxides (NO<sub>x</sub>)

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

**SAFETY DATA SHEET**

Revision Date: 10/20/2017

Print Date: 11/2/2017

SDS Number: R0170829

PREMIUM CONVENTIONAL SAE 10W-30 Motor Oil

Version: 1.6

797578

**SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
Lubricating oils (petroleum), hydrotreated	64742-58-1	TWA	5 mg/m3 Inhalable fraction	ACGIH

**Engineering measures** : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**SAFETY DATA SHEET**

Revision Date: 10/20/2017

Print Date: 11/2/2017

SDS Number: R0170829

PREMIUM CONVENTIONAL SAE 10W-30 Motor Oil

Version: 1.6

797578

**Personal protective equipment**

- Respiratory protection : No personal respiratory protective equipment normally required.
- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:  
Safety shoes  
Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : General industrial hygiene practice.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Physical state : liquid
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : > 390 °F / > 199 °C  
Method: Cleveland open cup
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : 0.0133333 hPa (21.11 °C)  
Calculated Vapor Pressure
- Relative vapour density : No data available
- Relative density : No data available

**SAFETY DATA SHEET**

Revision Date: 10/20/2017

Print Date: 11/2/2017

SDS Number: R0170829

PREMIUM CONVENTIONAL SAE 10W-30 Motor Oil

Version: 1.6

797578

Density : 0.868 g/cm<sup>3</sup> (15.56 °C)

## Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition :  
No data available

## Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 70 mm<sup>2</sup>/s (40 °C)

Oxidizing properties : No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide  
Hydrocarbons  
Nitrogen oxides (NO<sub>x</sub>)**SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion

**SAFETY DATA SHEET**

Revision Date: 10/20/2017

Print Date: 11/2/2017

SDS Number: R0170829

PREMIUM CONVENTIONAL SAE 10W-30 Motor Oil

Version: 1.6

797578

**Acute toxicity**

Not classified based on available information.

**Components:**

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Acute oral toxicity : LD50 (Rat): &gt; 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): &gt; 5 g/kg

Lubricating oils (petroleum), hydrotreated:

Acute oral toxicity : LD50 (Rat): &gt; 2,000 mg/kg

Assessment: Not classified as acutely toxic by ingestion under GHS.

Acute dermal toxicity : LD50 (Rat): &gt; 2,000 mg/kg

Assessment: Not classified as acutely toxic by dermal absorption under GHS.

**Skin corrosion/irritation**

Not classified based on available information.

**Components:**

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

Lubricating oils (petroleum), hydrotreated:

Result: No skin irritation

Result: Repeated exposure may cause skin dryness or cracking.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks: Unlikely to cause eye irritation or injury.

**Components:**

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation


Lubricating oils (petroleum), hydrotreated:

Result: Slight, transient irritation

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

		Page: 8
<b>SAFETY DATA SHEET</b>		Revision Date: 10/20/2017
		Print Date: 11/2/2017
		SDS Number: R0170829
PREMIUM CONVENTIONAL SAE 10W-30 Motor Oil		Version: 1.6
797578		

Germ cell mutagenicity  
Not classified based on available information.

**Carcinogenicity**  
Not classified based on available information.

**Reproductive toxicity**  
Not classified based on available information.

**STOT - single exposure**  
Not classified based on available information.

**STOT - repeated exposure**  
Not classified based on available information.

**Aspiration toxicity**  
Not classified based on available information.

**Product:**  
No aspiration toxicity classification

**Components:**  
Distillates (Petroleum), Hydrotreated Heavy Paraffinic:  
May be fatal if swallowed and enters airways.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:  
May be fatal if swallowed and enters airways.

**Further information**  
**Product:**  
Remarks: No data available

**Carcinogenicity:**  
**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

---

## SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity**  
**Product:**  
Ecotoxicology Assessment  
Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**Components:**



**SAFETY DATA SHEET**

Revision Date: 10/20/2017

Print Date: 11/2/2017

SDS Number: R0170829

PREMIUM CONVENTIONAL SAE 10W-30 Motor Oil

Version: 1.6

797578

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
Exposure time: 72 h

Toxicity to fish (Chronic : NOEC (Fish): 10 mg/l  
toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l  
aquatic invertebrates  
(Chronic toxicity)

Lubricating oils (petroleum), hydrotreated:

Toxicity to daphnia and other : LC50 (Brine shrimp (Artemia salina)): > 22,500 mg/l  
aquatic invertebrates Exposure time: 48 h

Ecotoxicology Assessment  
Chronic aquatic toxicity : No toxicity at the limit of solubility

**Persistence and degradability**

**Components:**

No data available

**Bioaccumulative potential**

**Components:**

No data available

**Mobility in soil**

**Components:**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological : No data available  
information

**Components:**

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

General advice : Dispose of in accordance with all applicable local, state and  
federal regulations.

Contaminated packaging : Empty remaining contents.



**SAFETY DATA SHEET**

Revision Date: 10/20/2017

Print Date: 11/2/2017

SDS Number: R0170829

PREMIUM CONVENTIONAL SAE 10W-30 Motor Oil

Version: 1.6

797578

**SECTION 14. TRANSPORT INFORMATION**

**International transport regulations**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

**U.S. DOT - ROAD**

Not dangerous goods

**CFR\_RAIL\_C**

Not dangerous goods

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods

**TDG\_ROAD\_C**

Not dangerous goods

**TDG\_RAIL\_C**

Not dangerous goods

**TDG\_INWT\_C**

Not dangerous goods

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods

**MX\_DG**

Not dangerous goods

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID



<b>SAFETY DATA SHEET</b>	Revision Date: 10/20/2017
	Print Date: 11/2/2017
	SDS Number: R0170829
PREMIUM CONVENTIONAL SAE 10W-30 Motor Oil 797578	Version: 1.6

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION**

**EPCRA - Emergency Planning and Community Right-to-Know Act  
CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
TOLUENE	108-88-3	1000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313** This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**California Prop 65** This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

**The components of this product are reported in the following inventories:**

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : Contact your sales representative for additional information.
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : Low volume exemption
- IECSC : q (quantity restricted)

**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

**SAFETY DATA SHEET**

Revision Date: 10/20/2017

Print Date: 11/2/2017

SDS Number: R0170829

PREMIUM CONVENTIONAL SAE 10W-30 Motor Oil


Version: 1.6

797578

**SECTION 16. OTHER INFORMATION**

**Further information**

Revision Date: 10/20/2017

<p><b>NFPA:</b></p>  <p style="text-align: center;">Special hazard.</p>	<p><b>HMIS III:</b></p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;"><b>HEALTH</b></td> <td style="text-align: center;"><b>0</b></td> </tr> <tr> <td style="background-color: red; color: white;"><b>FLAMMABILITY</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td style="background-color: yellow;"><b>PHYSICAL HAZARD</b></td> <td style="text-align: center;"><b>0</b></td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>0</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>0</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

**NFPA Flammable and Combustible Liquids Classification**

Combustible Liquid Class IIIB

**Full text of H-Statements**

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).


List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

		Page: 13
<b>SAFETY DATA SHEET</b>		Revision Date: 10/20/2017
		Print Date: 11/2/2017
		SDS Number: R0170829
PREMIUM CONVENTIONAL SAE 10W-30 Motor Oil		Version: 1.6
797578		

FG : Food grade  
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
 H-statement : Hazard Statement  
 IATA : International Air Transport Association.  
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization  
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
 IMDG : International Maritime Code for Dangerous Goods  
 ISO : International Organization for Standardization  
 logPow : octanol-water partition coefficient  
 LCxx : Lethal Concentration, for xx percent of test population  
 LDxx : Lethal Dose, for xx percent of test population.  
 ICxx : Inhibitory Concentration for xx of a substance  
 Ecxx : Effective Concentration of xx  
 N.O.S.: Not Otherwise Specified  
 OECD : Organization for Economic Co-operation and Development  
 OEL : Occupational Exposure Limit  
 P-Statement : Precautionary Statement  
 PBT : Persistent , Bioaccumulative and Toxic  
 PPE : Personal Protective Equipment  
 STEL : Short-term exposure limit  
 STOT : Specific Target Organ Toxicity  
 TLV : Threshold Limit Value  
 TWA : Time-weighted average  
 vPvB : Very Persistent and Very Bioaccumulative  
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT : Department of Transportation  
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
 HMIRC : Hazardous Materials Information Review Commission  
 HMIS : Hazardous Materials Identification System  
 NFPA : National Fire Protection Association  
 NIOSH : National Institute for Occupational Safety and Health  
 OSHA : Occupational Safety and Health Administration  
 PMRA : Health Canada Pest Management Regulatory Agency  
 RTK : Right to Know  
 WHMIS : Workplace Hazardous Materials Information System