		Page: 1
SAFETY DATA SHEET		Revision Date: 01/22/2018
		Print Date: 3/21/2018
		SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil		Version: 1.7
883595		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Motor Oil

<p>Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825)</p>	<p>Emergency telephone number 1-800-VALVOLINE (1-800-825-8654)</p> <p>Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825)</p> <p>Product Information 1-800-TEAMVAL (1-800-832-6825)</p>
---	--

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards


None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Mineral Oil		Asp. Tox. 1; H304	6.039
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	1.366

		Page: 2
SAFETY DATA SHEET		Revision Date: 01/22/2018
		Print Date: 3/21/2018
		SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil		Version: 1.7
883595		

SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
 If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.
- If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.
- In case of skin contact : Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.
- First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.
- Remove contact lenses.
 Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
- Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally,



SAFETY DATA SHEET

Revision Date: 01/22/2018

Print Date: 3/21/2018

SDS Number: R0396488

NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil

Version: 1.7

883595

persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

- acne
- stomach or intestinal upset (nausea, vomiting, diarrhea)
- irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

- Water spray
- Foam
- Carbon dioxide (CO₂)
- Dry chemical

- Dry chemical
- Carbon dioxide (CO₂)
- Water spray

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
nitrogen oxides (NO_x)

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid.

Use water spray to cool fire exposed containers and



SAFETY DATA SHEET	Revision Date: 01/22/2018
	Print Date: 3/21/2018
	SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil 883595	Version: 1.7

structures until fire is out if it can be done with minimal risk.
Avoid spreading burning material with water used for cooling purposes.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil barriers).
Do not let product enter drains.
Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Keep in suitable, closed containers for disposal.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Other information : Comply with all applicable federal, state, and local regulations.

Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

SAFETY DATA SHEET

Revision Date: 01/22/2018

Print Date: 3/21/2018

SDS Number: R0396488

NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil

Version: 1.7

883595

Conditions for safe storage : Store in a cool, dry, ventilated area.

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

The identity and concentration of one or more component(s) is being withheld under business confidentiality.

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

**SAFETY DATA SHEET**

Revision Date: 01/22/2018

Print Date: 3/21/2018

SDS Number: R0396488

NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil

Version: 1.7

883595

- Skin and body protection : Wear resistant gloves (consult your safety equipment supplier).
Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.
Wear resistant gloves (consult your safety equipment supplier).
Wear as appropriate:
Safety shoes
- Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : 626 °F / 330 °C
(1,013.333333 hPa)
Calculated Phase Transition Liquid/Gas
- Flash point : 394 - 480 °F / 201 - 249 °C
Method: Cleveland open cup
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : 1.3333333 hPa (20 °C)
Calculated Vapor Pressure
- Relative vapour density : No data available

**SAFETY DATA SHEET**

Revision Date: 01/22/2018

Print Date: 3/21/2018

SDS Number: R0396488

NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil

Version: 1.7

883595

Relative density : No data available

Density : 0.861 g/cm³

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Stable.

Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide
Hydrocarbons
Nitrogen oxides (NO_x)

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact

**SAFETY DATA SHEET**

Revision Date: 01/22/2018

Print Date: 3/21/2018

SDS Number: R0396488

NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil

Version: 1.7

883595

Ingestion
Inhalation
Skin absorption
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result: Slight, transient irritation

Remarks: Expected based on components.

Remarks: Unlikely to cause eye irritation or injury.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Mineral Oil:

May be fatal if swallowed and enters airways.

**SAFETY DATA SHEET**

Revision Date: 01/22/2018

Print Date: 3/21/2018

SDS Number: R0396488

NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil

Version: 1.7

883595

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:
May be fatal if swallowed and enters airways.

Further information**Product:**

Remarks: No data available

Carcinogenicity:**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 hToxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l
aquatic invertebrates Exposure time: 48 hToxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 hToxicity to fish (Chronic : NOEC (Fish): 10 mg/l
toxicity)Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l
aquatic invertebrates
(Chronic toxicity)**Persistence and degradability**

No data available



SAFETY DATA SHEET

Revision Date: 01/22/2018

Print Date: 3/21/2018

SDS Number: R0396488

NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil

Version: 1.7

883595

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C



SAFETY DATA SHEET

Revision Date: 01/22/2018

Print Date: 3/21/2018

SDS Number: R0396488

NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil

Version: 1.7

883595

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

**EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
TOLUENE	108-88-3	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
SULFUR DIOXIDE	7446-09-5	500	*
SULFUR DIOXIDE	7446-09-5		*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : No SARA Hazards

SARA 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SAFETY DATA SHEET

Revision Date: 01/22/2018

Print Date: 3/21/2018

SDS Number: R0396488

NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil

Version: 1.7

883595

California Prop 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SULFUR DIOXIDE 7446-09-5

The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : Not in compliance with the inventory
- ENCS : q (quantity restricted)
- KECI : On the inventory, or in compliance with the inventory
- IECSC : q (quantity restricted)
- PICCS : Not in compliance with the inventory
- TSCA : On TSCA Inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information


Revision Date: 01/22/2018

NFPA:	HMIS III:						
 <p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<table border="1"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: yellow; color: black;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	0	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	0						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

	Page: 14
SAFETY DATA SHEET	Revision Date: 01/22/2018
	Print Date: 3/21/2018
	SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil 883595	Version: 1.7

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System