

INFLEXION™ DUAL POLE HORIZONTAL CABLES

A BETTER way to power trailers with high current demands

- Used for charging trailer liftgate batteries and other high current auxiliary power applications
- Solid, overmolded plugs encapsulate the terminals and wires in order to seal out water and other contaminants
- 4 gauge, high strand count copper conductors
- Advanced ArticFlex™ cable jacket formula allows for use in extreme cold temperatures as low as -85°F (-65°C)
- Maximum current carrying capacity of 200 amps for 12V intermittent use and 100 amps for continuous 12V use
- SAE J3082 compliant
- Compatible with 670-22 and 670P-22W mating sockets

 **MADE IN THE USA**
WITH DOMESTIC & IMPORTED MATERIALS



Overmolded plugs made with a high performance, engineered polymer

Part number 2HCM52 shown



Integrated strain relief section protects the cable and terminal connections

Cable shown installed in 670P-22W socket



INFLEXION™ DUAL POLE HORIZONTAL CABLES

A BETTER way to power trailers with high current demands



Part number 2HSM15 shown

Abrasion-resistant jacket withstands exposure to diesel, gasoline, and commonly encountered road and cleaning chemicals

Recessed positive terminal enhances safety for operators and can protect the primary trailer wiring

Machine crimped, solid brass terminals with retention springs for excellent conductivity and reliability

Part No.	Stock Code	Type	Size	Leads	Cable
2HCM22	14792	Coil	12FT	12"X12"	4GA
2HCM52	14793	Coil	15FT	12"X12"	4GA
2HCM54	14794	Coil	15FT	12"X48"	4GA
2HSM12	14795	Straight Cable	12FT	-	4GA
2HSM135	14796	Straight Cable	13.5FT	-	4GA
2HSM15	14797	Straight Cable	15FT	-	4GA