



SAFETY DATA SHEET

According to OSHA HazCom 2012, 29 CFR 1910.1200

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : High Viscosity 80W90 Gear Lube
Product code : 270XX

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application : Lubricants, greases, release agents.

1.3. Details of the supplier of the safety data sheet

Supplier : Star Brite
4041 SW 47th Avenue
33314 Fort Lauderdale, Florida, United States of America
Telephone : 1-800-327-8583
E-mail : vwaclawek@kinpakinc.com
Website : http://www.starbrite.com

1.4. Emergency telephone number

EMERGENCY TELEPHONE NUMBER, for DOCTORS/FIRE BRIGADE/POLICE only:

US - Telephone : 1-703-527-3887 (During office hours only)

EMERGENCY TELEPHONE NUMBER (for DOCTORS only):

Chemtrec 1-703-527-3887 (24/7)

SECTION 2 HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification (HCS : Skin sensitization, category 1.
§1910.1200)

2.2. Label elements

Label elements (1910.1200)

Hazard pictograms :



Signal word : Warning

H- and P-phrases	:	H317	May cause an allergic skin reaction.
		P261 vapour	Avoid breathing vapours.
		P272	Contaminated work clothing should not be allowed out of the workplace.
		P280 gloves	Wear protective gloves.
		P302+P352	IF ON SKIN: Wash with plenty of water/soap.
		P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
		P321 sds	Specific treatment (see section 4 on the SDS).
		P363	Wash contaminated clothing before reuse.
		P501	Dispose of contents/container to an official chemical waste depot.



SAFETY DATA SHEET

According to OSHA HazCom 2012, 29 CFR 1910.1200

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.2. Mixtures

Product description : Mixture.

Information on hazardous substances:

Substance name	Concentration (w/w%)	CAS nr.	Additional CAS nr.	Hazards
Polysulfides	1 - < 5	Trade Secret	-----	Flam. Liq. 4; H227 Skin Sens. 1B; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410

Occupational exposure limit(s), if relevant, are listed in section 8. The actual concentration has been withheld as a trade secret.

Reference is made to chapter 16 for full text of each relevant H phrase.

SECTION 4 FIRST-AID MEASURES

4.1. Description of first aid measures

First aid measures

- Inhalation : Move victim into fresh air. Consult a doctor if victim feels unwell.
- Skin contact : Take off contaminated clothing. Wash off skin with plenty of water and soap before product dries up.
Consult a doctor if irritation occurs.
- Eye contact : Wash out with (lukewarm) water. Remove contact lenses. Consult a doctor if irritation persists.
- Ingestion : Do not induce vomiting. Give nothing to drink. Do rinse the mouth. Never give anything by mouth to an unconscious person. Consult a doctor if victim feels unwell.

4.2. Most important symptoms and effects, both acute and delayed

Effects and symptoms

- Inhalation : May cause headache, dizziness and a feeling of sickness.
- Skin contact : May cause redness and irritation, sensitisation. May produce an allergic reaction. May cause dry skin.
- Eye contact : May cause stinging of eyes and redness.
- Ingestion : May cause a feeling of sickness, vomiting and diarrhoea. May cause lung damage, sore throat and lack of breath.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians : None known.

SECTION 5 FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

- Suitable : Carbondioxide (CO2). Foam. Dry chemical. Water fog.
- Not suitable : Water jet. Use of heavy stream of water may spread fire.

5.2. Special hazards arising from the substance or mixture

Special exposure hazards : Will float on water and can be reignited.



SAFETY DATA SHEET

According to OSHA HazCom 2012, 29 CFR 1910.1200

Hazardous thermal decomposition products : Carbon monoxide may be evolved if incomplete combustion occurs.

5.3. Advice for firefighters

Special protective equipment for fire-fighters : Use adequate respiratory equipment in case of insufficient ventilation.

NFPA hazard rating :



SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions : Danger of slipping. Clean up spills immediately. Wear shoes with non-slip soles. Avoid contact with spilled or released material. Vapours are heavier than air. Build up (of gasses) in low areas involves risk of suffocation.

6.2. Environmental precautions

Environmental precautions : Avoid release of product into sewers, surface water and/or ground water. In case of large spills: contain with dike. Waste product should not be allowed to contaminate soil or water.

Other information : Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Collect spilled material in containers. Absorb residues in sand or other inert material. Dispose at an authorised waste collection point. Wash away remainder with plenty of water and soap.

6.4. Reference to other sections

Reference to other sections : See also section 8.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling : Handle in accordance with good occupational hygiene and safety practices in well-ventilated areas. Do not breathe vapour. Avoid contact with skin and eyes. Avoid splashing. Wear protective clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage : Keep frost-free, in a cool, dry and well-ventilated place. Keep away from oxidizing agents.

Recommended packaging : Keep only in the original container.

Non recommended packaging : PE and PP.

7.3. Specific end use(s)

Use : Use only as directed.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION



SAFETY DATA SHEET

According to OSHA HazCom 2012, 29 CFR 1910.1200

8.1. Control parameters

Occupational exposure limits : Occupational exposure limits have not been established for this product.

Workplace exposure limits (mg/m³):

Chemical name	Country	TWA 8 hour (mg/m ³)	STEL 15 min (mg/m ³)	Comments	Source
Distillates (petroleum), hydrotreated heavy paraffinic	US	5	-	Mist	OSHA
Distillates (petroleum), hydrotreated heavy paraffinic	US	5	-	inhalable particulate matter	ACGIH
Distillates (petroleum), hydrotreated heavy paraffinic	US	5	10	Mist	NIOSH
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	US	5	10	Mist	NIOSH
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	US	5	-	Mist	OSHA
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	US	5	-	inhalable particulate matter	ACGIH

8.2. Exposure controls

Engineering measures : Use only in well-ventilated areas. Comply with standard precautionary measures for working with chemicals.

Hygienic measures : When using do not eat, drink or smoke.

Personal protective equipment:

The efficiency of personal protective equipment depends among other things on temperature and degree of ventilation. Always get professional advice for the particular local situation.



Body protection : Wear appropriate protective clothing, overalls or suit, and similar boots. Suitable material: nitril. Indication of permeation breakthrough time: 6 hours.

Respiratory protection : Take care of sufficient ventilation. Wear suitable respiratory protection in case of large scale exposure. Suitable: gas filter type A (brown), class I or higher on e.g. a facemask.

Hand protection : Wear appropriate safety gloves. Suitable material: nitril. ± 0,5 mm. Indication of permeation breakthrough time: 6 hours.

Eye protection : Wear appropriate safety glasses with side shields when there is danger of possible eye contact.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state : Liquid.
 Colour : Green.
 Odour : Characteristic.



SAFETY DATA SHEET

According to OSHA HazCom 2012, 29 CFR 1910.1200

Odour threshold	: Not known.	
pH	: Not applicable.	Waterfree product.
Solubility in water	: Not soluble.	
Partition coefficient (n-octanol/water)	: Not known.	Not measured. Not relevant for mixtures.
Flash point	: > 100 °C	
Flammability (solid, gas)	: Not applicable.	Liquid. See flashpoint.
Auto ignition temperature	: Not known.	Does not contain substances with a known auto ignition temperature.
Boiling point/boiling range	: > 100 °C	
Freezing point	: < 0 °C	
Explosion limits (% in air)	: Not known.	Lower explosion limit in air (%): 0,9 (Distillates (petroleum), hydrotreated heavy paraffinic)
	:	Upper explosion limit in air (%): 7 (Distillates (petroleum), hydrotreated heavy paraffinic)
Oxidising properties	: Not applicable.	Does not contain oxidizing substances.
Decomposition temperature	: Not applicable.	
Viscosity (20°C)	: Not known.	
Viscosity (40°C)	: 130 mm ² /sec	
Vapour pressure (20°C)	: Not known.	
Relative vapour density	: > 1	(air = 1)
Relative density (20°C)	: 0,87 g/ml	
Evaporation rate	: Not known.	

SECTION 10 STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity : See sub-sections below.

10.2. Chemical stability

Stability : Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactivity : No other hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid : See section 7.

10.5. Incompatible materials

Materials to avoid : Keep away from oxidizing agents.

10.6. Hazardous decomposition products

Hazardous decomposition products : Not known.

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological research has been carried out on this product.



SAFETY DATA SHEET

According to OSHA HazCom 2012, 29 CFR 1910.1200

Inhalation

- Acute toxicity : Calculated LC50: > 6,222 mg/l. Ingredients of unknown toxicity: 10 %. ATE: > 5 mg/l. Low toxicity. Not classified - based on available data, the classification criteria are not met. May cause headache, dizziness and a feeling of sickness.
- Corrosion/irritation : Not classified - based on available data, the classification criteria are not met.
- Sensitisation : Does not contain substances classified as respiratory sensitiser. Not classified - based on available data, the classification criteria are not met.
- Carcinogenicity : Not expected to be carcinogenic. Not classified - based on available data, the classification criteria are not met.
- Mutagenicity : Not expected to be mutagenic. Not classified - based on available data, the classification criteria are not met.

Skin contact

- Acute toxicity : Calculated LD50: > 5000 mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw. Low toxicity. Not classified - based on available data, the classification criteria are not met.
- Corrosion/irritation : Not classified - based on available data, the classification criteria are not met.
- Sensitisation : May cause sensitisation by skin contact. May produce an allergic reaction.
- Mutagenicity : Not expected to be mutagenic. Not classified - based on available data, the classification criteria are not met.

Eye contact

- Corrosion/irritation : Slight irritation possible. Not classified - based on available data, the classification criteria are not met.

Ingestion

- Acute toxicity : Calculated LD50: > 4286 mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw. Low toxicity. Not classified - based on available data, the classification criteria are not met.
- Aspiration : Not expected to be an aspiration hazard. Contains a substance/substances with an aspiration hazard. Not classified - based on available data, the classification criteria are not met.
- Corrosion/irritation : May cause a feeling of sickness, stomachache, vomiting and diarrhoea.
- Carcinogenicity : Not expected to be carcinogenic. Not classified - based on available data, the classification criteria are not met.
- Mutagenicity : Not expected to be mutagenic. Not classified - based on available data, the classification criteria are not met.

Toxicological information:

Chemical name	Property		Method	Test animal
Polysulfides	LD50 (oral)	> 2000 mg/kg bw	OECD 401	Rat
	LD50 (dermal)	> 2000 mg/kg bw	OECD 402	Rat
	Skin sensitisation	Sensitizing.	OECD 406	Guinea pig

11.2. Information on other hazards

- Other information : No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity

No ecotoxicological research has been carried out on this product.



SAFETY DATA SHEET

According to OSHA HazCom 2012, 29 CFR 1910.1200

Ecotoxicity : Toxic to aquatic organisms. Calculated LC50 (fish): 687 mg/l. Calculated EC50 (waterflea): 6 mg/l. Contains 0 % of components with unknown hazards to the aquatic environment. May form an oil film on the water surface causing a decline in oxygen content with possible adverse effects for aquatic organisms.

12.2. Persistence and degradability

Persistence – degradability : May cause long-term adverse effects in the aquatic environment.

12.3. Bioaccumulative potential

Bioaccumulative potential : Contains bioaccumulating substances.

12.4. Mobility in soil

Mobility : Adsorbs to soil and has low mobility. Floats on water.

12.7. Other adverse effects

Other adverse effects : Not applicable.

Ecological information:

Chemical name	Property		Method	Test animal
Polysulfides	EC50 (waterflea)	0.24 mg/l	OECD 202	Daphnia magna
	IC50 (algae)	0.838 mg/l	OECD 201	Pseudokirchnerella subcapitata
	Ultimate aerobic biodegradation (%)	13 %	OECD 301 B	

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product residues : Do not dispose empty pack with waste produced by households. Containers may be recycled. Treat product residues and non-empty pack as hazardous waste.

Additional warning : None.

Waste water discharge : Do not dispose of into the environment, drains, sewers or water courses.

Local legislation : Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

SECTION 14 TRANSPORT INFORMATION

14.1. UN number or ID number

UN nr. : UN 3082

14.2. UN proper shipping name

Transport name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Polysulfides)

Transport name (IMDG, IATA) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Polysulfides)

14.3/14.4/14.5. Transport hazard class(es)/Packing group/Environmental hazards


DOT (land)



SAFETY DATA SHEET

According to OSHA HazCom 2012, 29 CFR 1910.1200

Class : 9
 Packaging group : III
 Danger label : 9 + the "environmentally hazardous substance" mark.
 ERG number : 171



Other information : Not intended for carriage by tank-vessels on inland waterways. Single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other requirements provided the packagings meet the general requirements in §§173.24 and 173.24a (49 CFR 171.4).

IMDG (sea)

Class : 9
 Packaging group : III
 EmS (fire / spill) : F - A / S - F
 Marine pollutant : Yes
 Other information : This product is not regulated as a dangerous good when transported in sizes of ≤ 5 L or ≤ 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 (IMDG code 37-14, 2.10.2.7).

IATA (air)

Class : 9
 ERG code : 9L
 Packaging group : III

14.6. Special precautions for user

Other information : Country specific variations may apply.

14.7. Maritime transport in bulk according to IMO instruments

Marpol : Not intended to be carried in bulk according to International Maritime Organisation (IMO) instruments. Packaged liquids are not considered bulk.

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations : OSHA HazCom 2012, 29 CFR 1910.1200 and other Regulations.

United States TSCA (Toxic Substances Control Act) inventory

: All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

US State Regulation

California Proposition 65

WARNING: Contains traces of the following substances known to the state of California to cause cancer, birth defects or other reproductive harm

Chemical name	CAS	Type of toxicity	NSRL or MADL (ug/d)
Cumene	98-82-8	cancer	
Ethylbenzene	100-41-4	cancer	54 (inhalation) 41 (oral)

Product name : High Viscosity 80W90 Gear Lube
 Date of issue : 2022-07-11
 : AOATT.B-CC

Replaces issue dated : ---

Page 8/10
 INFO CARE SDS



SAFETY DATA SHEET

According to OSHA HazCom 2012, 29 CFR 1910.1200

SECTION 16 OTHER INFORMATION

16.1. Other information

The information in this safety data sheet is compiled in compliance with Hazcom 1910.1200. It is the user's obligation to use this product safely and to comply with all applicable laws and regulations concerning the use of the product. This safety data sheet complements the technical information sheets but does not replace them and offers no warranty with regard to product properties.

Users are also forewarned for any hazards involved when the product is used for other purposes than those for which it is designed.

Changed or new information with regard to the previous release is indicated with an asterisk (*).

List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

ATE	: Acute Toxicity Estimate
CMR	: Carcinogenic, Mutagenic or toxic for Reproduction
DOT	: Department of Transportation
DSL	: Domestic Substances List
GHS	: Globally Harmonized System of Classification and Labelling of Chemicals
HPA	: Hazardous Products Act
HPR	: Hazardous Products Regulations
IATA	: International Air Transport Association
IBC code	: International Bulk Chemical Code
IMDG	: International Maritime Dangerous Goods Code
LD50/LC50	: Lethal Dose/Concentration for 50% of a population
MARPOL	: International Convention for the Prevention of Pollution From Ships
NO(A)EL	: No Observed (Adverse) Effect Level
OECD	: Organisation for Economic Co-operation and Development
OSHA	: United States Occupational Safety and Health Administration
PBT	: Persistent, Bioaccumulative and Toxic
REACH	: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	: Regulations concerning the International Carriage of Dangerous Goods by Rail
STP	: Sewage Treatment Plant
TWA/STEL	: Time-Weighted Average/Short Term Exposure Limit
UN	: United Nations
VOC	: Volatile Organic Compounds
vPvB	: Very Persistent and Very Bioaccumulative
WHMIS	: Workplace Hazardous Materials Information System

Key data used to compile the Safety Data Sheet are from, but not limited to, one or more sources of information e.g. toxicological data from material suppliers, CONCAWE, IFRA, CESIO, Regulation EG 1272/2008, etc. Also used: OSHA HazCom 2012, 29 CFR 1910.1200.

Full text of H-phrases mentioned in section 3:

H227	Combustible liquid.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Advice on any training appropriate for workers: none.

Number format : ", " used as decimal separator.

Date of preparation or latest revision : 2022-07-11



SAFETY DATA SHEET

According to OSHA HazCom 2012, 29 CFR 1910.1200

End of safety data sheet.

