



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name **Armor All Extreme Shield + Ceramic Tire Coating - Aerosol**

Alternative number(s) 070612194015, 067788193829, 067788001513, 070612001399

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use

#### 1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc.  
25225 Detroit Rd.  
Westlake OH 44145  
United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)  
e-mail: Autocare.regulatory@energizer.com  
Website: <http://data.energizer.com>

#### 1.4 Emergency telephone number

Emergency information service FOR EMERGENCY in USA & Canada CALL +1 800 255-3924 / For International CALL +1 813 248 0585  
This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
B.3	flammable aerosol	1	Flam. Aerosol 1	H222
B.5	gases under pressure	C	Press. Gas C	H280

For full text of abbreviations: see SECTION 16.

#### The most important adverse physicochemical, human health and environmental effects

Contains gas under pressure; may explode if heated. The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word            danger

- Pictograms

GHS02, GHS04, GHS07



- Hazard statements

H222                    Extremely flammable aerosol.  
H280                    Contains gas under pressure; may explode if heated.  
H319                    Causes serious eye irritation.

- Precautionary statements

P101                    If medical advice is needed, have product container or label at hand.  
P102                    Keep out of reach of children.  
P103                    Read label before use.  
P210                    Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P211                    Do not spray on an open flame or other ignition source.  
P251                    Pressurized container: Do not pierce or burn, even after use.  
P280                    Wear eye protection/face protection.  
P305+P351+P338    If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313            If eye irritation persists: Get medical advice/attention.  
P410+P403            Protect from sunlight. Store in a well-ventilated place.  
P410+P412            Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### 2.3 Other hazards

Hazards not otherwise classified

May be harmful if swallowed (GHS category 5: acutely toxic - oral).  
May be harmful in contact with skin (GHS category 5: acutely toxic - dermal).  
Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Contains a PBT-substance at a concentration of  $\geq 0.1\%$ . Contains a vPvB-substance at a concentration of  $\geq 0.1\%$ .

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of  $\geq 0.1\%$ .

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21




### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Not relevant (mixture)

#### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Diethylene glycol monobutyl ether	CAS No 112-34-5	50 - < 75	Eye Irrit. 2 / H319	
Decamethylcyclopentasiloxane	CAS No 541-02-6	10 - < 25	Flam. Liq. 4 / H227	
isobutane	CAS No 75-28-5	1 - < 5	Flam. Gas 1 / H220 Press. Gas C / H280	
propane	CAS No 74-98-6	1 - < 5	sA / OSHA002 Flam. Gas 1 / H220 Press. Gas C / H280	
Dodecamethylcyclohexasiloxane	CAS No 540-97-6	< 1	Flam. Liq. 4 / H227	

#### Remarks

For full text of abbreviations: see SECTION 16

Legend: Press. Gas

Press. Gas C: Gas under pressure: compressed gas

Press. Gas L: Gas under pressure: liquefied gas

Press. Gas R: Gas under pressure: refrigerated liquefied gas

Press. Gas D: Gas under pressure: dissolved gas.

### SECTION 4: First-aid measures

#### 4.1 Description of first-aid measures

##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

##### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

##### Following skin contact

Thaw frosted parts with lukewarm water. Do not rub affected area.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder

Unsuitable extinguishing media

Water jet

### 5.2 Special hazards arising from the substance or mixture

Contact with the product can cause burns and/or frostbite. Contains gas under pressure; may explode if heated.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	diethylene glycol monobutyl ether	112-34-5	TLV®	10						iv	AC-GIH® 2024
US	propane	74-98-6	REL	1,000 (10 h)	1,800 (10 h)						NIOSH REL
US	propane	74-98-6	PEL	1,000	1,800						29 CFR 1910.1000
US	propane	74-98-6	PEL (CA)	1,000	1,800					asphyx(+expl)	Cal/OSHA PEL
US	propane	74-98-6	TLV®							oxygen, asphyx, E	AC-GIH® 2024
US	isobutane	75-28-5	REL	800 (10 h)	1,900 (10 h)						NIOSH REL
US	isobutane	75-28-5	TLV®			1,000				E	AC-GIH® 2024

#### Notation

asphyx	simple asphyxiants
asphyx(+expl)	A number of gases and vapors, when present in high concentrations, act primarily as asphyxiants without other adverse effects. A concentration limit is not included for each material because the limiting factor is the available oxygen. (Several of these materials present fire or explosion hazards.)
Ceiling-C	ceiling value is a limit value above which exposure should not occur
E	explosive
iv	inhalable fraction and vapor
oxygen	Adequate oxygen delivery to the tissues is necessary for sustaining life
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

### Relevant DNELs of components

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Diethylene glycol monobutyl ether	112-34-5	DNEL	67.5 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

### Relevant DNELs of components

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Diethylene glycol monobutyl ether	112-34-5	DNEL	83 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Diethylene glycol monobutyl ether	112-34-5	DNEL	67.5 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
Diethylene glycol monobutyl ether	112-34-5	DNEL	101.2 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
Decamethylcyclopentasiloxane	541-02-6	DNEL	97.3 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
Decamethylcyclopentasiloxane	541-02-6	DNEL	24.2 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
Decamethylcyclopentasiloxane	541-02-6	DNEL	97.3 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Decamethylcyclopentasiloxane	541-02-6	DNEL	24.2 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
Dodecamethylcyclohexasiloxane	540-97-6	DNEL	11 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Dodecamethylcyclohexasiloxane	540-97-6	DNEL	1.22 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
Dodecamethylcyclohexasiloxane	540-97-6	DNEL	6.1 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects

### Relevant PNECs of components

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Diethylene glycol monobutyl ether	112-34-5	PNEC	200 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Diethylene glycol monobutyl ether	112-34-5	PNEC	1.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
Diethylene glycol monobutyl ether	112-34-5	PNEC	0.11 mg/l	aquatic organisms	marine water	short-term (single instance)
Diethylene glycol monobutyl ether	112-34-5	PNEC	4.4 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Diethylene glycol monobutyl ether	112-34-5	PNEC	0.44 mg/kg	aquatic organisms	marine sediment	short-term (single instance)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Diethylene glycol monobutyl ether	112-34-5	PNEC	0.32 mg/kg	terrestrial organisms	soil	short-term (single instance)
Decamethylcyclopentasiloxane	541-02-6	PNEC	1.2 µg/l	aquatic organisms	freshwater	short-term (single instance)
Decamethylcyclopentasiloxane	541-02-6	PNEC	0.12 µg/l	aquatic organisms	marine water	short-term (single instance)
Decamethylcyclopentasiloxane	541-02-6	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Decamethylcyclopentasiloxane	541-02-6	PNEC	11 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Decamethylcyclopentasiloxane	541-02-6	PNEC	1.1 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Decamethylcyclopentasiloxane	541-02-6	PNEC	2.54 mg/kg	terrestrial organisms	soil	short-term (single instance)
Dodecamethylcyclohexasiloxane	540-97-6	PNEC	1 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Dodecamethylcyclohexasiloxane	540-97-6	PNEC	3.77 mg/kg	terrestrial organisms	soil	short-term (single instance)
Dodecamethylcyclohexasiloxane	540-97-6	PNEC	13.5 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Dodecamethylcyclohexasiloxane	540-97-6	PNEC	1.35 mg/kg	aquatic organisms	marine sediment	short-term (single instance)

### 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear protective gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

### Respiratory protection

During spraying wear suitable respiratory equipment.

### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	aerosol (spray aerosol)
Color	not determined
Particle	not relevant (aerosol)
Odor	characteristic

#### Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	-161.5 °C at 1,013 hPa
Flash point	-88.6 °C at 1,013 hPa
Evaporation rate	Not determined
Flammability (solid, gas)	flammable aerosol in accordance with GHS criteria

#### Explosive limits

- Lower explosion limit (LEL)	5 vol%
- Upper explosion limit (UEL)	15 vol%
Vapor pressure	33.2 Pa at 25 °C
Density	not determined
Vapor density	this information is not available



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

Relative density	Information on this property is not available
Solubility(ies)	not determined
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	210 °C (auto-ignition temperature (liquids and gases))
Viscosity	not relevant (aerosol)
Explosive properties	none
Oxidizing properties	none

### 9.2 Other information

Propellant content	9 %
Temperature class (USA, acc. to NEC 500)	T3 (maximum permissible surface temperature on the equipment: 200°C)

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Gas under pressure. Risk of ignition.

If heated:

Danger of explosion, Gas under pressure, Danger of bursting container

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

### 10.5 Incompatible materials

Oxidizers



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

##### Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed or in contact with skin.

##### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

##### Serious eye damage/eye irritation

Causes serious eye irritation.

##### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

##### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

##### Carcinogenicity

Shall not be classified as carcinogenic.

##### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

##### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

##### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

##### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

### SECTION 12: Ecological information

#### 12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Diethylene glycol monobutyl ether	112-34-5	LC50	1,300 mg/l	fish	96 h
Diethylene glycol monobutyl ether	112-34-5	EC50	>100 mg/l	aquatic invertebrates	48 h
Diethylene glycol monobutyl ether	112-34-5	ErC50	>100 mg/l	algae	96 h
Diethylene glycol monobutyl ether	112-34-5	NOEC	≥100 mg/l	aquatic invertebrates	48 h
Decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	96 h
Decamethylcyclopentasiloxane	541-02-6	EC50	>2.9 µg/l	aquatic invertebrates	48 h
Decamethylcyclopentasiloxane	541-02-6	NOEC	≥16 µg/l	fish	96 h
isobutane	75-28-5	LC50	49.9 mg/l	fish	96 h
isobutane	75-28-5	EC50	19.37 mg/l	algae	96 h
propane	74-98-6	LC50	49.9 mg/l	fish	96 h
propane	74-98-6	EC50	19.37 mg/l	algae	96 h
Dodecamethylcyclohexasiloxane	540-97-6	ErC50	>2 µg/l	algae	72 h
Dodecamethylcyclohexasiloxane	540-97-6	EC50	>2 µg/l	algae	72 h
Dodecamethylcyclohexasiloxane	540-97-6	NOEC	≥2 µg/l	algae	72 h

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	14 d

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Decamethylcyclopentasiloxane	541-02-6	EC50	>15 µg/l	aquatic invertebrates	21 d
Decamethylcyclopentasiloxane	541-02-6	NOEC	16 µg/l	fish	14 d
Decamethylcyclopentasiloxane	541-02-6	LOEC	>14 µg/l	fish	90 d
Dodecamethylcyclohexasiloxane	540-97-6	EC50	>100 mg/l	microorganisms	3 h
Dodecamethylcyclohexasiloxane	540-97-6	NOEC	≥14 µg/l	fish	90 d
Dodecamethylcyclohexasiloxane	540-97-6	LOEC	>14 µg/l	fish	90 d

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Contains a PBT-substance at a concentration of ≥ 0.1%. Contains a vPvB-substance at a concentration of ≥ 0.1%.

### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of ≥ 0.1%.

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## SECTION 14: Transport information

### 14.1 UN number

DOT	UN 1950
IMDG-Code	UN 1950
ICAO-TI	UN 1950

### 14.2 UN proper shipping name

DOT	Aerosols
IMDG-Code	AEROSOLS
ICAO-TI	Aerosols, flammable

### 14.3 Transport hazard class(es)

DOT	2.1
IMDG-Code	2.1
ICAO-TI	2.1

### 14.4 Packing group

not assigned

### 14.5 Environmental hazards

Environmentally hazardous substance (aquatic environment)	Decamethylcyclopentasiloxane
---	------------------------------

### 14.6 Special precautions for user

There is no additional information.

### 14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

### Information for each of the UN Model Regulations

DOT

### Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN1950, Aerosols, 2.1, environmentally hazardous
Reportable quantity (RQ)	55,000 lbs (25,000 kg) (methanol)
Danger label(s)	2.1

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21



Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	N82
ERG No	126

### International Maritime Dangerous Goods Code (IMDG) - Additional information

Particulars in the shipper's declaration	UN1950, AEROSOLS, (Decamethylcyclopentasiloxane), 2.1, -88.6°C c.c., MARINE POLLUTANT
Marine pollutant	yes (hazardous to the aquatic environment)
Danger label(s)	2.1



Special provisions (SP)	63, 190, 277, 327, 344, 381, 959
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
EmS	F-D, S-U
Stowage category	-

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Particulars in the shipper's declaration	UN1950, Aerosols, flammable, 2.1
Environmental hazards	yes (hazardous to the aquatic environment)
Danger label(s)	2.1



Special provisions (SP)	A145, A167
Excepted quantities (EQ)	E0
Limited quantities (LQ)	30 kg

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

#### National regulations (United States)

**Toxic Substance Control Act (TSCA)** not all ingredients are listed (ACTIVE)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

### Superfund Amendment and Reauthorization Act (SARA TITLE III )

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

### Clean Air Act

Name of substance	CAS No	Type of registration	Basis for listing	Threshold quantity (lbs)
isobutane	75-28-5	Flammable substance	f	10000
propane	74-98-6	Flammable substance	f	10000

#### Legend

f Flammable gas.

### Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Diethylene glycol monobutyl ether		solvents	CA TACs
Decamethylcyclopentasiloxane	541-02-6	emulsifier	Canada PBiTs CECBP - Priority Chemicals EC PBTs
Amino Functionalized Silicone	Trade secret	water repellent	
isobutane	75-28-5	propellant	EC Annex VI CMRs - Cat. 1A EC Annex VI CMRs - Cat. 1B
Trimethylsilyl silicate	104133-09-7	defoamer	
propane	68476-86-8		EC Annex VI CMRs - Cat. 1A EC Annex VI CMRs - Cat. 1B
Alkyl functionalized silane	Trade secret	water repellent	
Dodecamethylcyclohexasiloxane	540-97-6	emulsifier	Canada PBiTs CECBP - Priority Chemicals EC PBTs
Octamethylcyclotetrasiloxane	556-67-2	emulsifier	Canada PBiTs CECBP - Priority Chemicals EC PBTs
methanol	67-56-1	impurity	CA TACs IRIS Neurotoxicants NTP OHAT - Repr. or Dev. Toxicants OEHHH RELs Prop 65



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

### - Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
Diethylene glycol monobutyl ether		1022			1.0 %

### - Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
isobutane		N	
propane	74-98-6	A, O	
propane		N	
propane		A	gases

#### Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- gases Refers to displacement of air asphyxiation hazard.
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

### - Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Diethylene glycol monobutyl ether			
isobutane	75-28-5		F4
propane	74-98-6		F4

#### Legend

- F4 Flammable - Fourth Degree

### - Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
GLYCOL ETHERS		E
PROPANE, 2-METHYL-	75-28-5	
PROPANE	74-98-6	

#### Legend

- E Environmental hazard



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

### - Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
isobutane	106-97-8	T, F
propane	74-98-6	T
propane	74-98-6	T, F

#### Legend

F Flammability (NFPA®)  
T Toxicity (ACGIH®)

### California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

#### Proposition 65 List of chemicals

Name acc. to inventory	CAS No	Remarks	Type of the toxicity
methanol	67-56-1		developmental

### Drug precursors, Chemicals designated within the Controlled Substances Act, 21 U.S.C. § 802, paragraphs 34 (list I) and 35 (list II)

none of the ingredients are listed

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	2	temporary or minor injury may occur
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

#### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

Category	Degree of hazard	Description
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

### National inventories

Country	Inventory	Status
AU	AIIC	not all ingredients are listed
CA	DSL	not all ingredients are listed
CA	NDSL	substance is listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed or exempt from listing
VN	NCI	not all ingredients are listed

#### Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

### Legend

NCI	National Chemical Inventory
NDSL	Non-domestic Substances List (NDSL)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information, including date of preparation or last revision

#### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.3	Results of PBT and vPvB assessment: Contains a PBT-substance in a concentration of $\geq 0.1\%$ . Contains a vPvB-substance in a concentration of $\geq 0.1\%$ .	Results of PBT and vPvB assessment: Contains a PBT-substance at a concentration of $\geq 0.1\%$ . Contains a vPvB-substance at a concentration of $\geq 0.1\%$ .	yes
2.3	Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$ .	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$ .	yes
3.2		Description of the mixture: change in the listing (table)	yes
3.2		Remarks: For full text of abbreviations: see SECTION 16	yes
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
12.3	Bioaccumulative potential: The substance fulfills the very bioaccumulative criterion.	Bioaccumulative potential: Data are not available.	yes
12.5	Results of PBT and vPvB assessment: Contains a PBT-substance in a concentration of $\geq 0.1\%$ . Contains a vPvB-substance in a concentration of $\geq 0.1\%$ .	Results of PBT and vPvB assessment: Contains a PBT-substance at a concentration of $\geq 0.1\%$ . Contains a vPvB-substance at a concentration of $\geq 0.1\%$ .	yes
12.6	Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$ .	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$ .	yes
14.7	Danger label(s): 2.1, fish and tree	Danger label(s): 2.1	yes
14.7	Danger label(s): 2.1, fish and tree	Danger label(s): 2.1	yes



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Armor All Extreme Shield + Ceramic Tire Coating - Aerosol

Version number: 7.0  
Replaces version of: 2023-08-24 (6)

Revision: 2024-05-21

---

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.