



20132 Radiator Stop Leak

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Issue date: 6/24/2022 Revision date: 1/11/2023 Supersedes: 6/24/2022 Version: 3.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : 20132 Radiator Stop Leak
Product code :

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Automotive Care Products.
Restrictions on use : None known

1.3. Supplier

Liqui Moly GmbH
Jerg-Wieland-Strasse 4 Ulm D-89081 Germany
T +49 731 1420 0
info@liqui-moly.de - www.liqui-moly.us

1.4. Emergency telephone number

Emergency number : INFOTRAC
+1800 535 5053 (USA, Canada); +1352 323 3500 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Not classified

2.2. GHS Label elements, including precautionary statements

GHS US labeling

No labeling applicable

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None known.

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Glycerin	CAS-No.: 56-81-5	10 – 30

Full text of hazard classes and H-statements : see section 16

20132 Radiator Stop Leak

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with mild soap and water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Get medical attention if irritation develops and persists.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: No adverse effects expected.
Inhalation	: Adverse effects not expected from this product.
Skin	: Adverse effects not expected from this product.
Eyes	: May cause minor eye irritation.
Ingestion	: Irritation to the digestive tract.
Chronic symptoms	: None known.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: Use of heavy stream of water may spread fire.

5.2. Specific hazards arising from the chemical

Fire hazard	: This product is not classified as flammable or combustible.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO ₂).

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Cool down the containers exposed to heat with a water spray.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Avoid contact with eyes, skin and clothing.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Absorb and/or contain spill with inert material, then place in suitable container.

20132 Radiator Stop Leak

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with eyes. Avoid repeated or prolonged skin contact.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store at room temperature. Store in a dry area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

20132 Radiator Stop Leak

No additional information available

Glycerin (56-81-5)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA	10 mg/m ³
---------------	----------------------

USA - OSHA - Occupational Exposure Limits

Local name	Glycerin (mist)
OSHA PEL (TWA)	15 mg/m ³ (Total dust) 5 mg/m ³ (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

In case of repeated or prolonged contact wear gloves. Consult supplier for specific recommendations.

Eye protection:

Not required for normal conditions of use

Skin and body protection:

Wear suitable protective clothing

20132 Radiator Stop Leak

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Respiratory protection:

In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Cloudy. Liquid.
Color	: White
Odor	: Characteristic
Odor threshold	: No data available
pH	: 7.6
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 100 °C 212F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.05
Solubility	: Partially soluble. in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: > 100 mm ² /s @40C
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: None.
Oxidizing properties	: None.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong oxidizers.

20132 Radiator Stop Leak

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Glycerin (56-81-5)	
LD50 oral rat	27200 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Female, Experimental value, Oral)
LD50 oral	25000 mg/kg body weight
LD50 dermal	56750 mg/kg (4 day(s), Guinea pig, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 2.75 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male, Converted value, Inhalation (vapours))
LC50 Inhalation - Rat (Dust/Mist)	50100 mg/l
LC50 Inhalation - Rat (Vapours)	> 2.75 mg/l Source: ECHA
ATE US (oral)	25000 mg/kg body weight
ATE US (dermal)	56750 mg/kg body weight
ATE US (dust, mist)	50100 mg/l/4h

Skin corrosion/irritation : Not classified
pH: 7.6
Serious eye damage/irritation : Not classified
pH: 7.6
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : > 100 mm²/s @40C

Glycerin (56-81-5)	
Viscosity, kinematic	1119.746 mm ² /s

Symptoms/effects : No adverse effects expected.
Inhalation : Adverse effects not expected from this product.
Skin : Adverse effects not expected from this product.
Eyes : May cause minor eye irritation.
Ingestion : Irritation to the digestive tract.
Chronic symptoms : None known.

20132 Radiator Stop Leak

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Glycerin (56-81-5)	
LC50 - Fish [1]	54000 mg/l (96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 10000 mg/l (24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
EC50 - Other aquatic organisms [1]	> 10000 mg/l waterflea
EC50 - Other aquatic organisms [2]	> 10000 mg/l

12.2. Persistence and degradability

Glycerin (56-81-5)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.87 g O ₂ /g substance
Chemical oxygen demand (COD)	1.16 g O ₂ /g substance
ThOD	1.217 g O ₂ /g substance
BOD (% of ThOD)	0.71

12.3. Bioaccumulative potential

Glycerin (56-81-5)	
Partition coefficient n-octanol/water (Log Pow)	-1.75 (Experimental value, Equivalent or similar to OECD 107, 25 °C)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

Glycerin (56-81-5)	
Surface tension	0.0634 N/m (20 °C, 1000 g/l)
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

20132 Radiator Stop Leak

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available			

14.6. Special precautions for user

DOT

No data available

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

20132 Radiator Stop Leak

SARA Section 311/312 Hazard Classes	Refer to Section 2 for OSHA Hazard Classification.
-------------------------------------	--

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. International regulations

CANADA

Glycerin (56-81-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

20132 Radiator Stop Leak

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

National regulations

20132 Radiator Stop Leak

Listed on the Canadian DSL (Domestic Substances List)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Glycerin(56-81-5)	U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)


Revision date : 1/11/2023

Data sources : This safety data sheet was compiled with data and information from the following sources : RTECS, ECOSAR, HSDB, SIDS SIAP, CESAR, Chemical DB.

NFPA health hazard : 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Safety Data Sheet (SDS), USA/CA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.