

# SAFETY DATA SHEET

## 1. Identification

**Product number** 1000000000  
**Product identifier** GLASS CLEANER  
**Revision date** 07-30-2017  
**Company information**  
Hopkins Manufacturing Corp.  
1225 East Artesia Blvd, Carson CA  
92354, United States of America  
**Company phone**  
**Emergency telephone US** General Assistance 1-310-761-8510  
**Emergency telephone outside US Version #** 1-562-616-7617  
**Supersedes date** 02  
**Recommended use** 07-30-2017  
**Recommended restrictions** cleaner  
None known.

## 2. Hazard(s) identification

**Physical hazards** Gases under pressure Liquefied gas  
**Health hazards** Not classified.  
**Environmental hazards** Not classified.  
**OSHA defined hazards** Not classified.

### Label elements



**Signal word Hazard** Warning  
**statement Precautionary statement** Contains gas under pressure; may explode if heated.  
**Prevention** Observe good industrial hygiene practices.  
**Response** Wash hands after handling.  
**Storage** Protect from sunlight. Store in a well-ventilated place.  
**Disposal** Dispose of waste and residues in accordance with local authority requirements.  
**Hazard(s) not otherwise classified (HNOC)** None known.  
**Supplemental information** None.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-Butoxyethanol		111-76-2	2.5 - 10
Ethyl Alcohol		64-17-5	2.5 - 10
Butane		106-97-8	1 - 2.5
Propane		74-98-6	1 - 2.5
Other components below reportable levels			90 - 100

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

<b>Inhalation</b>	Move to fresh air. Get medical attention if symptoms persist.
<b>Skin contact</b>	Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth.
<b>Most important symptoms/effects, acute and delayed</b>	Direct contact with eyes may cause temporary irritation.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire-fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. See Section 8 of the SDS for Personal Protective Equipment. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.

#### 7. Handling and storage

<b>Precautions for safe handling</b>	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
--------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Conditions for safe storage, including any incompatibilities**

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep containers tightly closed in a dry, cool and well-ventilated place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

**8. Exposure controls/personal protection**

**Occupational exposure limits**

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3 50 ppm
Ethyl Alcohol (CAS 64-17-5)	PEL	1900 mg/m3 1000 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3 5 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Ethyl Alcohol (CAS 64-17-5)	TWA	1900 mg/m3 1000 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm

**Biological limit values**

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines**

**US - California OELs: Skin designation**

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

2-Butoxyethanol (CAS 111-76-2) Skin designation applies.

**US - Tennessee OELs: Skin designation**

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

**US NIOSH Pocket Guide to Chemical Hazards: Skin designation**

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

<b>Eye/face protection</b>	If contact is likely, safety glasses with side shields are recommended.
<b>Hand protection</b>	For prolonged or repeated skin contact use suitable protective gloves.
<b>Skin protection</b>	
<b>Other</b>	Wear suitable protective clothing.
<b>Respiratory protection</b>	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations** When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties**

<b>Appearance</b>	Clear.
<b>Physical state</b>	Gas.
<b>Form</b>	Aerosol. Liquefied gas.
<b>Color</b>	Light yellow.
<b>Odor</b>	Characteristic.
<b>Odor threshold</b>	Not available.
<b>pH</b>	9.1 - 10.1 estimated
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	212 °F (100 °C) estimated
<b>Flash point</b>	-156.0 °F (-104.4 °C) Propellant estimated
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	80 - 100 psig @70F estimated
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Aerosol spray enclosed space</b>	
<b>Deflagration density</b>	> 2.52 g/cm <sup>3</sup> Tested
<b>Aerosol spray ignition distance</b>	< 15 cm Tested estimated
<b>Specific gravity</b>	0.977 - 0.997

## 10. Stability and reactivity

<b>Reactivity Chemical</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>stability Possibility of hazardous reactions</b>	Material is stable under normal conditions. No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Ingestion</b>	Expected to be a low ingestion hazard.
<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	No adverse effects due to skin contact are expected.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Symptoms related to the physical, chemical and toxicological characteristics** Direct contact with eyes may cause temporary irritation.

### Information on toxicological effects

**Acute toxicity** May be harmful if swallowed. May be harmful in contact with skin. May be harmful if inhaled. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
2-Butoxyethanol (CAS 111-76-2)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Guinea pig	230 ml/kg, 24 Hours 7.3 ml/kg, 4 Days
	Rabbit	450 ml/kg, 24 Hours 435 mg/kg, 24 Hours 0.63 ml/kg
	Rat	> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rabbit	400 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
<i>Oral</i>		
LD100	Rabbit Dog	695 mg/kg
LD50	Guinea pig	> 695 mg/kg
	Rat	1200 mg/kg 530 - 2800 mg/kg
Butane (CAS 106-97-8)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l

Components	Species	Test Results
Ethyl Alcohol (CAS 64-17-5)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Cat	85.41 mg/l, 4.5 Hours 43.68 mg/l, 6 Hours
	Mouse	> 60000 ppm 79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours 51.3 mg/l, 6 Hours
<i>Oral</i>		
LD50	Monkey	6000 mg/kg
	Mouse	10500 ml/kg
	Rat	1187 - 2769 mg/kg 7800 ml/kg
Propane (CAS 74-98-6)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l 658 mg/l/4h

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	May be irritating to the skin. Prolonged skin contact may cause temporary irritation.
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation. May be irritating to eyes.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
2-Butoxyethanol (CAS 111-76-2)	3 Not classifiable as to carcinogenicity to humans.
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>	
Not listed.	
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	Not an aspiration hazard. Not likely, due to the form of the product.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. May be harmful if absorbed through skin.  2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

## 12. Ecological information

**Ecotoxicity** Harmful to aquatic life.

Product	Species		Test Results
GLASS CLEANER (CAS Mixture)			
<b>Aquatic</b>			
Crustacea	EC50	Daphnia	13838.1602 mg/l, 48 hours estimated
Components	Species		Test Results
2-Butoxyethanol (CAS 111-76-2)			
<b>Aquatic</b>			
Fish	LC50	Inland silverside ( <i>Menidia beryllina</i> )	1250 mg/l, 96 hours
Ethyl Alcohol (CAS 64-17-5)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	7700 - 11200 mg/l, 48 hours
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	> 100.1 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Partition coefficient n-octanol / water (log Kow)**

2-Butoxyethanol	0.83
Butane	2.89
Ethyl Alcohol	-0.31
Propane	2.36

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal instructions** Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

### 14. Transport information

#### DOT

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.2
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.2
<b>Packing group</b>	Not applicable.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Packaging exceptions</b>	306
<b>Packaging non bulk</b>	None
<b>Packaging bulk</b>	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

#### IATA

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, non-flammable

**Transport hazard class(es)**

**Class** 2.2  
**Subsidiary risk** -  
**Label(s) Packing group** 2.2  
**Environmental hazards** Not applicable.  
**ERG Code** No.  
2L

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Other information**

**Passenger and cargo aircraft** Allowed.  
**Cargo aircraft only** Allowed.  
**Packaging Exceptions** LTD QTY

**IMDG**

**UN number** UN1950  
**UN proper shipping name** AEROSOLS  
**Transport hazard class(es)**

**Class** 2.2  
**Subsidiary risk** -  
**Label(s) Packing group** 2.2  
**Environmental hazards** Not applicable.  
**Marine pollutant** No.

**EmS** Not available.

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Packaging Exceptions** LTD QTY

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

**DOT**



**IATA; IMDG**



**15. Regulatory information**

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
All components are on the U.S. EPA TSCA Inventory List.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.



Country(s) or region	Inventory name	On inventory (yes/no)*
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

**Issue date** 07-30-2017

**Revision date** 07-30-2017

**Version #** 02

**References**  
 EPA: AQUIRE database  
 NLM: Hazardous Substances Data Base  
 US. IARC Monographs on Occupational Exposures to Chemical Agents

**Disclaimer**  
 The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Revision Information**  
 Product and Company Identification: Alternate Trade Names