



Product Data

Castrol GTX High Mileage 5W-20

HELPS EXTEND ENGINE LIFE FOR YOUR HIGH MILEAGE VEHICLES

Description

Castrol GTX High Mileage is the premium part synthetic motor oil specially formulated for vehicles with over 75,000 miles. As vehicles age, they change and some of these changes can result in costly repairs or replacement. Catalytic converter failure is one of the most common – and costliest problems faced by higher mileage vehicles.

All motor oil contains phosphorus to prevent engine wear. Phosphorus is an industry recognized catalyst poison. Castrol GTX High Mileage is specially formulated with less phosphorus than other leading oils, replacing it with advanced technology invented and patented by Castrol that helps prevent catalytic converter and emission system failure and delivers unsurpassed protection against sludge, wear and oil burn-off*

Provides superior protection in gasoline direct injection engines (including but not limited to GDI, FSI, SIDI, EcoBoost - check your owner's manual for details).

Application

Castrol GTX High Mileage is designed for all car types.

Advantages

The Castrol GTX High Mileage range:

- Helps prevent catalytic converter and emission system failure
- Provides superior dispersancy that fights sludge build-up
- Delivers exceptional oil burn-off protection exceeding industry standards**
- Has seal conditioners to help reduce leaks
- Advanced additives to minimize engine wear

For more, visit castrol.com

*vs leading conventional oils, 5W-30 tested

** Based on API and ACEA volatility specifications

Typical Characteristics

Name	Method	Units	Castrol GTX High Mileage 5W-20
Density @ 15C, Relative	ASTM D4052	g/ml	0.855
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	8.3
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	5250
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	49
Viscosity Index	ASTM D2270	None	145
Pour Point	ASTM D97	°C	-42
Flash Point, PMCC	ASTM D93	°C	205
Ash, Sulphated	ASTM D874	% wt	0.83

Product Performance Claims

API SQ

ILSAC GF-7

Meets Ford WSS-M2C960-A1

Meets engine test performance of Chrysler MS-6395

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol GTX High Mileage 5W-20

29 Jan 2026

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

www.castrol.com/us Email: contactus@bp.com