



Product Data

Castrol GTX Ultraclean 5W-30

HELPS EXTEND ENGINE LIFE

Description

Castrol GTX's 3X Protect formula has been developed to fight the three main causes of engine sludge: heat, contaminants and short trips. By cleaning away existing sludge and creating a barrier that helps stop deposits from forming, Castrol GTX keeps engines cleaner for longer. This means drivers and their vehicles enjoy more years together.

Help extend the life of your engine with GTX Ultraclean.

Application

Exceeds manufacturer's warranty requirements for applications requiring API SQ, ILSAC GF-7 and previous categories.

Castrol GTX Ultraclean 5W-30 Meets - Ford WSS-M2C946-A / WSS-M2C946-B1 specifications.

Advantages

Castrol GTX Ultraclean also delivers:

- superior sludge protection compared to tough industry standards*
- Advanced protection against viscosity and thermal breakdown
- Superior protection against high temperature deposits
- Premium quality base oils and anti-wear additives that help extend the life of your engine

* 1.4X cleaner than the industry standard as measured in the API SQ Seq. VH Sludge test

** When tested in engines with high level of sludge

Typical Characteristics

Name	Method	Units	Castrol GTX Ultraclean 5W-30
Density @ 15C, Relative	ASTM D4052	g/ml	0.857
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	10.2
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	5845
Pour Point	ASTM D97	°C	-38
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	61
Viscosity Index	ASTM D2270	None	148
Flash Point, PMCC	ASTM D93	°C	200
Ash, Sulphated	ASTM D874	% wt	0.78

Product Performance Claims

API SQ

ILSAC GF-7

Meets Ford WSS-M2C946-B1/ WSS-M2C961-A1

Meets engine test performance of Chrysler MS-6395

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol GTX Ultraclean 5W-30

13 Feb 2026

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

www.castrol.com/us Email: contactus@bp.com