

Valvoline Premium Carb & Throttle Body Cleaner PN# 681045

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name	Mixture
CAS No.	Mixture
Trade Name	Valvoline Premium Carb & Throttle Body Cleaner
Product Code	N/A

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Brake cleaner
Uses Advised Against	None

Company Identification	Spray Products Corporation P.O. Box 737 Norristown, PA 19404
------------------------	--

Telephone	(610) 277-1010
Fax	(610) 277-4390
E-Mail (competent person)	sds@sprayproducts.com

Emergency telephone number

Emergency Phone No.	Transportation Emergency: CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)
---------------------	---

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Flam. Aerosol 1; Compressed dissolved gas; Acute Tox. 4; STOT SE 1
Repr. 2; STOT RE 2; Skin Irrit. 2; Eye Irrit. 2; Asp. Tox. 1

Label elements

Hazard Symbol



DANGER

Signal word(s)

Hazard Statement(s)

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Harmful if swallowed. Harmful if inhaled. Harmful in contact with skin.
Causes damage to organs: Optic nerve, Central nervous system. May cause drowsiness or dizziness.
Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated exposure:
Inhalation - neuropsychological effects, auditory dysfunction and effects on colour vision.
Causes skin irritation. Causes serious eye irritation.
Repeated exposure may cause skin dryness or cracking.
May be harmful if swallowed and enters airways.

Valvoline Premium Carb & Throttle Body Cleaner

PN# 681045

Precautionary Statement(s)

Do not handle until all safety precautions have been read and understood.
 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
 Do not spray on an open flame or other ignition source.
 Do not breathe mist/vapours/spray.
 Wash hands and exposed skin after use.
 Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.
 Keep out of reach of children.

Other hazards

None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
Acetone	80-90	67-64-1	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336
Methanol	1-3	67-56-1	Flam. Liq. 2; H225 Acute Tox. 3; H301, H311, H331 STOT SE 1; H370 (Optic nerve, Central nervous system)
Toluene	4-6	108-88-3	Flam. Liq. 2; H225 Repr. 2; H361 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Asp. Tox. 1; H304 STOT SE 3; H336 STOT RE 2; H373: Inhalation - neuropsychological effects, auditory dysfunction and effects on colour vision. Aquatic Chronic 4; H412
Carbon dioxide	5 - 10	124-38-9	Compressed dissolved gas

Additional Information - None

* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation

Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.

Skin Contact

Wash affected skin with soap and water. If symptoms develop, obtain medical attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If symptoms occur obtain medical attention.

Ingestion

Do not give anything by mouth to an unconscious person. Seek medical treatment.

Most important symptoms and effects, both acute and delayed

May cause damage to organs: (Optic nerve, Central nervous system).
 May be harmful if swallowed and enters airways.

Valvoline Premium Carb & Throttle Body Cleaner

PN# 681045

Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

- Suitable Extinguishing Media
- Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray. Do not use water jet.

Special hazards arising from the substance or mixture

Highly flammable vapor (flash point below 23°C).

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Avoid breathing vapors.

Environmental precautions

Prevent liquid entering sewers, basements and work pits.

Methods and material for containment and cleaning up

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

Reference to other sections

None

Additional Information

None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only.

Conditions for safe storage, including any incompatibilities

-Storage temperature

Keep in a cool, well ventilated place. Store at temperatures not exceeding 50 °C / 122 °F.

-Incompatible materials

This product should be stored away from sources of strong heat or oxidizing chemicals.

Specific end use(s)

Brake cleaner

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Valvoline Premium Carb & Throttle Body Cleaner

PN# 681045

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Acetone	67-64-1	1000	500	-----	750	^NIC
Methanol	67-56-1	200 ppm	200 ppm	----	250 ppm	None
Toluene	108-88-3	200	20	300*	-----	*10-min. Ceiling
Carbon dioxide	124-38-9		5000 ppm		30,000 ppm	

^NIC = Notice of Intended Changes (ACGIH®);

Recommended monitoring method

NIOSH 1300 (Ketones I); NIOSH 2000 (Methanol); NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C) ; NIOSH 1501 (Hydrocarbons, Aromatic)

Exposure controls

Appropriate engineering controls

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

Personal protection equipment

Eye/face protection

Wear protective eyewear (goggles, face shield, or safety glasses).



Skin protection (Hand protection/ Other)

Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber)



Respiratory protection

Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment.



Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

Environmental Exposure Controls

None known

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Liquid
Color	Colorless
Odor	Acetone-like
Odor Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	56 (Acetone)
Flash Point (°C)	-17 (Acetone)
Evaporation Rate	Not available
Flammability (solid, gas)	Not applicable
Explosive Limit Ranges	2.5% - 12.8% v/v (Acetone)
Vapor pressure (Pascal)	2.4 x 10 ⁴ (Acetone)
Vapor Density (Air=1)	Not available
Density (g/ml)	Not available
Solubility (Water)	Not available
Solubility (Other)	Not available

Valvoline Premium Carb & Throttle Body Cleaner

PN# 681045

Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	465 (Acetone)
Decomposition Temperature (°C)	Not available
Kinematic Viscosity	<20
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Other information	Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions.
Chemical stability	Stable.
Possibility of hazardous reactions	None anticipated.
Conditions to avoid	Avoid contact with heat and ignition sources.
Incompatible materials	Strong oxidizing agents
Hazardous decomposition product(s)	Carbon monoxide, Carbon dioxide, Acrid smoke

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact
Information on toxicological effects

Methanol (CAS# 67-56-1)

Acute toxicity *	LD50 (oral, monkey): 7000 mg/kg-bw LD0 (oral, rat): ≥ 2528 mg/kg-bw LC50 (inhal., cat, 6-hours): 43.68 mg/L LC50 (inhal., monkey, 4-hours): 52 mg/L Ingestion may damage the optic nerve. May cause dizziness and drowsiness.
Irritation	May cause eye irritation.
Sensitisation	It is not a skin sensitiser.
Repeated dose toxicity	NOAEC (2-yr. inhal., mouse): ≥ 1.3 mg/L
Developmental Toxicity	Negative. Not a specific developmental toxin.
Toxicity for reproduction	Negative. Not a specific reproductive toxin.
Mutagenicity	Negative

Carcinogenicity

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Other information	* ATE (oral) = 100 mg/kg * ATE (dermal) = 300 mg/kg * ATE (inhalation) = 3 mg/L
--------------------------	---

*ATE = Acute Toxicity Estimate for purposes of classification

Acetone (CAS No. 67-64-1)

Acute toxicity	Oral LD50 = 5800 mg/kg (rat) Dermal LD50 >15800 mg/kg (rabbit) Inhalation LC50 76 mg/L (4 hour(s)) (rat) - Vapours may cause drowsiness and dizziness.
Irritation / Corrosivity	Causes serious eye irritation. Repeated exposure may cause skin dryness or cracking.
Sensitisation	It is not a skin sensitiser.

Valvoline Premium Carb & Throttle Body Cleaner

PN# 681045

Repeated dose toxicity

Oral NOAEL = 900 mg/kg/day (rat) (90-days)
Inhalation NOAEL ≥ 19,000 ppm (rat)

Carcinogenicity

It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity

Negative

Toxicity for reproduction

Negative

Other information

None known.

Toluene (CAS No. 108-88-3)

Acute toxicity

Oral LD50 = 5580 mg/kg (rat)
Dermal LD50 >5000 mg/kg (rabbit)
Inhalation LC50 (4 hour(s)) 28.1 mg/l (rat) - Vapours may cause drowsiness and dizziness.

Irritation / Corrosivity

Causes serious eye irritation. Causes skin irritation.

Sensitisation

It is not a skin sensitiser.

Repeated dose toxicity

Inhalation NOAEC = 1131 mg/m³ (rat), 2 Year(s) - May cause damage to organs through prolonged or repeated exposure: neuropsychological effects, auditory dysfunction and effects on colour vision.

Carcinogenicity

It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity

There is no evidence of mutagenic potential.

Reproductive toxicity

Suspected of damaging the unborn child. NOAEC: 2.8 mg/liter (rat)

SECTION 12: ECOLOGICAL INFORMATION

Substances in preparations / mixtures:

Toluene (CAS No. 108-88-3)

Acute toxicity

LC50 (96 hour): 5.5 mg/l (*Oncorhynchus kisutch*)
EC50 (48 hour): 3.78 mg/l (*Ceriodaphnia dubia*)
EC50 (3 hour): 134 mg/l (Algae)

Long Term Toxicity

NOEC (40 days): 1.39 mg/l (*Oncorhynchus kisutch*)
NOEC (7 days): 0.74 mg/l (*Ceriodaphnia dubia*)

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

SECTION 14: TRANSPORT INFORMATION

	<u>U.S. DOT</u>	<u>Sea transport (IMDG)</u>	<u>Air transport (ICAO/IATA)</u>
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable

Valvoline Premium Carb & Throttle Body Cleaner

PN# 681045

Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
Acetone	67-64-1	40 - 60	5000
Methanol	67-56-1	10 - 30	5000
Toluene	108-88-3	3 - 6	1000

SARA 311/312 - Hazard Categories: See SECTION 2: HAZARDS IDENTIFICATION

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
Methanol	67-56-1	1 - 5
Toluene	108-88-3	15 - 20

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	----	----	----

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
Methanol	67-56-1	Developmental
Toluene	108-88-3	Developmental, Female Reproductive

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: May 21, 2025

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

Hazard Statement(s)

- H225: Highly flammable liquid and vapor.
- H301: Toxic if swallowed.
- H304: May be fatal if swallowed and enters airways.
- H311: Toxic in contact with skin.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H331: Toxic if inhaled.
- H336: May cause drowsiness or dizziness.
- H361: Suspected of damaging fertility or the unborn child.
- H370: Causes damage to organs.
- H373: May cause damage to organs through prolonged or repeated exposure.

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.