		Page: 1
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/3/2016
		SDS Number: R0076416
Valvoline™ MOLY FORTIFIED MULTIPURPOSE GREASE		Version: 1.1
VV630		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ MOLY FORTIFIED MULTIPURPOSE GREASE

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509 United States of America SDS@valvoline.com	Emergency telephone number 1-800-VALVOLINE Regulatory Information Number 1-800-TEAMVAL Product Information 1-800-TEAMVAL
---	--

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.


SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components


Chemical Name	CAS-No.	Classification	Concentration (%)
RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED	64742-01-4	Not a hazardous substance or mixture.	50.00

		Page: 2
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/3/2016
		SDS Number: R0076416
Valvoline™ MOLY FORTIFIED MULTIPURPOSE GREASE		Version: 1.1
VV630		

Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	Not a hazardous substance or mixture.	50.00
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA	64742-52-5	Not a hazardous substance or mixture.	9.99
MOLYBDENUM DISULFIDE	1317-33-5	Not a hazardous substance or mixture.	2.49

SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

		Page: 3
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/3/2016
		SDS Number: R0076416
Valvoline™ MOLY FORTIFIED MULTIPURPOSE GREASE		Version: 1.1
VV630		

the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
Aldehydes
Ketones
Nitrogen oxides (NO_x)
Sulphur oxides
- Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SAFETY DATA SHEET

Revision Date: 07/31/2016

Print Date: 11/3/2016

SDS Number: R0076416

Valvoline™ MOLY FORTIFIED MULTIPURPOSE GREASE

Version: 1.1


VV630

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
- Conditions for safe storage : Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED	64742-01-4	ST ESL	1,000 µg/m ³	TX ESL
		AN ESL	100 µg/m ³	TX ESL
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	PEL	500 ppm 2,000 mg/m ³	OSHA_TRANS
		REL	5 mg/m ³ Mist.	NIOSH/GUIDE
		STEL	10 mg/m ³ Mist.	NIOSH/GUIDE
		PEL	5 mg/m ³ Mist.	OSHA_TRANS
		TWA	5 mg/m ³ Mist.	Z1A
		TWA	400 ppm 1,600 mg/m ³	Z1A
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA	64742-52-5	PEL	500 ppm 2,000 mg/m ³	OSHA_TRANS
		REL	5 mg/m ³ Mist.	NIOSH/GUIDE
		STEL	10 mg/m ³ Mist.	NIOSH/GUIDE
		PEL	5 mg/m ³ Mist.	OSHA_TRANS
MOLYBDENUM DISULFIDE	1317-33-5	TWA	3 mg/m ³ Respirable	ACGIH

		Page: 5
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/3/2016
		SDS Number: R0076416
Valvoline™ MOLY FORTIFIED MULTIPURPOSE GREASE		Version: 1.1
VV630		

			fraction. (as Mo)	
		TWA	10 mg/m3 Inhalable fraction. (as Mo)	ACGIH
		PEL	15 mg/m3 Total dust. (as Mo)	OSHA_TRA NS
		TWA	10 mg/m3 Total dust. (as Mo)	Z1A

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
Safety shoes
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Physical state : liquid


Colour : grey

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

		Page: 6
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/3/2016
		SDS Number: R0076416
Valvoline™ MOLY FORTIFIED MULTIPURPOSE GREASE		Version: 1.1
VV630		

Boiling point/boiling range : 640 °F / 338 °C

Flash point : 500 °F / 260 °C

Evaporation rate :
No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure :
No data available

Relative vapour density :
No data available

Relative density : No data available

Density : 0.94 g/cm³ (20 °C)

Solubility(ies)
Water solubility : negligible

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : > 315 °C


Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm²/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

		Page: 7
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/3/2016
		SDS Number: R0076416
Valvoline™ MOLY FORTIFIED MULTIPURPOSE GREASE		Version: 1.1
VV630		

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide
Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : LD 50 (Rat): 6,477 mg/kg
Method: Acute toxicity estimate

Acute dermal toxicity : LD 50 (Rabbit): 169,492 mg/kg
Method: Acute toxicity estimate

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Information given is based on data obtained from similar substances.


Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 402
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): > 5,000 mg/kg

		Page: 8
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/3/2016
		SDS Number: R0076416
Valvoline™ MOLY FORTIFIED MULTIPURPOSE GREASE		Version: 1.1
VV630		

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:

Acute oral toxicity : LD 50 (Rat): > 5 g/kg

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
 Assessment: Not classified as acutely toxic by dermal absorption under GHS.
 Remarks: No mortality observed at this dose.

MOLYBDENUM DISULFIDE:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC 50 (Rat): > 2.82 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Species: Rabbit

Result: Not irritating to skin

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Result: Mildly irritating to skin

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:

Species: Rabbit

Result: Not irritating to skin

MOLYBDENUM DISULFIDE:

Result: Not irritating to skin


Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

		Page: 9
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/3/2016
		SDS Number: R0076416
Valvoline™ MOLY FORTIFIED MULTIPURPOSE GREASE		Version: 1.1
VV630		

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Species: Rabbit

Result: Mildly irritating to eyes

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Result: Mildly irritating to eyes

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:

Species: Rabbit

Result: Mildly irritating to eyes

MOLYBDENUM DISULFIDE:

Result: Not irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.


Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

		Page: 10
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/3/2016
		SDS Number: R0076416
Valvoline™ MOLY FORTIFIED MULTIPURPOSE GREASE		Version: 1.1
VV630		

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:
No aspiration toxicity classification

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:


Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Scud (Gammarus pulex)): > 10,000 mg/l
Exposure time: 48 h
Test Type: semi-static test
Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test

		Page: 11
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/3/2016
		SDS Number: R0076416
Valvoline™ MOLY FORTIFIED MULTIPURPOSE GREASE		Version: 1.1
VV630		

Test substance: WAF
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
Exposure time: 21 d
Test Type: semi-static test
Test substance: WAF
Method: OECD Test Guideline 211

Persistence and degradability

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Information given is based on data obtained from similar substances.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:

Biodegradability : Result: Inherently biodegradable
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Bioaccumulative potential

Components:

No data available


Mobility in soil

Components:

No data available

Other adverse effects

No data available

		Page: 12
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/3/2016
		SDS Number: R0076416
Valvoline™ MOLY FORTIFIED MULTIPURPOSE GREASE		Version: 1.1
VV630		

Product:

Additional ecological information : No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods


TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

		Page: 13
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/3/2016
		SDS Number: R0076416
Valvoline™ MOLY FORTIFIED MULTIPURPOSE GREASE		Version: 1.1
VV630		

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : No SARA Hazards


SARA 313 Component(s)SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED	64742-01-4	50.00 - 70.00 %
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	50.00 - 70.00 %
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA	64742-52-5	5.00 - 10.00 %
ETHYLENE 1-OCTENE COPOLYMER	26221-73-8	5.00 - 10.00 %

New Jersey Right To Know

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED	64742-01-4	50.00 - 70.00 %
--	------------	-----------------

		Page: 14
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/3/2016
		SDS Number: R0076416
Valvoline™ MOLY FORTIFIED MULTIPURPOSE GREASE		Version: 1.1
VV630		

Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	50.00 - 70.00 %
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA	64742-52-5	5.00 - 10.00 %
ETHYLENE 1-OCTENE COPOLYMER	26221-73-8	5.00 - 10.00 %
MOLYBDENUM DISULFIDE	1317-33-5	1.00 - 5.00 %

California Prop 65


This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL.
- AUSTR : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECL : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECL (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

		Page: 15
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/3/2016
		SDS Number: R0076416
Valvoline™ MOLY FORTIFIED MULTIPURPOSE GREASE		Version: 1.1
VV630		

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/31/2016

<p>NFPA:</p> <div style="text-align: center;"> <p>Flammability</p>  <p>Health Instability</p> <p>Special hazard.</p> </div>	<p>HMS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: yellow;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	0	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	0						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification
Combustible Liquid Class IIIB


Full text of H-Statements referred to under sections 2 and 3.

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

- ACGIH : American Conference of Industrial Hygienists
- BEI : Biological Exposure Index
- CAS : Chemical Abstracts Service (Division of the American Chemical Society).
- CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
- FG : Food grade
- GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
- H-statement : Hazard Statement
- IATA : International Air Transport Association.

		Page: 16
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/3/2016
		SDS Number: R0076416
Valvoline™ MOLY FORTIFIED MULTIPURPOSE GREASE		Version: 1.1
VV630		

IATA-DGR : Dangerous Goods Regulation by the “International Air Transport Association” (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the “International Civil Aviation Organization”

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System