



## Material Safety Data Sheet

Copyright, 2014, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**PRODUCT NAME:** 3M™ Composite & Metal Bonding Adhesive - 35 PN 08273, 58273

**MANUFACTURER:** 3M

**DIVISION:** Automotive Aftermarket

**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA

**Telephone:** 1-888-3M HELPS (1-888-364-3577)

**EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)**

**Issue Date:** 05/30/14

**Supersedes Date:** 05/23/14

**Document Group:** 27-0452-6

### ID Number(s):

LB-K100-0712-4, LB-K100-0907-6, 41-0003-6755-1, 41-0003-8005-9, 41-9103-0380-3, 60-4550-5028-0, 60-4550-7095-7

**This product is a kit or a multipart product which consists of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are:**

27-4706-1, 27-0145-6

**Reason for Reissue:** The MSDS has been revised because 3M has adopted the 16-section ANSI/ISO format. The potential hazards of the product have not changed. We encourage you to reread the MSDS and review the information.

Revision Changes: Not Applicable

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**



## Safety Data Sheet

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 27-4706-1 | <b>Version Number:</b>  | 3.00     |
| <b>Issue Date:</b>     | 05/23/14  | <b>Supersedes Date:</b> | 12/10/12 |

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ SMC/Fiberglass Repair Adhesive-35 Part A, PN 08273, 58273

#### Product Identification Numbers

LB-K100-0739-0, LB-K100-0908-6, LB-K100-1317-8

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive, Repair Adhesive

#### 1.3. Supplier's details

|                      |                                         |
|----------------------|-----------------------------------------|
| <b>MANUFACTURER:</b> | 3M                                      |
| <b>DIVISION:</b>     | Automotive Aftermarket                  |
| <b>ADDRESS:</b>      | 3M Center, St. Paul, MN 55144-1000, USA |
| <b>Telephone:</b>    | 1-888-3M HELPS (1-888-364-3577)         |

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

#### 2.1. Hazard classification

Acute Toxicity (inhalation): Category 4.  
Serious Eye Damage/Irritation: Category 2A.  
Skin Corrosion/Irritation: Category 2.  
Respiratory Sensitizer: Category 1.  
Skin Sensitizer: Category 1.  
Specific Target Organ Toxicity (respiratory irritation): Category 3.  
Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

##### Signal word

Danger

### Symbols

Exclamation mark | Health Hazard |

### Pictograms



### Hazard Statements

Causes serious eye irritation.

Causes skin irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Harmful if inhaled.

May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure:  
respiratory system |

### Precautionary Statements

#### Prevention:

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

In case of inadequate ventilation wear respiratory protection.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

#### Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Call a POISON CENTER or doctor/physician if you feel unwell.

#### Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

### 2.3. Hazards not otherwise classified

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

## SECTION 3: Composition/information on ingredients

| <b>Ingredient</b>                          | <b>C.A.S. No.</b> | <b>% by Wt</b>         |
|--------------------------------------------|-------------------|------------------------|
| Methylene Phenylene Isocyanate             | 101-68-8          | 25 - 60 Trade Secret * |
| Urethane Prepolymer (NJTSRN 04499600-6779) | Trade Secret*     | 15 - 40 Trade Secret * |
| Diisocyanate Polymer                       | Trade Secret*     | 5 - 15 Trade Secret *  |
| Aluminium Silicate (NJTSRN 04499600-6789)  | Trade Secret*     | 7 - 13 Trade Secret *  |
| Talc                                       | 14807-96-6        | 7 - 13 Trade Secret *  |
| Thickening Agent (NJTSRN 04499600-6784)    | Trade Secret*     | 1 - 5 Trade Secret *   |

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### **If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

DO NOT USE WATER

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

#### **Substance**

Carbon monoxide  
Carbon dioxide  
Hydrogen Cyanide  
Oxides of Nitrogen

#### **Condition**

During Combustion  
During Combustion  
During Combustion  
During Combustion

**5.3. Special protective actions for fire-fighters**

No unusual fire or explosion hazards are anticipated.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Dispose of collected material as soon as possible.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

For industrial or professional use only. Do not use in a confined area with minimal air exchange. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep container tightly closed to prevent loss of stabilizing materials. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from acids. Store away from strong bases.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

| Ingredient                     | C.A.S. No. | Agency                  | Limit type                                                                                         | Additional Comments |
|--------------------------------|------------|-------------------------|----------------------------------------------------------------------------------------------------|---------------------|
| FREE ISOCYANATES               | 101-68-8   | Manufacturer determined | TWA:0.005 ppm;STEL:0.02 ppm                                                                        |                     |
| Methylene Phenylene Isocyanate | 101-68-8   | ACGIH                   | TWA:0.005 ppm                                                                                      |                     |
| Methylene Phenylene Isocyanate | 101-68-8   | OSHA                    | CEIL:0.2 mg/m3(0.02 ppm)                                                                           |                     |
| Talc                           | 14807-96-6 | ACGIH                   | TWA(respirable fraction):2 mg/m3                                                                   |                     |
| Talc                           | 14807-96-6 | CMRG                    | TWA(as respirable dust):0.5 mg/m3                                                                  |                     |
| Talc                           | 14807-96-6 | OSHA                    | TWA concentration(as total dust):0.3 mg/m3;TWA concentration(respirable):0.1 mg/m3(2.4 millions of |                     |

|                                           |              |       |                                                                  |  |
|-------------------------------------------|--------------|-------|------------------------------------------------------------------|--|
|                                           |              |       | particles/cu. ft.);TWA:20 millions of particles/cu. ft.          |  |
| Aluminium Silicate (NJTSRN 04499600-6789) | Trade Secret | ACGIH | TWA(respirable fraction):1 mg/m3                                 |  |
| Thickening Agent (NJTSRN 04499600-6784)   | Trade Secret | OSHA  | TWA concentration:0.8 mg/m3;TWA:20 millions of particles/cu. ft. |  |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Wear eye/face protection. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Wear protective gloves.

Gloves made from the following material(s) are recommended: Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

General Physical Form:

Liquid

|                                                |                                                               |
|------------------------------------------------|---------------------------------------------------------------|
| <b>Odor, Color, Grade:</b>                     | White, slight isocyanate odor                                 |
| <b>Odor threshold</b>                          | <i>No Data Available</i>                                      |
| <b>pH</b>                                      | <i>Not Applicable</i>                                         |
| <b>Melting point</b>                           | <i>Not Applicable</i>                                         |
| <b>Boiling Point</b>                           | <i>No Data Available</i>                                      |
| <b>Flash Point</b>                             | > 383 °F [ <i>Test Method:</i> Closed Cup]                    |
| <b>Evaporation rate</b>                        | < 1 [ <i>Ref Std:</i> ETHER=1]                                |
| <b>Flammability (solid, gas)</b>               | Not Applicable                                                |
| <b>Flammable Limits(LEL)</b>                   | <i>No Data Available</i>                                      |
| <b>Flammable Limits(UEL)</b>                   | <i>No Data Available</i>                                      |
| <b>Vapor Pressure</b>                          | .010 mmHg [ <i>Details:</i> @77.00 F for product]             |
| <b>Vapor Density</b>                           | < 1 [ <i>Ref Std:</i> AIR=1]                                  |
| <b>Density</b>                                 | 10.72 lb/gal                                                  |
| <b>Specific Gravity</b>                        | 1.288 [ <i>Ref Std:</i> WATER=1]                              |
| <b>Solubility In Water</b>                     | <i>No Data Available</i>                                      |
| <b>Solubility- non-water</b>                   | <i>No Data Available</i>                                      |
| <b>Partition coefficient: n-octanol/ water</b> | <i>No Data Available</i>                                      |
| <b>Autoignition temperature</b>                | <i>No Data Available</i>                                      |
| <b>Decomposition temperature</b>               | <i>No Data Available</i>                                      |
| <b>Viscosity</b>                               | <i>No Data Available</i>                                      |
| <b>Hazardous Air Pollutants</b>                | 45.2 % weight [ <i>Test Method:</i> Calculated]               |
| <b>Volatile Organic Compounds</b>              | 0 g/l [ <i>Test Method:</i> calculated SCAQMD rule 443.1]     |
| <b>Volatile Organic Compounds</b>              | 0 % weight [ <i>Test Method:</i> calculated per CARB title 2] |
| <b>Percent volatile</b>                        | 0 %                                                           |
| <b>VOC Less H2O &amp; Exempt Solvents</b>      | 0 g/l [ <i>Test Method:</i> calculated SCAQMD rule 443.1]     |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization may occur.

### 10.4. Conditions to avoid

Heat  
Sparks and/or flames

### 10.5. Incompatible materials

Strong acids  
Strong bases  
Water

### 10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
|------------------|------------------|

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation:

Harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause target organ effects after inhalation.

##### Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

##### Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

##### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Target Organ Effects:

##### Prolonged or repeated exposure may cause:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

##### Additional Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

| Name                                       | Route                          | Species | Value                                           |
|--------------------------------------------|--------------------------------|---------|-------------------------------------------------|
| Overall product                            | Inhalation-Vapor(4 hr)         |         | No data available; calculated ATE 10 - 20 mg/l  |
| Overall product                            | Ingestion                      |         | No data available; calculated ATE > 5,000 mg/kg |
| Methylene Phenylene Isocyanate             | Inhalation-Vapor               |         | LC50 estimated to be 10 - 20 mg/l               |
| Methylene Phenylene Isocyanate             | Dermal                         | Rabbit  | LD50 > 5,000 mg/kg                              |
| Methylene Phenylene Isocyanate             | Inhalation-Dust/Mist (4 hours) | Rat     | LC50 0.369 mg/l                                 |
| Methylene Phenylene Isocyanate             | Ingestion                      | Rat     | LD50 31,600 mg/kg                               |
| Urethane Prepolymer (NJTSRN 04499600-6779) | Ingestion                      |         | LD50 estimated to be 2,000 - 5,000 mg/kg        |
| Aluminium Silicate (NJTSRN 04499600-6789)  | Dermal                         | Rabbit  | LD50 > 2,000 mg/kg                              |
| Aluminium Silicate (NJTSRN 04499600-6789)  | Inhalation-Dust/Mist (4 hours) | Rat     | LC50 > 4.57 mg/l                                |
| Aluminium Silicate (NJTSRN 04499600-6789)  | Ingestion                      | Rat     | LD50 > 5,000 mg/kg                              |
| Talc                                       | Dermal                         |         | LD50 Not available                              |
| Talc                                       | Ingestion                      |         | LD50 Not available                              |
| Thickening Agent (NJTSRN 04499600-6784)    | Dermal                         | Rabbit  | LD50 > 5,000 mg/kg                              |
| Thickening Agent (NJTSRN 04499600-6784)    | Inhalation-Dust/Mist (4 hours) | Rat     | LC50 > 0.691 mg/l                               |
| Thickening Agent (NJTSRN 04499600-6784)    | Ingestion                      | Rat     | LD50 > 5,110 mg/kg                              |

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

| Name                                    | Species                 | Value                     |
|-----------------------------------------|-------------------------|---------------------------|
| Methylene Phenylene Isocyanate          | official classification | Irritant                  |
| Talc                                    | Rabbit                  | No significant irritation |
| Thickening Agent (NJTSRN 04499600-6784) | Rabbit                  | No significant irritation |

**Serious Eye Damage/Irritation**

| Name                                    | Species                 | Value                     |
|-----------------------------------------|-------------------------|---------------------------|
| Methylene Phenylene Isocyanate          | official classification | Severe irritant           |
| Talc                                    | Rabbit                  | No significant irritation |
| Thickening Agent (NJTSRN 04499600-6784) | Rabbit                  | No significant irritation |

**Skin Sensitization**

| Name                                    | Species                 | Value           |
|-----------------------------------------|-------------------------|-----------------|
| Methylene Phenylene Isocyanate          | official classification | Sensitizing     |
| Thickening Agent (NJTSRN 04499600-6784) | Human and animal        | Not sensitizing |

**Respiratory Sensitization**

| Name                           | Species | Value           |
|--------------------------------|---------|-----------------|
| Methylene Phenylene Isocyanate | Human   | Sensitizing     |
| Talc                           | Human   | Not sensitizing |

**Germ Cell Mutagenicity**

| Name                                    | Route    | Value                                                                        |
|-----------------------------------------|----------|------------------------------------------------------------------------------|
| Methylene Phenylene Isocyanate          | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Talc                                    | In Vitro | Not mutagenic                                                                |
| Talc                                    | In vivo  | Not mutagenic                                                                |
| Thickening Agent (NJTSRN 04499600-6784) | In Vitro | Not mutagenic                                                                |

**Carcinogenicity**

| Name                                    | Route         | Species | Value                                                                        |
|-----------------------------------------|---------------|---------|------------------------------------------------------------------------------|
| Methylene Phenylene Isocyanate          | Inhalation    | Rat     | Some positive data exist, but the data are not sufficient for classification |
| Talc                                    | Inhalation    | Rat     | Some positive data exist, but the data are not sufficient for classification |
| Thickening Agent (NJTSRN 04499600-6784) | Not Specified | Mouse   | Some positive data exist, but the data are not sufficient for classification |

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

| Name                                    | Route      | Value                                                                                      | Species | Test Result           | Exposure Duration    |
|-----------------------------------------|------------|--------------------------------------------------------------------------------------------|---------|-----------------------|----------------------|
| Methylene Phenylene Isocyanate          | Inhalation | Some positive developmental data exist, but the data are not sufficient for classification | Rat     | NOAEL 0.004 mg/l      | during organogenesis |
| Talc                                    | Ingestion  | Not toxic to development                                                                   | Rat     | NOAEL 1,600 mg/kg     | during organogenesis |
| Thickening Agent (NJTSRN 04499600-6784) | Ingestion  | Not toxic to female reproduction                                                           | Rat     | NOAEL 509 mg/kg/day   | 1 generation         |
| Thickening Agent (NJTSRN 04499600-6784) | Ingestion  | Not toxic to male reproduction                                                             | Rat     | NOAEL 497 mg/kg/day   | 1 generation         |
| Thickening Agent (NJTSRN 04499600-6784) | Ingestion  | Not toxic to development                                                                   | Rat     | NOAEL 1,350 mg/kg/day | during organogenesis |

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

| Name                           | Route      | Target Organ(s)        | Value                            | Species                 | Test Result         | Exposure Duration |
|--------------------------------|------------|------------------------|----------------------------------|-------------------------|---------------------|-------------------|
| Methylene Phenylene Isocyanate | Inhalation | respiratory irritation | May cause respiratory irritation | official classification | NOAEL Not available |                   |

**Specific Target Organ Toxicity - repeated exposure**

| Name                                    | Route      | Target Organ(s)                         | Value                                                                        | Species | Test Result         | Exposure Duration     |
|-----------------------------------------|------------|-----------------------------------------|------------------------------------------------------------------------------|---------|---------------------|-----------------------|
| Methylene Phenylene Isocyanate          | Inhalation | respiratory system                      | Causes damage to organs through prolonged or repeated exposure               | Rat     | LOAEL 0.004 mg/l    | 13 weeks              |
| Talc                                    | Inhalation | pneumoconiosis                          | Causes damage to organs through prolonged or repeated exposure               | Human   | NOAEL Not available | occupational exposure |
| Talc                                    | Inhalation | pulmonary fibrosis   respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat     | NOAEL 18 mg/m3      | 113 weeks             |
| Thickening Agent (NJTSRN 04499600-6784) | Inhalation | respiratory system   silicosis          | All data are negative                                                        | Human   | NOAEL Not available | occupational exposure |

**Aspiration Hazard**

| Name | Value |
|------|-------|
|      |       |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - Yes   Pressure Hazard - No   Reactivity Hazard - Yes   Immediate Hazard - Yes   Delayed Hazard - Yes

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

| <u>Ingredient</u>                                                             | <u>C.A.S. No</u> | <u>% by Wt</u> |
|-------------------------------------------------------------------------------|------------------|----------------|
| Methylene Phenylene Isocyanate                                                | 101-68-8         | 25 - 60        |
| Methylene Phenylene Isocyanate<br>(DIISOCYANATES (CERTAIN CHEMICALS<br>ONLY)) | 101-68-8         | 25 - 60        |
| Methylene Phenylene Isocyanate (Benzene, 1,1'-<br>methylenebis[4-isocyanato-) | 101-68-8         | 25 - 60        |

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

**Health:** 2 **Flammability:** 1 **Instability:** 1 **Special Hazards:** Reacts with Water

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Document Group:** 27-4706-1  
**Issue Date:** 05/23/14

**Version Number:** 3.00  
**Supersedes Date:** 12/10/12

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at [www.3M.com](http://www.3M.com)



## Safety Data Sheet

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 27-0145-6 | <b>Version Number:</b>  | 3.00     |
| <b>Issue Date:</b>     | 05/23/14  | <b>Supersedes Date:</b> | 12/10/12 |

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ SMC/Fiberglass Repair Adhesive-35 Part B, PN 08273, 58273

#### Product Identification Numbers

LB-K100-0711-6, LB-K100-0910-5, LB-K100-1317-9

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive, Body Repair

#### 1.3. Supplier's details

|                      |                                         |
|----------------------|-----------------------------------------|
| <b>MANUFACTURER:</b> | 3M                                      |
| <b>DIVISION:</b>     | Automotive Aftermarket                  |
| <b>ADDRESS:</b>      | 3M Center, St. Paul, MN 55144-1000, USA |
| <b>Telephone:</b>    | 1-888-3M HELPS (1-888-364-3577)         |

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

#### 2.1. Hazard classification

Respiratory Sensitizer: Category 1.  
Skin Sensitizer: Category 1.  
Reproductive Toxicity: Category 2.  
Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Health Hazard |

**Pictograms****Hazard Statements**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 May cause an allergic skin reaction.  
 Suspected of damaging fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure:  
 respiratory system |

**Precautionary Statements****Prevention:**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 In case of inadequate ventilation wear respiratory protection.  
 Wear protective gloves.  
 Do not eat, drink or smoke when using this product.  
 Wash thoroughly after handling.  
 Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.  
 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.  
 IF ON SKIN: Wash with plenty of soap and water.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Wash contaminated clothing before reuse.  
 Get medical advice/attention if you feel unwell.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Hazards not otherwise classified**

None.

2% of the mixture consists of ingredients of unknown acute oral toxicity.

## SECTION 3: Composition/information on ingredients

| Ingredient                                 | C.A.S. No.    | % by Wt                |
|--------------------------------------------|---------------|------------------------|
| Polyether Polyol (NJTSRN 04499600-6782)    | Trade Secret* | 30 - 60 Trade Secret * |
| Polyol (NJTSRN 04499600-6783)              | Trade Secret* | 15 - 40 Trade Secret * |
| Talc                                       | 14807-96-6    | 15 - 40 Trade Secret * |
| Urethane Prepolymer (NJTSRN 04499600-6781) | Trade Secret* | 3 - 7 Trade Secret *   |
| Thickening Agent                           | Trade Secret* | 1 - 5 Trade Secret *   |

|                  |            |                      |
|------------------|------------|----------------------|
| Piperazine       | 110-85-0   | < 1 Trade Secret *   |
| Quartz Silica    | 14808-60-7 | < 0.1 Trade Secret * |
| Titanium Dioxide | 13463-67-7 | < 0.1 Trade Secret * |

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### Hazardous Decomposition or By-Products

##### Substance

Carbon monoxide  
Carbon dioxide  
Oxides of Nitrogen

##### Condition

During Combustion  
During Combustion  
During Combustion

### 5.3. Special protective actions for fire-fighters

No unusual fire or explosion hazards are anticipated.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

## 6.2. Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

# SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

For industrial or professional use only. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

## 7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidizing agents.

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

### Occupational exposure limits

| Ingredient       | C.A.S. No. | Agency | Limit type                                                                                                                                                 | Additional Comments |
|------------------|------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|
| Piperazine       | 110-85-0   | ACGIH  | TWA(as piperazine, inhalable fraction & vapor):0.03 ppm                                                                                                    | Sensitizer          |
| Titanium Dioxide | 13463-67-7 | ACGIH  | TWA:10 mg/m3                                                                                                                                               |                     |
| Titanium Dioxide | 13463-67-7 | CMRG   | TWA(as respirable dust):5 mg/m3                                                                                                                            |                     |
| Titanium Dioxide | 13463-67-7 | OSHA   | TWA(as total dust):15 mg/m3                                                                                                                                |                     |
| Talc             | 14807-96-6 | ACGIH  | TWA(respirable fraction):2 mg/m3                                                                                                                           |                     |
| Talc             | 14807-96-6 | CMRG   | TWA(as respirable dust):0.5 mg/m3                                                                                                                          |                     |
| Talc             | 14807-96-6 | OSHA   | TWA concentration(as total dust):0.3 mg/m3;TWA concentration(respirable):0.1 mg/m3(2.4 millions of particles/cu. ft.);TWA:20 millions of particles/cu. ft. |                     |
| Quartz Silica    | 14808-60-7 | ACGIH  | TWA(respirable fraction):0.025 mg/m3                                                                                                                       |                     |
| Quartz Silica    | 14808-60-7 | OSHA   | TWA concentration(as total                                                                                                                                 |                     |

|  |  |  |                                                                                                                               |  |
|--|--|--|-------------------------------------------------------------------------------------------------------------------------------|--|
|  |  |  | dust):0.3 mg/m <sup>3</sup> ;TWA<br>concentration(respirable):0.1<br>mg/m <sup>3</sup> (2.4 millions of<br>particles/cu. ft.) |  |
|--|--|--|-------------------------------------------------------------------------------------------------------------------------------|--|

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                                  |                                                        |
|----------------------------------|--------------------------------------------------------|
| <b>General Physical Form:</b>    | Liquid                                                 |
| <b>Specific Physical Form:</b>   | Viscous                                                |
| <b>Odor, Color, Grade:</b>       | Slight ammonia like odor, dark green.                  |
| <b>Odor threshold</b>            | <i>No Data Available</i>                               |
| <b>pH</b>                        | <i>Not Applicable</i>                                  |
| <b>Melting point</b>             | <i>No Data Available</i>                               |
| <b>Boiling Point</b>             | <i>No Data Available</i>                               |
| <b>Flash Point</b>               | > 340 °F [ <i>Test Method:</i> Tagliabue Closed Cup]   |
| <b>Evaporation rate</b>          | <=1 [ <i>Details:</i> Gels with exposure to humidity.] |
| <b>Flammability (solid, gas)</b> | Not Applicable                                         |
| <b>Flammable Limits(LEL)</b>     | <i>Not Applicable</i>                                  |

|                                                |                                                                  |
|------------------------------------------------|------------------------------------------------------------------|
| <b>Flammable Limits(UEL)</b>                   | <i>Not Applicable</i>                                            |
| <b>Vapor Pressure</b>                          | $\leq 0.000004$ mmHg [ <i>@ 68 °F</i> ]                          |
| <b>Vapor Density</b>                           | $\geq 1$ [ <i>Ref Std: AIR=1</i> ]                               |
| <b>Density</b>                                 | 1.2 g/ml                                                         |
| <b>Specific Gravity</b>                        | 1.0 - 1.2 [ <i>Ref Std: WATER=1</i> ]                            |
| <b>Solubility in Water</b>                     | Negligible                                                       |
| <b>Solubility- non-water</b>                   | <i>No Data Available</i>                                         |
| <b>Partition coefficient: n-octanol/ water</b> | <i>No Data Available</i>                                         |
| <b>Autoignition temperature</b>                | <i>No Data Available</i>                                         |
| <b>Decomposition temperature</b>               | <i>No Data Available</i>                                         |
| <b>Viscosity</b>                               | <i>No Data Available</i>                                         |
| <b>Hazardous Air Pollutants</b>                | 0 % weight [ <i>Test Method: Calculated</i> ]                    |
| <b>Volatile Organic Compounds</b>              | 1 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]       |
| <b>Volatile Organic Compounds</b>              | 0.1 % weight [ <i>Test Method: calculated per CARB title 2</i> ] |
| <b>Percent volatile</b>                        | 0.093 % weight                                                   |
| <b>VOC Less H2O &amp; Exempt Solvents</b>      | 1 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]       |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

High shear and high temperature conditions

### 10.5. Incompatible materials

Strong acids

Strong bases

Alcohols

Strong oxidizing agents

### 10.6. Hazardous decomposition products

#### Substance

Aldehydes

Hydrogen Cyanide

#### Condition

Not Specified

Not Specified

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be

reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation:

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

Vapors released during curing may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

##### Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

##### Eye Contact:

Vapors released during curing may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

##### Ingestion:

No health effects are expected.

#### Target Organ Effects:

##### Prolonged or repeated exposure may cause:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

##### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### Carcinogenicity:

| Ingredient          | C.A.S. No. | Class Description              | Regulation                                  |
|---------------------|------------|--------------------------------|---------------------------------------------|
| Quartz Silica       | 14808-60-7 | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |
| SILICA, CRYSTALLINE | 14808-60-7 | Known human carcinogen         | National Toxicology Program Carcinogens     |
| Titanium Dioxide    | 13463-67-7 | Grp. 2B: Possible human carc.  | International Agency for Research on Cancer |

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

| Name                                       | Route     | Species | Value                                           |
|--------------------------------------------|-----------|---------|-------------------------------------------------|
| Overall product                            | Ingestion |         | No data available; calculated ATE > 5,000 mg/kg |
| Polyether Polyol (NJTSRN 04499600-6782)    | Dermal    | Rat     | LD50 > 2,000 mg/kg                              |
| Polyether Polyol (NJTSRN 04499600-6782)    | Ingestion | Rat     | LD50 > 2,500 mg/kg                              |
| Talc                                       | Dermal    |         | LD50 Not available                              |
| Talc                                       | Ingestion |         | LD50 Not available                              |
| Polyol (NJTSRN 04499600-6783)              | Dermal    | Rabbit  | LD50 > 5,000 mg/kg                              |
| Polyol (NJTSRN 04499600-6783)              | Ingestion | Rat     | LD50 > 10,000 mg/kg                             |
| Urethane Prepolymer (NJTSRN 04499600-6781) | Ingestion |         | LD50 estimated to be 2,000 - 5,000 mg/kg        |

|                  |                                |        |                                    |
|------------------|--------------------------------|--------|------------------------------------|
| Piperazine       | Dermal                         |        | estimated to be > 5,000 mg/kg      |
| Piperazine       | Inhalation-Dust/Mist           |        | estimated to be > 12.5 mg/l        |
| Piperazine       | Inhalation-Vapor               |        | estimated to be > 50 mg/l          |
| Piperazine       | Ingestion                      |        | estimated to be > 5,000 mg/kg      |
| Quartz Silica    | Dermal                         |        | LD50 estimated to be > 5,000 mg/kg |
| Quartz Silica    | Ingestion                      |        | LD50 estimated to be > 5,000 mg/kg |
| Titanium Dioxide | Dermal                         | Rabbit | LD50 > 10,000 mg/kg                |
| Titanium Dioxide | Inhalation-Dust/Mist (4 hours) | Rat    | LC50 > 6.82 mg/l                   |
| Titanium Dioxide | Ingestion                      | Rat    | LD50 > 10,000 mg/kg                |

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

| Name             | Species | Value                     |
|------------------|---------|---------------------------|
| Talc             | Rabbit  | No significant irritation |
| Quartz Silica    |         | No significant irritation |
| Titanium Dioxide | Rabbit  | No significant irritation |

**Serious Eye Damage/Irritation**

| Name             | Species | Value                     |
|------------------|---------|---------------------------|
| Talc             | Rabbit  | No significant irritation |
| Titanium Dioxide | Rabbit  | No significant irritation |

**Skin Sensitization**

| Name             | Species          | Value           |
|------------------|------------------|-----------------|
| Titanium Dioxide | Human and animal | Not sensitizing |

**Respiratory Sensitization**

| Name | Species | Value           |
|------|---------|-----------------|
| Talc | Human   | Not sensitizing |

**Germ Cell Mutagenicity**

| Name             | Route    | Value                                                                        |
|------------------|----------|------------------------------------------------------------------------------|
| Talc             | In Vitro | Not mutagenic                                                                |
| Talc             | In vivo  | Not mutagenic                                                                |
| Quartz Silica    | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Quartz Silica    | In vivo  | Some positive data exist, but the data are not sufficient for classification |
| Titanium Dioxide | In Vitro | Not mutagenic                                                                |
| Titanium Dioxide | In vivo  | Not mutagenic                                                                |

**Carcinogenicity**

| Name             | Route      | Species                 | Value                                                                        |
|------------------|------------|-------------------------|------------------------------------------------------------------------------|
| Talc             | Inhalation | Rat                     | Some positive data exist, but the data are not sufficient for classification |
| Quartz Silica    | Inhalation | Human and animal        | Carcinogenic                                                                 |
| Titanium Dioxide | Ingestion  | Multiple animal species | Not carcinogenic                                                             |
| Titanium Dioxide | Inhalation | Rat                     | Carcinogenic                                                                 |

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test Result | Exposure |
|------|-------|-------|---------|-------------|----------|
|------|-------|-------|---------|-------------|----------|

|      |           |                          |     |                      |                                         |
|------|-----------|--------------------------|-----|----------------------|-----------------------------------------|
| Talc | Ingestion | Not toxic to development | Rat | NOAEL<br>1,600 mg/kg | <b>Duration</b><br>during organogenesis |
|------|-----------|--------------------------|-----|----------------------|-----------------------------------------|

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|------|-------|-----------------|-------|---------|-------------|-------------------|
|      |       |                 |       |         |             |                   |

**Specific Target Organ Toxicity - repeated exposure**

| Name             | Route      | Target Organ(s)                         | Value                                                                        | Species | Test Result         | Exposure Duration     |
|------------------|------------|-----------------------------------------|------------------------------------------------------------------------------|---------|---------------------|-----------------------|
| Talc             | Inhalation | pneumoconiosis                          | Causes damage to organs through prolonged or repeated exposure               | Human   | NOAEL Not available | occupational exposure |
| Talc             | Inhalation | pulmonary fibrosis   respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat     | NOAEL 18 mg/m3      | 113 weeks             |
| Quartz Silica    | Inhalation | silicosis                               | Causes damage to organs through prolonged or repeated exposure               | Human   | NOAEL Not available | occupational exposure |
| Titanium Dioxide | Inhalation | respiratory system                      | Some positive data exist, but the data are not sufficient for classification | Rat     | LOAEL 0.010 mg/l    | 2 years               |
| Titanium Dioxide | Inhalation | pulmonary fibrosis                      | All data are negative                                                        | Human   | NOAEL Not available | occupational exposure |

**Aspiration Hazard**

| Name | Value |
|------|-------|
|      |       |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated &

disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## SECTION 14: Transport Information

Not regulated per U.S. DOT, IATA or IMO.

*These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.*

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No   Pressure Hazard - No   Reactivity Hazard - No   Immediate Hazard - Yes   Delayed Hazard - Yes

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: Other information

### HMIS Hazard Classification

**Health: 2   Flammability: 1   Physical Hazard: 1   Personal Protection: X** - See PPE section.

Hazardous Material Identification System (HMIS® III) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® III ratings are to be used with a fully implemented HMIS® III program. HMIS® is a registered mark of the American Coatings Association (ACA).

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 27-0145-6 | <b>Version Number:</b>  | 3.00     |
| <b>Issue Date:</b>     | 05/23/14  | <b>Supersedes Date:</b> | 12/10/12 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR

USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**