



Prestone



COMMAND

PATENTED FORMULA

HEAVY DUTY ANTIFREEZE/ COOLANT

ANTICONGELANTE/REFRIGERANTE
SERVICIO PESADO

NITRITE FREE

with

EXTENDED LIFE

TECHNOLOGY

con TECNOLOGÍA DE LARGA DURACIÓN

600,000 Mile Service Life*

Vida Útil de 600,000 Millas (965,600 km)



SCAN HERE

P-6102

CONCENTRATE

WARNING: HARMFUL OR FATAL IF SWALLOWED. Read carefully other cautions on back panel.

ADVERTENCIA: DAÑO O FATAL SI SE INGIERE. Lea atentamente otras precauciones al reverso.

1 GAL (3.78 L)
3,78 L (1 GALÓN)



**PATENTED
FORMULA**

**Prestone Command®
HD NITRITE FREE Extended
Life (ELC)** is intended for use and

compatible with ANY nitrite free HD Organic Acid Technology (OAT) coolant in ANY diesel powered commercial vehicle engine or stationary engine with aluminum or other engine metals. Its patented and advanced OAT nitrite free formulation is based upon a concentrated blend of premium long-lasting inhibitors designed to provide up to 600,000 miles / 12,000 hours* of protection against temperature extremes, rust, cavitation corrosion, scale and premature water pump failure. When used as directed, **Prestone**

Command HD NITRITE FREE ELC may be added to the antifreeze/coolant of any HD commercial or stationary engine.

**Provides extended life protection when flushed and filled according to the directions in the vehicle manufacturer's owner's manual.*

Specifications and Performance: Prestone Command HD NITRITE FREE Extended Life (ELC) meets or exceeds performance requirements of the major engine manufacturer's and the following specifications • TMC RP329 • TMC RP338 • ASTM D6210 • ASTM D3306 • ASTM D7583 • SAE J1941

WARNING: CONTAINS ETHYLENE GLYCOL (107-21-1), DIETHYLENE GLYCOL (111-46-6) AND PROPRIETARY INHIBITORS.

DO NOT DRINK ANTIFREEZE OR SOLUTION. DO NOT STORE IN OPEN OR UNLABELED CONTAINERS. AVOID CONTACT WITH EYE, SKIN AND CLOTHING. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING VAPORS OR MISTS. SOLUTION IS POISONOUS TO ANIMALS. CONTAINS ETHYLENE GLYCOL AND DIETHYLENE GLYCOL. IF SWALLOWED, CALL A POISON CENTER OR GO TO A HOSPITAL EMERGENCY ROOM IMMEDIATELY. IF INHALED, MOVE TO FRESH AIR. SEEK MEDICAL ATTENTION IF SYMPTOMS PERSIST. IN CASE OF CONTACT, WASH WITH WATER.

KEEP OUT OF REACH OF CHILDREN

ADVERTENCIA: CONTIENE ETILENGLICOL (107-21-1), DIETILENGLICOL (111-46-6) E INHIBIDORES PATENTADOS.

NO BEBA LA SOLUCIÓN ANTICONGELANTE. NO ALMACENE EN ENVASES ABIERTOS O SIN ETIQUETA. EVITE EL CONTACTO CON LOS OJOS, LA PIEL Y LA ROPA. LÁVESE BIEN DESPUÉS DE MANIPULARLO. EVITE RESPIRAR LOS VAPORES O ROCIOS. LA SOLUCIÓN ES TÓXICA PARA LOS ANIMALES. CONTIENE ETILENGLICOL Y DIETILENGLICOL. SI SE INGIERE, LLAME A UN CENTRO DE CONTROL DE ENVENENAMIENTOS O VAYA A LA SALA DE EMERGENCIA DE UN HOSPITAL INMEDIATAMENTE. SI SE INHALA, SALGA AL AIRE FRESCO. OBTENGA ATENCIÓN MÉDICA SI LOS SÍNTOMAS PERSISTEN. EN CASO DE CONTACTO, LAVE CON AGUA.

MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.

**HEAVY DUTY
NITRITE FREE EXTENDED LIFE
ANTIFREEZE/COOLANT**

CAUTION: Do not remove cooling system cap while cooling system is hot. Do not store antifreeze/coolant in open or unlabeled containers. After use, tighten child resistant cap and wash exposed skin with soap and water.

DIRECTIONS: Check the specific maintenance and changeover intervals, antifreeze/coolant to water ratio, cooling system capacity, and service instructions recommended for your vehicle. Start with a cool and clean cooling system. A minimum of 40%, maximum of 60% antifreeze/coolant is recommended to achieve optimal freeze/boil and corrosion protection, never exceed 70%. Follow the cooling system service instructions recommended for your vehicle when Flushing and Filling your cooling system.



For more information, scan this code or visit our website

WWW.PRESTONECOMMAND.COM

TOP OFF - Check coolant level frequently and top off with the desired ratio of Prestone Command HD NITRITE FREE (ELC) Concentrate and quality water as needed.

Mixing Coolant Technology: Diluting the antifreeze/coolant in your cooling system with different coolant technologies has the potential of reducing protection levels. Refer to engine manufacturer or TMC (RP338A and RP32) for recommendations.

DISPOSING OF USED ANTIFREEZE/COOLANT: Dispose of contents and container in accordance with local and national regulations.

Para instrucciones en español, visite www.PrestoneCommand.com

PROTECTION	FREEZE-UP Protection	BOIL-OVER Protection†	CORROSION Protection
Recommended 50% Prestone Command (ELC) 50% Water	- 34° F	+265° F	Meets or exceeds ASTM D8306, ASTM D6210, ATSM D7583
Maximum 70% Prestone Command (ELC) 30% Water	- 84° F	+276° F	

† Using a 15 lb. pressure cap in good condition.

WARNING: Reproductive Harm - www.P65Warnings.ca.gov

ADVERTENCIA: Daño Reproductivo - www.P65Warnings.ca.gov



Recyclable Bottle
This bottle may not be recyclable in your area

PRESTONE PRODUCTS CORPORATION
69 Eagle Road, Danbury, CT 06810
AFC12000 P-6102 SDS 671

Visit WWW.PRESTONECOMMAND.COM
Questions? Call 1-888-269-0750

©2018 Prestone Products Corporation
Made in the U.S.A. with domestic and imported materials
Patents: Prestone.com/patents