

Prestone[®]

Quality Since 1927

DOT 3 HIGH TEMPERATURE **SYNTHETIC** **BRAKE FLUID**

*DOT 3 460°F Dry Boil Point for Extended
Fluid Life and Added Margin of Safety*



WARNING: CAUSES SEVERE EYE IRRITATION.
CAUSES SKIN IRRITATION. HARMFUL IF SWALLOWED.
Read carefully other cautions on back panel.

1 GAL (3.78 L)

Dieline: 5.8 in w x 7 in h

→ NET WT - 3/16"

Prestone®

Quality Since 1927

Prestone® DOT 3 HIGH TEMPERATURE SYNTHETIC BRAKE FLUID

Complies with Federal Motor Vehicle Safety Standard 116 and SAE J1703. Minimum wet boiling point 284°F (140°C). High boiling point synthetic brake fluid gives an extra margin of safety. Designed for safe operation of today's modern high-powered vehicles. Suitable for all ABS, Disc, and Drum brake systems. Safe to mix with any DOT 3 brake fluid.

CAUTION: Do not refill container or use for other liquids. Avoid spilling fluid on car finish or brake lining.

NOTE: 1. FOLLOW VEHICLE OWNER'S MANUAL RECOMMENDATIONS WHEN ADDING BRAKE FLUID. 2. KEEP BRAKE FLUID CLEAN AND DRY. CONTAMINATION WITH DIRT, WATER, PETROLEUM PRODUCTS, OR OTHER MATERIALS MAY RESULT IN BRAKE FAILURE OR COSTLY REPAIRS. 3. STORE BRAKE FLUID ONLY IN ITS ORIGINAL CONTAINER. KEEP CONTAINER CLEAN AND TIGHTLY CLOSED TO PREVENT ABSORPTION OF MOISTURE. CAUTION: DO NOT REFILL CONTAINER, AND DO NOT USE FOR OTHER LIQUIDS.

DIRECTIONS: Clean all dirt from around cover on master cylinder before removing. Fill unit to level specified by vehicle owner's manual. Replace cover. Check fluid level once a month.

WARNING: Cancer - www.P65Warnings.ca.gov

WARNING: Contains triethylene glycol monobutyl ether (143-22-6), diethylene glycol (111-46-6), tetraethylene glycol monobutyl ether (1559-34-8), polyethylene glycol monobutyl ether (9004-77-7), and other glycols and glycol ethers. **PRECAUTIONARY MEASURES:** Prevent contact with eyes. Avoid contact with skin and clothing. Wash thoroughly after handling. Do not swallow or breathe vapors. Avoid prolonged exposure. Use in a well-ventilated area. **FIRST AID:** If in **eyes**, flush thoroughly with water for at least 20 minutes. Seek immediate medical attention. If on **skin**, remove contaminated clothing and wash exposed skin thoroughly with soap and water. If irritation develops and persists, contact a doctor. If **breathing** is affected, move person into fresh air. If **swallowed**, do NOT induce vomiting. IMMEDIATELY call a local poison control center or hospital emergency department. **KEEP OUT OF THE REACH OF CHILDREN.**

DOT 3 HIGH TEMPERATURE SYNTHETIC BRAKE FLUID

- 460°F Dry Boil Point for Extended Fluid Life
- Added Margin of Safety
- Fits all ABS, Disc, and Drum brake systems



For a video on how to change your brake fluid, scan this code or visit www.prestone.com

Prestone®

PRODUCTS CORPORATION

69 Eagle Road, Danbury, CT 06810
AS402Y P-6544 SDS 042
Visit WWW.PRESTONE.COM
Questions? Call 1-888-269-0750
©2018 Prestone Products Corporation
Patents: Prestone.com/patents
Made in the U.S.A. with domestic and imported materials



Warning - 5/32" ←
Keep Out... - 7/64"
Contains... - 3/32"