



Prestone

COMMAND

**HEAVY DUTY PREDILUTED
ANTIFREEZE/
COOLANT 50/50**

ANTICONGELANTE/REFRIGERANTE
PREDILUIDO 50/50 SERVICIO PESADO

For ANY Heavy Duty Engine

SCA PRE-CHARGED

with

**EXTENDED SERVICE INTERVAL
TECHNOLOGY**

SCA Precargado con Tecnología de Intervalo de Servicio Extendido

- Prevents Coolant Drop Out and Gel
- No Phosphates
- Low Silicate Formula
- Outstanding Corrosion Protection



SCAN HERE

P-6099

DO NOT ADD WATER

WARNING: HARMFUL OR FATAL IF SWALLOWED. Read carefully other cautions on back panel.

ADVERTENCIA: DAÑINO O FATAL SI SE INGIERE. Lea atentamente otras precauciones al reverso.

1 GAL (3.78 L)
3,78 L (1 GALÓN)



**PATENTED
FORMULA**

**Prestone Command®
HD 50/50 Prediluted SCA
Antifreeze/Coolant** is formulated
with advanced corrosion protection
technology. This provides an exceptional
SCA pre-charged Extended Service Interval
(ESI) Technology product which is compatible with
any conventional heavy duty coolants and all filter
technologies. **Prestone Command HD 50/50 Prediluted
SCA Antifreeze/Coolant** is a blend of antifreeze/coolant

and demineralized water designed for use in ANY Heavy Duty
Engines used in normal to severe duty cycles and extreme
temperature conditions. This product will provide complete
protection against freezing, overheating, cavitation erosion,
corrosion, scale and foaming with just an easy pour and does not require
SCA's in the initial fill. For flush and fill use **Prestone Command HD
concentrate.**

In Compliance with TMC RP329

Specifications and Performance: **Prestone Command HD 50/50
Prediluted SCA Antifreeze/Coolant** meets or exceeds performance
requirements of the major engine manufacturer's and the following specifications
• **TMC RP329 • ASTM D6210 • ASTM D4985 • ASTM D3306 • SAE J1941**

PROTECTION	FREEZE-UP Protection	BOIL-OVER Protection†	CORROSION Protection
Prestone Command HD Prediluted 50/50	- 34° F	+265° F	Meets or exceeds ASTM D3306, ASTM D4985, ASTM D6210

† Using a 15 lb. pressure cap in good condition.

WARNING: CONTAINS ETHYLENE GLYCOL (107-21-1), DIETHYLENE
GLYCOL (111-46-6), WATER (7732-18-5) AND PROPRIETARY INHIBITORS.

**DO NOT DRINK ANTIFREEZE OR SOLUTION. DO NOT STORE IN OPEN OR
UNLABELED CONTAINERS. AVOID CONTACT WITH EYE, SKIN AND CLOTHING.
WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING VAPORS OR
MISTS. SOLUTION IS POISONOUS TO ANIMALS. CONTAINS ETHYLENE
GLYCOL AND DIETHYLENE GLYCOL. IF SWALLOWED, CALL A POISON
CENTER OR GO TO A HOSPITAL EMERGENCY ROOM IMMEDIATELY. IF
INHALED, MOVE TO FRESH AIR. SEEK MEDICAL ATTENTION IF SYMPTOMS
PERSIST. IN CASE OF CONTACT, WASH WITH WATER.**

KEEP OUT OF REACH OF CHILDREN

ADVERTENCIA: CONTIENE ETILENGLICOL (107-21-1),
DIETILENGLICOL (111-46-6), AGUA (7732-18-5) E INHIBIDORES PATENTADOS.

**NO BEBA LA SOLUCIÓN ANTICONGELANTE. NO ALMACENE EN ENVASES
ABIERTOS O SIN ETIQUETA. EVITE EL CONTACTO CON LOS OJOS, LA PIEL Y
LA ROPA. LÁVESE BIEN DESPUÉS DE MANIPULARLO. EVITE RESPIRAR LOS
VAPORES O ROCÍOS. LA SOLUCIÓN ES TÓXICA PARA LOS ANIMALES.
CONTIENE ETILENGLICOL Y DIETILENGLICOL. SI SE INGIERE, LLAME A UN
CENTRO DE CONTROL DE ENVENENAMIENTOS O VAYA A LA SALA DE
EMERGENCIA DE UN HOSPITAL INMEDIATAMENTE. SI SE INHALA,
SALGA AL AIRE FRESCO. OBTENGA ATENCIÓN MÉDICA SI LOS SÍNTOMAS
PERSISTEN. EN CASO DE CONTACTO, LAVE CON AGUA.**

MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.

**HEAVY DUTY 50/50 PREDILUTED
SCA PRE-CHARGED
ANTIFREEZE/COOLANT**

CAUTION: Do not remove cooling system cap while cooling system is hot.
Do not store antifreeze/coolant in open or unlabeled containers. After use,
tighten child resistant cap and wash exposed skin with soap and water.

DO NOT ADD WATER

DIRECTIONS: Check the specific maintenance and changeover intervals,
antifreeze/coolant to water ratio, cooling system capacity, and service
instructions recommended for your vehicle.

TOP OFF - Check engine coolant level frequently and top off with **Prestone
Command® HD 50/50 Prediluted SCA** antifreeze/coolant as needed.
When Flushing and Filling your cooling system use Prestone Command HD
SCA Concentrate.

Periodically check SCA level. Add maintenance SCA's according to
manufacturer's recommendation.



For more information, scan this
code or visit our website
WWW.PRESTONECOMMAND.COM

Mixing Coolant Technology: Diluting the antifreeze/coolant in your
cooling system with different coolant technologies has the potential of
reducing protection levels. Refer to engine manufacturer or TMC (RP338A
and RP362) for recommendations.

**DISPOSING OF USED ANTIFREEZE/COOLANT: Dispose of contents
and container in accordance with local and national regulations.**

Para instrucciones en español, visite www.PrestoneCommand.com

WARNING: Reproductive Harm - www.P65Warnings.ca.gov
ADVERTENCIA: Daño Reproductivo - www.P65Warnings.ca.gov



Recyclable Bottle
This bottle may
not be recyclable
in your area

PRESTONE PRODUCTS CORPORATION
69 Eagle Road, Danbury, CT 06810
AFC10100 P-6099 SDS 650

Visit WWW.PRESTONECOMMAND.COM
Questions? Call 1-888-269-0750
©2018 Prestone Products Corporation
Made in the U.S.A. with domestic and imported materials
Patents: Prestone.com/patents