



# HEAVY DUTY PREDILUTED ANTIFREEZE/COOLANT 50/50

PATENTED FORMULA  
**NITRITE FREE**  
with  
**EXTENDED LIFE**  
TECHNOLOGY  
**DO NOT ADD WATER**

MEETS PERFORMANCE REQUIREMENTS OF: ASTM D-3306, ASTM D-6210, ASTM D-7583

**ATTENTION:** EMPTIED CONTAINER RETAINS VAPOR AND PRODUCT RESIDUE, OBEY ALL LABEL WARNINGS. DO NOT CUT OR WELD ON OR NEAR THE CONTAINER. DO NOT REUSE UNLESS THOROUGHLY CLEANED.

BEFORE USING, READ AND UNDERSTAND THE CURRENT PRESTONE PRODUCTS CORPORATION SAFETY DATA SHEET FOR THIS PRODUCT.  
**SDS 672**

## 55 GALLONS

PRODUCT CODE

## AFC12100-55/F

DISTRIBUTED BY:  
PRESTONE PRODUCTS CORPORATION  
69 Eagle Road, Danbury, CT 06810  
1-888-269-0750

**P-6608**

**WARNING!** HARMFUL IF SWALLOWED. SUSPECTED OF DAMAGING THE UNBORN CHILD. MAY CAUSE DAMAGE TO KIDNEYS THROUGH PROLONGED OR REPEATED EXPOSURE.

**PREVENTION:** OBTAIN SPECIAL INSTRUCTIONS BEFORE USE. DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. DO NOT BREATHE MIST OR VAPORS. WASH EXPOSED SKIN THOROUGHLY AFTER HANDLING. DO NOT EAT, DRINK, OR SMOKE WHEN USING THIS PRODUCT. WEAR PROTECTIVE GLOVES AND EYE PROTECTION.

**RESPONSE:** IF SWALLOWED: CALL A POISON CENTER OR PHYSICIAN IF YOU FEEL UNWELL. RINSE MOUTH. IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE.

**DISPOSAL:** STORE LOCKED UP. DISPOSE OF CONTENTS AND CONTAINER IN ACCORDANCE WITH LOCAL AND NATIONAL REGULATIONS.



**CONTAINS:** Water (7732-18-5), Ethylene Glycol (107-21-1), Diethylene Glycol (111-46-6), 2-Ethyl Hexanoic Acid, Sodium Salt (19766-89-3)

**SUPPLEMENTAL LABELING:** SUDDEN RELEASE OF HOT ORGANIC CHEMICAL VAPORS OR MISTS FROM PROCESS EQUIPMENT OPERATING AT ELEVATED TEMPERATURE AND PRESSURE, OR SUDDEN INGRESS OF AIR INTO VACUUM EQUIPMENT, MAY RESULT IN IGNITIONS WITHOUT ANY OBVIOUS SOURCES OF IGNITION. PUBLISHED "AUTOIGNITION" OR "IGNITION" TEMPERATURES CANNOT BE TREATED AS SAFE OPERATING TEMPERATURES IN CHEMICAL PROCESSES WITHOUT ANALYSIS OF THE ACTUAL PROCESS CONDITIONS. USE OF THIS PRODUCT IN ELEVATED TEMPERATURE APPLICATIONS SHOULD BE THOROUGHLY EVALUATED TO ASSURE SAFE OPERATING CONDITIONS.

**FIRST AID: INHALATION:** REMOVE THE VICTIM TO FRESH AIR. IF BREATHING HAS STOPPED ADMINISTER ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, HAVE MEDICAL PERSONNEL ADMINISTER OXYGEN. GET MEDICAL ATTENTION.

**SKIN CONTACT:** REMOVE CONTAMINATED CLOTHING. IMMEDIATELY WASH CONTACTED AREA THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.

**EYE CONTACT:** IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

**INGESTION:** SEEK IMMEDIATE MEDICAL ATTENTION. IMMEDIATELY CALL LOCAL POISON CONTROL CENTER OR GO TO AN EMERGENCY DEPARTMENT. NEVER GIVE ANYTHING BY MOUTH TO OR INDUCE VOMITING IN AN UNCONSCIOUS OR DROWSY PERSON. BEFORE USING CONSULT THE PRESTONE PRODUCTS CORPORATION SAFETY DATA SHEET FOR THIS PRODUCT.

**WARNING:** Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

PROTECTION	FREEZE-UP Protection	BOILOVER Protection†	CORROSION Protection
Prestone Command HD Nitrite Free Prediluted 50/50 ELC	- 34° F	+265° F	Meets or exceeds ASTM D-3306, ASTM D-6210 and ASTM D-7583

† Using a 15 lb. pressure cap in good condition.

**DISPOSAL OF USED ANTIFREEZE/COOLANT: OBSERVE LOCAL LAWS AND REGULATIONS. DO NOT DRAIN ONTO THE GROUND OR INTO STORM DRAINAGE SYSTEMS.**



7 97496 87912 7